\ \ \ \ \ DISTRIC PHASE


PLANT UPGRADE WATER AND

TREATMENT SEWER **EASTSOUND** WASTEWATER


6 00 P

WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2

# AREA MAP- NOT TO SCALE



# VICINITY MAP- NOT TO SCALE



### INDEX TO DRAWINGS

/ER SHEET	0.1 COVER SHEET	Ĺ
-----------	-----------------	---

- G0.2 LEGEND & ABBREVIATIONS CIVIL & ARCHITECTURAL G0.3 NOTES & SPECIFICATIONS
- G0.4 W.A.C. 332-130 COMPLIANCE SHEET G0.5 PROCESS SCHEMATIC
- G0.6 PROCESS AREA DESIGNATIONS GO 7 HYDRAULIC PROFILE
- G0.8 DESIGN CRITERIA
- G0.9 DEWATERING BUILDING WSEC COMPLIANCE
- CO.1 EXISTING CONDITIONS CO.2 EXISTING CONDITIONS
- CO.3 T.E.S.C. NARRATIVE
- CO.4 T.E.S.C. SITE PLAN CO.5 DEMOLITION PLAN
- CO.6 MANHOLE REPLACEMENT TESC & DEMO PLAN CO.7 TESC DETAILS
- CO.8 STAGING PLAN
  CO.9 WWTP INTERIM PLAN OF OPERATION
- SITE PIPING PLAN WITH GENERAL NOTES
- SITE DIMENSIONAL PLAN C1.3 SITE PIPING PLAN WITH PIPING & VALVE ID
- C1.4 SITE PIPING PLAN WITH PIPE ELEVATIONS
- C1.5 INFLUENT DISCHARGE PORT & SLUDGE BOX PLAN
  C1.6 INFLUENT DISCHARGE PORT & SLUDGE BOX PROFILE
- SEPTAGE POLYTANK PIPING PLAN & PROFILE
- TRAIN 1 AFRATION PIPING PLAN & PROFILE
- C2.1 GRADING & STORM DRAINAGE PLAN C2.2 SURFACING PLAN

- TRAIN 1 PLAN
- TRAIN 1 SECTION A C3.3 TRAIN 1 SECTION B
- TRAIN 2 PLAN
- TRAIN 2 SECTION A
- C3.6 TRAIN 2 SECTION B
- INFLUENT PUMP STATION MODIFICATION
- C4.2 DEWATER SUMP PUMP STATION UPGRADE
- C5.2 SLUDGE BOX DETAILS
  C5.3 BIOSOLIDS HANDLING SECTION
- C5.4 BIOSOLIDS HANDLING SECTION
  C5.5 SLUDGE BOX PIPING PROFILE
- C6.1 CIVIL DETAILS
- C6.2 CIVIL DETAILS
- C6.3 CIVIL DETAILS CIVIL DETAILS
- C6.5 CIVIL DETAILS
- C7.1 DEWATERING BUILDING & EQUIPMENT LAYOUT

- A1.2 DEWATERING BUILDING EXTERIOR ELEVATIONS A1.3 DEWATERING BUILDING INTERIOR ELEVATIONS
- A1.4 DEWATERING BUILDING EQUIPMENT PROTECTION PLAN

# CONTACT INFORMATION

WILSON ENGINEERING LLC IEFF CHRISTNER. PE & MATTHEW STRITTMATTER. PE PHONE 360,733,6100

EASTSOUND SEWER AND WATER DISTRICT IASON BRADSHAW, GENERAL MANAGER



# PROJECT DATUM

HORIZONTAL: NAD 83/91

# VERTICAL: NGVD 1929

# INDEX TO DRAWINGS (CONTINUED)

- A2.1 EXISTING LAB INTERIOR
- A2.2 PROPOSED LAB INTERIOR IMPROVEMENTS A2.3 LAB SCHEDULES & TYPES
- H0.1 MECHANICAL LEGEND. ABBREVIATIONS, AND GENERAL NOTES
- H1.0 DEWATERING BUILDING MECHANICAL PLAN
- H2.0 MECHANICAL SECTIONS
- S1.1 STRUCTURAL NOTES
- S2.1 DEWATERING BUILDING FOUNDATION & ROOF FRAMING PLANS S2.2 DEWATERING BUILDING DETAILS

- TYP STRUCTURAL DETAILS
- E0.1 ELECTRICAL SYMBOLS AND ABBREVIATIONS E0.2 ELECTRICAL DEMOLITION SITE PLAN
- E0.3 AREA CLASSIFICATION SITE PLAN E0.4 PROCESS AREA ELECTRICAL PLAN
- E0.5 ELECTRICAL SITE PLAN
- E1.1 DEWATERING BUILDING POWER AND CONTROL PLAN
- DEWATERING BUILDING HVAC ELECTRICAL PLAN
- E1.3 DEWATERING BUILDING LIGHTING PLAN
  E2.1 LABORATORY ELECTRICAL PLAN AND SCHEDULES
- TRAINS NO.1 AND 2 ELECTRICAL PLAN AND ELEVATION TRAINS NO.1 AND 2 - INTERCONNECTION DIAGRAM
- ELECTRICAL ONE LINE DIAGRAM
- F6.1 CONDUIT AND CONDUCTOR SCHEDULES
- F7.0 CONTROL SYSTEM OVERVIEW
- E7.1 DEWATERING BUILDING PLC CONTROL PANEL ELEVATION
- E7.2 DEWATERING BUILDING PLC CONTROL PANEL POWER WIRING DIAGRAM
  E7.3 DEWATERING BUILDING PLC CONTROL PANEL DIGITAL INPUTS
- E7.4 DEWATERING BUILDING PLC CONTROL PANEL DIGITAL OUTPUTS
  E7.5 DEWATERING BUILDING PLC CONTROL PANEL ANALOG INPUTS SHEET 1
- E7.6 DEWATERING BUILDING PLC CONTROL PANEL ANALOG INPUTS SHEET 2
- E7.7 DEWATERING BUILDING PLC CONTROL PANEL ANALOG INPUTS SHEET 3
- E7.8 DEWATERING BUILDING PLC CONTROL PANEL ANALOG OUTPUTS
- E8.1 DEWATERING BUILDING VENTILATION CONTROL PANEL
  E8.2 DEWATERING SUMP PUMP STARTER WIRING DIAGRAM
- E9.1 ELECTRICAL DETAILS

# PROTECTION OF THE ENVIRONMENT


NO CONSTRUCTION—RELATED ACTIVITY SHALL CONTRIBUTE TO THE DEGRADATION OF THE ENVIRONMENT, ALLOW MATERIAL TO ENTER SURFACE OR GROUND WATERS, OR ALLOW PARTICULATE EMISSIONS TO THE ATMOSPHERE, WHICH EXCEED STATE OR FEDERAL STANDARDS. ANY ACTIONS THAT POTENTIALLY ALLOW A DISCHARGE TO STATE WATERS MUST HAVE PRIOR APPROVAL OF THE WASHINGTON STATE DEPARTMENT OF ECOLOGY.

# PROJECT FUNDING INFORMATION

ECOLOGY SRF FUNDING NO. WQC-2023-EaSoWD

THIS PROJECT IS FUNDED IN PART BY THE WASHINGTON STATE DEPARTMENT OF ECOLOGY





AND

SEWER

 $\infty$ 

00

. O

P

# **NOTES & SPECIFICATIONS**

# GENERAL NOTES

- THE CONTRACTOR SHALL COORDINATE WITH EASTSOUND SEWER AND WATER DISTRICT ON ALL CHANGES TO EXISTING WASTEWATER FACILITY OPERATIONS. IT IS ESSENTIAL THAT EASTSOUND SEWER AND WATER DISTRICT OPERATIONS ARE NOT INTERRUPTED BY
- CONTRACTOR AGREES THAT HE SHALL ASSUME SOLE AND COMPLETE RESPONSIBILITY FOR JOB SITE CONDITIONS DURING THE COURSE OF CONSTRUCTION OF THIS PROJECT, INCLUDING SAFETY OF ALL PERSONS AND PROPERTY, THAT THIS REQUIREMENT SHALL APPLY CONTINUOUSLY AND NOT BE LIMITED TO NORMAL WORKING HOURS, AND THAT THE CONTRACTOR SHALL DEFEND, INDEMNIFY, AND HOLD THE EASTSOUND SEWER AND WATER DISTRICT AND THE ENGINEER HARMLESS FROM ANY AND ALL LIABILITY. REAL OR ALLEGED. IN CONNECTION WITH THE PERFORMANCE OF WORK ON THIS PROJECT, EXCEPTING FOR LIABILITY ARISING FROM THE SOLE NEGLIGENCE OF THE EASTSOUND WATER AND SEWER DISTRICT OR THE ENGINEER.
- IF THERE ARE ANY DISCREPANCIES BETWEEN DIMENSIONS IN DRAWING AND EXISTING CONDITIONS WHICH WILL AFFECT THE WORK, THE CONTRACTOR SHALL BRING SUCH DISCREPANCIES TO THE ATTENTION OF THE ENGINEER FOR ADJUSTMENT BEFORE PROCEEDING WITH THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE PROPER FITTING OF ALL WORK AND FOR THE COORDINATION OF ALL TRADES, SUBCONTRACTORS, AND PERSONS ENGAGED UPON THIS CONTRACT.
- CONTRACTOR SHALL BE RESPONSIBLE TO REPAIR OR REPLACE ANY EXISTING IMPROVEMENTS OR UNDERGROUND FACILITIES DAMAGED BY HIM, HIS SUBCONTRACTORS, OR HIS MATERIAL SUPPLIERS WITHIN 48 HOURS OF THE DAMAGE OCCURRENCE AND/OR AS REQUIRED BY THE
- EXISTING UTILITIES AND UNDERGROUND FACILITIES INDICATED ARE FOR INFORMATION ONLY. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THE LOCATION AND DEPTH. NEITHER THE EASTSOUND SEWER AND WATER DISTRICT NOR THE ENGINEER ASSUMES RESPONSIBILITY THAT THE UTILITIES AND UNDERGROUND FACILITIES INDICATED WILL BE THE UTILITIES AND UNDERGROUND FACILITIES
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THE ELEVATIONS OF THE EXISTING STORM DRAINS, SEWERS, AND WATER TO BE EXTENDED, CROSSED, OR CONNECTED TO PRIOR TO COMMENCING THE WORK. NOTIFY ENGINEER IF ACTUAL IS DIFFERENT FROM PLANS.
- ALL TRENCHES AND EXCAVATIONS SHALL BE CONSTRUCTED IN STRICT COMPLIANCE WITH THE APPLICABLE SECTIONS OF FEDERAL OSHA REQUIREMENTS AND OTHER APPLICABLE SAFETY ORDINANCES. CONTRACTOR SHALL BEAR FULL RESPONSIBILITY FOR TRENCH SHORING
- THE CONTRACTOR IS RESPONSIBLE FOR MATCHING EXISTING STREETS, SURROUNDING LANDSCAPE, AND OTHER IMPROVEMENTS WITH A SMOOTH TRANSITION IN PAVING, CURBS, GUTTERS, SIDEWALKS, GRADING, ETC, AND TO AVOID ANY ABRUPT OR APPARENT CHANGES IN GRADES OR CROSS SLOPES, LOW SPOTS, OR HAZARDOUS CONDITIONS.
- A 1-WEEK NOTIFICATION TO THE EASTSOUND SEWER AND WATER DISTRICT IS REQUIRED PRIOR TO ANY UTILITY SERVICE DISRUPTION. CONTRACTOR MUST PROVIDE TEMPORARY EQUIPMENT (POWER GENERATOR, PUMPS, PIPING, ETC) AND AN APPROVED PLAN FOR ALL WASTEWATER TREATMENT PLANT DISRUPTIONS. SEE SUMMARY OF WORK (SPECIFICATION SECTION 01 11 00.
- ALL APPROVALS AND PERMITS REQUIRED BY SAN JUAN COUNTY SHALL BE OBTAINED BY THE CONTRACTOR PRIOR TO THE START OF

ALL SITE EARTH WORK, CONCRETE WORK, AND ASPHALT PAVEMENT REPAIR TO BE PRIORITIZED DURING DRY WEATHER MONTHS.

# SURVEY MONUMENTATION:

CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR OBTAINING PERMITS FROM THE WASHINGTON STATE DEPARTMENT OF NATURAL RESOURCES FOR REMOVING AND REPLACING ALL SURVEY MONUMENTATION THAT MAY BE AFFECTED BY CONSTRUCTION ACTIVITY, PURSUANT TO WAC 332–120. APPLICATIONS MUST BE COMPLETED BY A REGISTERED LAND SURVEYOR. APPLICATIONS FOR PERMITS TO REMOVE MONUMENTS MAY BE OBTAINED FROM THE WASHINGTON STATE DEPARTMENT OF NATURAL RESOURCES (DNR), OR BY CONTACTING THEIR OFFICE BY TELEPHONE AT (206) 902-1190.

WASHINGTON STATE DEPARTMENT OF NATURAL RESOURCES PUBLIC LAND SURVEY OFFICE

1111 WASHINGTON STREET S.E.

UPON COMPLETION OF CONSTRUCTION, ALL MONUMENTS DISPLACED, REMOVED, OR DESTROYED SHALL BE REPLACED BY A REGISTERED LAND SURVEYOR. AT THE COST OF THE CONTRACTOR, PURSUANT TO THESE REGULATIONS. THE APPROPRIATE FORMS FOR REPLACEMENT OF SAID MONUMENTS SHALL BE COMPLETED AND FILED WITH DNR AT THE CONTRACTOR'S EXPENSE.

# CONSTRUCTION INSPECTIONS:

CONTRACTOR MUST COORDINATE REQUIRED INSPECTIONS WITH THE COUNTY BUILDING INSPECTION OFFICIALS. IN ADDITION, CONTRACTOR IS TO PROVIDE OWNER AND ENGINEER 24-HOUR (MINIMUM) NOTICE FOR SCHEDULED INSPECTIONS. REQUIRED INSPECTIONS INCLUDE THE FOLLOWING ITEMS:

- BUILDING FOOTINGS
- CONCRETE STRUCTURES WELDING INSPECTIONS
- FINAL OVERALL INSPECTION

CONTRACTOR MUST PROVIDE OWNER AND ENGINEER 24-HOUR (MINIMUM) NOTICE FOR ALL SPECIAL INSPECTIONS IDENTIFIED ON \$1.1 SPECIAL INSPECTIONS, TESTING, AND STRUCTURAL OBSERVATIONS.

# GENERAL NOTES, CONT.

# PROTECTION OF THE ENVIRONMENT

NO CONSTRUCTION RELATED ACTIVITY SHALL CONTRIBUTE TO THE DEGRADATION OF THE ENVIRONMENT, ALLOW MATERIAL TO ENTER SURFACE OR GROUND WATERS, OR ALLOW PARTICULATE EMISSIONS TO THE ATMOSPHERE, WHICH EXCEED STATE OR FEDERAL STANDARDS. ANY ACTIONS THAT POTENTIALLY ALLOW A DISCHARGE TO STATE WATERS MUST HAVE PRIOR APPROVAL OF THE STATE OF WASHINGTON, DEPARTMENT OF

# **OPERATION PLAN**

# WWTP UGRADE CONSTRUCTION - GENERAL NOTES

- THE EXISTING WASTEWATER TREATMENT PLANT (WWTP) SHALL NOT BE INTERRUPTED DURING CONSTRUCTION EXCEPT AS DESCRIBED BELOW. THE CONTRACTOR SHALL BE RESPONSIBLE FOR SEQUENCING CONSTRUCTION ACTIVITIES SO THAT NO INTERRUPTION OCCURS.
- THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING ALL TEMPORARY BY-PASS PUMPING, PIPING, HOLDING TANKS AND ADDITIONAL STORAGE NECESSARY TO KEEP SEWER AND WWTP SYSTEM UNINTERRUPTED
- THE PLAN ASSUMES THAT ALL BASIN, BUILDINGS, FOUIPMENT, AND PIPING WILL BE INSTALLED/TESTED AND READY TO BE CONNECTED PRIOR TO SWITCH-OVER. THIS IS A SUGGESTED PLAN AND DOES NOT RELIEVE THE CONTRACTOR FROM OBLIGATIONS TO AVOID INTERRUPTION. SEE SHEET CO.9 FOR THE INTERIM PLAN OF
- EMERGENCY CONTACTS:


ESWD: JASON BRADSHAW, GENERAL MANAGER, CELL: 620-441-4006 WILSON ENG: IEFF CHRISTNER, PROIECT ENGINEER, CELL: 360-303-5129



# EASTSOUND SEWER AND WATER DISTRICT

# WASTEWATER TREATMENT PLANT DESIGN W.A.C. 332-130 COMPLIANCE SHEET

# SECTIONAL INDEX DATA



NW QTR - SE QTR, SEC. 11, TWNSHP 37 NORTH, R 2 WEST, W.M.

### NOTICE TO USER

EFFECTIVE JANUARY 13, 2019, ALL TOPOGRAPHIC MAPS PREPARED BY A LICENSED SURVEYOR IN THE STATE OF WASHINGTON, AND SUBJECT TO THE LICENSURE AND PRACTICE REQUIREMENTS ESTABLISHED BY THE WASHINGTON STATE BOARD OF REGISTRATION FOR ENGINEERS AND LAND SURVEYORS, MUST INCLUDE THE DESCRIPTIVE NOTES AND METADATA FINIMERATED LINDER W. A.C. 332-130-145 AND ITS APPLIETENANT SECTIONS OF 332-130. THIS EXHIBIT IS INTENDED TO ADDRESS THE STATUTORY REQUIREMENTS STIPULATED BY THIS W.A.C DIRECTIVE.

# W.A.C. 332-130-145 REQUIRED DATA

1.E: THIS SURVEY WAS PREPARED UNDER THE DIRECT SUPERVISION OF:

PAUL J. DARROW, WA PLS #50697 WILSON ENGINEERING LLC 805 DUPONT STREET, SUITE 7 BELLINGHAM, WA 98225 360-733-6100 (EXT. 243)

- 2.A: BASIS OF ELEVATIONS: ELEVATION VALUES AND CONTOURS DEPICTED ON THIS SURVEY ARE BASED UPON HOLDING AS FIXED THE NGVD29 DATUM, PER BENCHMARK NO. 20 RLM, ACCORDING TO THE PERPETUATION OF SAN JUAN COUNTY BENCHMARK #00165, HAVING AN ELEVATION OF 34.28, PER LAND CORNER RECORD # 2000 0303018.
- 2.B: PURPOSE OF SURVEY: WILSON ENGINEERING PERFORMED THIS SURVEY DURING JANUARY OF 2013 WITH ADDITIONAL DATA AND CHANGES BEING SURVEYED IN MARCH OF 2021, JULY, SEPTEMBER AND NOVEMBER OF 2024 AT THE REQUEST OF EASTSOUND SEWER AND WATER DISTRICT PURSUANT TO WASTEWATER TREATMENT PLANT UPGRADE DESIGN. THIS SURVEY WAS PREPARED WITH THE BENEFIT OF A TITLE REPORT, AND THE DEPICTED PARCEL BOUNDARY SHOULD BE CONSIDERED.
- 2.C: SOURCE OF CONTOURS: THE CONTOURS DEPICTED ON THIS SURVEY WERE DERIVED BASED ON DIRECT FIELD OBSERVATIONS .
- 2.D: <u>CONTOUR INTERVAL LABELING:</u> MAJOR CONTOURS AT 1-FOOT INTERVALS HAVE BEEN EXPLICITLY LABELED.
- 2.E: DESCRIPTION OF BENCHMARKS SET PURSUANT TO THIS SURVEY: REFER TO THE ACCOMPANYING "CONTROL TABLE" FOR COORDINATES, ELEVATION, AND DESCRIPTION OF ON-SITE CONTROL SET PURSUANT TO THIS SURVEY.
- 2.F: ELEVATION AND/OR CONTOUR ACCURACY: IF CONTOURS HAVE BEEN DEPICTED ON THE FACE OF THIS SURVEY, IT IS ANTICIPATED THAT 90% OF ANY MEASURED ELEVATION VALUE, IF OBSERVED RELATIVE TO THE CONTROL POINTS SPECIFICALLY ENUMERATED IN THE ACCOMPANYING CONTROL TABLE, WILL BE, IN FACT, WITHIN ONE-HALF OF THE MINOR-CONTOUR INTERVAL DEPICTED HEREON. SPECIFIC ELEVATIONS DEPICTED HEREON, IF ANY, ARE EXPECTED TO BE WITHIN ONE INTEGRAL VALUE OF THE FINAL DEPICTED SIGNIFICANT FIGURE. THAT IS, 90% OF ELEVATIONS EXPRESSED TO THE TENTH-FOOT, SHOULD BE WITHIN 0.1 FEET OF THAT VALUE, IF ORSERVED RELATIVE TO THE SURVEY CONTROL SPECIFICALLY ENLIMERATED IN THE ACCOMPANYING CONTROL TABLE. IF OFF-SITE CONTROL IS EMPLOYED, EVEN CONTROL PURPORTING TO BE ON THE SAME DATUM OR BASED ON THE SAME OFF-SITE BENCHMARK, THEN NO ABSOLUTE STATEMENT REGARDING THE ACCURACY OF THE DEPICTED POINTS CAN BE MADE, AND VALUES SO OBSERVED ARE OUTSIDE OF THIS SURVEY'S AUTHORITY OR INTEREST.
- 2.G: STATEMENT OF USE: AS NOTED IN SECTION 2.B, THIS SURVEY WAS PREPARED FOR THE SPECIFIC PURPOSE OF WASTEWATER TREATMENT PLAN UPGRADE DESIGN. IN THE COURSE OF PREPARING THIS SURVEY, PURSUANT TO THIS PURPOSE, ANCILLARY DATA NECESSARY TO ACCOMPLISH THIS SURVEYS INTENDED PURPOSE MAY HAVE BEEN CAPTURED. IN THE CASE OF THIS SURVEY A NUMBER OF BUILDING ENVELOPES ON ADJACENT PARCELS WERE CAPTURED, BUT THE DEPICTION OF SAME SHOULD NOT BE CONSIDERED AUTHORITATIVE.
- 2.H: SOURCE OF CONTROLLING BOUNDARY INFORMATION: THE OWNERSHIP BOUNDARIES DEPICTED ON THIS SURVEY ARE BASED UPON SOME, OR ALL, OF THE DOCUMENTS ENUMERATED IN THE ACCOMPANYING "REFERENCE DOCUMENTS" AS THEREIN CHARACTERIZED. BEARINGS HAVE BEEN TRANSLATED AND/OR ROTATED FROM THE RECORD VALUES TO CONFORM WITH THE CURRENT DATUM OF THIS
- 3.A: SOURCE OF DEPICTED UTILITY INFORMATION: UTILITY LINES DEPICTED ON THIS SURVEY ARE BASED UPON DIRECT OBSERVATION OF SURFACE VISIBLE STRUCTURES AND LOCATE MARKS MADE BY UTILITY LOCATING PROFESSIONALS.
- 3.B: ACCURACY OF DEPICTED UTILITY INFORMATION: WILSON ENGINEERING DOES NOT PROVIDE FOR-HIRE UTILITY LOCATION AND/OR MARKING SERVICES, AND CAN NOT INDEPENDENTLY ASCERTAIN THE ACCURACY OF ANY DEPICTED UTILITY THAT WAS NOT DIRECTLY OBSERVED IN THE COURSE OF THIS SURVEY.
- 3.C: STATEMENT OF LIMITATIONS REGARDING UTILITY-DEPICTION ACCURACY:
  EASTSOUND SEWER AND WATER DISTRICT HAS BEEN NOTIFIED THAT WILSON CAN
  NOT, AND DOES NOT, GUARANTEE THE ACCURACY, AT ANY LEVEL, OF DEPICTED UTILITIES BASED ON THIRD-PARTY PAINT MARKS OR RECORD INFORMATION

# CONTROL NOTES

HORIZONTAL DATUM: BASIS OF COORDINATES, BEARINGS AND CALCULATIONS ARE NAD 83/91 WASHINGTON STATE PLANE NORTH ZONE BASED ON TIES TO MONUMENTS AS SHOWN PER RECORD OF SURVEY ON FILE IN BOOK 16 OF SURVEYS AT PAGE 99, RECORDS

BASIS OF COORDINATES: COORDINATION AND MENSURATION ARE LOCAL GROUND VALUES, BASED, UPON HOLDING THE PUBLISHED NAD83/91 POSITION FOR THE 3" BRASS DISC IN CASE AT PROJECTED CENTERLINE OF MT. BAKER ROAD, SOUTH OF THE AIRPORT CENTER BUILDING. DISC BEARS THE STAMP "SAN JUAN COUNTY SURVEY CONTROL MONUMENT 00165". SAID MONUMENT HAS THE FOLLOWING PUBLISHED POSITION

NORTHING = 628,007.20 EASTING = 1,138,590.22 USFT

BASIS OF BEARINGS: BEARINGS ARE BASED UPON HOLDING THE CALCULATED INVERSE BETWEEN SAN JUAN COUNTY MONUMENTS "00165" AND THE BRASS DISK PRESUMED TO BE THAT MONUMENT MARKING THE E 16TH CORNER BETWEEN SECTIONS 11 AND 14, PER THE AFOREMENTIONED RECORD OF SURVEY, SAID INVERSE BEING S 88° 16' 54" E. AT A DISTANCE OF 1301.67' (GRID). THE PUBLISHED WASHINGTON STATE PLANE (NORTH ZONE) VALUES FOR THE 16TH-CORNER MONUMENT ARE AS FOLLOWS:

NORTHING = 627,968.17 USFT EASTING = 1,139,891.30

# VERTICAL DATUM

BASIS OF ELEVATIONS: ELEVATIONS SHOWN ON THIS SURVEY ARE BASED ON THE USGS BENCH MARK DESIGNATED 20 RLM (BRASS DISC IN CONCRETE) AT THE SOUTH END OF THE RUNWAY AT ORCAS ISLAND AIRPORT, HAVING AN ELEVATION OF 31.0 FEET (NGVD 29), PER THE PERPETUATION OF SAN IUAN COUNTY BENCHMARK #00165, HAVING AN ELEVATION OF 34.28, PER LAND CORNER RECORD #2000 0303018.

# ON-SITE SURVEY CONTROL TABLE

POINT	NORTHING	EASTING	ELEVATION	DESCRIPTION
118	629,614.54	1,139,264.69	22.84	MAG NAIL
122	629,609.13	1,139,450.50	24.93	MAG NAIL
205	629,477.19	1,139,257.92	23.74	REBAR AND PLASTIC CAP

# SURVEYOR'S CERTIFICATE

HEREBY CERTIFY THAT I AM A LICENSED LAND SURVEYOR IN THE STATE OF WASHINGTON THAT THIS MAP IS BASED ON AN ACTUAL FIELD SURVEY DONE BY ME OR UNDER MY DIRECT SUPERVISION AND THAT ALL DATA SHOWN HEREON ACTUALLY EXISTS IN THE LOCATIONS SHOWN AT THE TIME OF THIS SURVEY. THIS TOPOGRAPHIC MAP WAS DONE AT THE REQUEST OF EASTSOUND SEWER AND WATER DISTRICT IN 2021 AND AMENDED IN 2024.



# LEGAL DESCRIPTION PER AFN, 2021-1022007

THE NORTH 144 FEET OF THE WEST 148 FEET OF THE SOUTH HALF OF THE SOUTHEAST QUARTER OF THE NORTHWEST QUARTER OF THE SOUTHEAST QUARTER OF SECTION 11, TOWNSHIP 37 NORTH, RANGE 2 WEST, W.M., IN SAN JUAN COUNTY, WASHINGTON.

TOGETHER WITH THE SOUTH 10 FEET OF THE NORTH 154 FEET OF THE EAST 112 FEET OF THE WEST 148 FEET OF THE SOUTH HALF OF THE SOUTHEAST QUARTER OF THE NORTHWEST QUARTER OF THE UTHEAST QUARTER OF SECTION 11, TOWNSHIP 37 NORTH, RANGE 2 WEST, W.M., IN SAN JUAN

### RECORD DOCUMENTS

- BOOK 3, PAGE 61 PLAT OF SURVEY FOR EASTSOUND WATER DISTRICT
- BOOK 18 PAGE 131 RECORD OF SURVEY FOR PORT OF ORCAS
- BOOK 16, PAGE 99 RECORD OF SURVEY FOR SAN JUAN COUNTY

# SURVEYOR'S NOTES

- 1. THIS TOPOGRAPHIC SURVEY WAS ORIGINALLY PERFORMED IN JANUARY 2013. ADDITIONAL DATA WAS SURVEYED IN MARCH 2021 AND JULY, SEPTEMBER AND NOVEMBER OF 2024. ALL MONUMENTS SHOWN HEREON WERE VISITED DURING THE COURSE OF THIS SURVEY LINESS. OTHERWISE NOTED. THIS SURVEY CORRECTLY SHOWS THE AREA OF THE SUBJECT PROPERTY AND THE LOCATION OF ALL STRUCTURES AND IMPROVEMENTS SITUATED ON THE SUBJECT
- 2. ANGULAR AND LINEAR MEASUREMENTS WERE COLLECTED USING A COMBINATION OF GPS AND CONVENTIONAL METHODOLOGIES. PRIMARY CONTROL WAS COLLECTED USING TRIMBLE 5700 SURVEY-GRADE GPS RECEIVERS OPERATING IN NETWORKED RTK MODE, FROM GPS CONTROL, A TRIMBLE 57 ROBOTIC TOTAL STATION WAS USED TO TIE SECONDARY CONTROL POINTS, COLLECT TOPOGRAPHIC DATA AND MEASURE LOT CORNERS.
- 3. THE LOCATION OF UTILITIES SHOWN HEREON ARE FROM OBSERVED EVIDENCE OF ABOVE









ARB

2 DISTRIC PHASE

**WATER** 

UPGRADE

PLANT

AND

TREATMENT

SEWER WASTEWATER


**EASTSOUND** 


. O


P

8

Call 811







 $\infty$ 6 00 OF 08

# WASTEWATER TREATMENT PLANT DESIGN INFORMATION

# PHASE 1 + PHASE 2 DESIGN INFORMATION

# FLOW:

ADF MMF = 0.22 MGD MAX. DAY = 0.46 MGD = 0.77 MGD PEAK HR

# AVERAGE DAILY LOADS:

Ammonia-N = 45 mg/L Nitrate/Nitrite-N = 0 mg/L = 45 mg/L = 60 mg/L

# MAX MONTH LOADS:

TSS Ammonia-N = 62 ma/L Nitrate/Nitrite-N = 0 mg/L = 62 mg/L TKN = 82 mg/L Alkalinity = 433 mg/L

NO. OF UNITS: DIAMETER: 18 FT SWD: 15 50 FT RAS:

# **CLARIFIERS**

ADF SOR: MMF SOR: PEAK HR:

# AERATION & ANOXIC BASIN INFORMATION

NO OF TRAINS: 3 NO. OF AERATION BASIN PER TRAIN: 2 NO. OF ANOXIC BASINS PER TRAIN: 2 TOTAL VOLUME OF AERATION & ANOXIC BASINS PER TRAIN: 0.0624 MG MMF HRT: 21 HOURS

# UV DISINFECTION:

WEEKLY GEOMETRIC MEAN: 0.5 MGD

ADF STORAGE AT 2.0% SOLIDS (WITH CARBON ADDITION) = 1.9 WEEKS

# PROCESS DESIGN CRITERIA

- TRAINS 1 & 2 AERATION BASIN: DESIGN INFORMATION

   AERATION BASIN MIXING = PLENUM COARSE BUBBLE DIFFUSERS
- ANOXIC BASIN MIXER = SUBMERSIBLE MIXERS O ONE 5 HP SUBMERSIBLE MIXER IN ANOXIC ZONE #1: 15,686 GALLONS.
  - O ONE 5 HP SUBMERSIBLE MIXER IN ANOXIC ZONE #2: 8,789 GALLONS.
- AERATION BASINS
- O AERATION ZONE #1: 29,793 GALLONS, 8 DIFFUSERS. DESIGN: 24 SCFM/DIFFUSER, 192 SCFM TOTAL O AERATION ZONE #2: 9,889 GALLONS, 2 DIFFUSERS. DESIGN: 24 SCFM/DIFFUSER, 48 SCFM TOTAL O TOTAL AERATION AIR = 240 SCFM
- O AIR NEEDED FOR RAS AIRLIFT PUMP = 15 SCFM. PIPE SIZE = 3-INCH. FLOW = 51 GPM. TARGET = 1Q
- O AIR NEEDED FOR NITRATE RECYCLE AIRLIFT PUMP = 61 SCFM. PIPE SIZE = 6-INCH. FLOW = 203 GPM. TARGET = 4Q. O TOTAL AIRLIFT AIR = 76 SCFM
- TOTAL AIR REQUIRED = 316 SCFM AT 9.2 PSIG
- SRT = 15 DAYS (YR-2040 MMF)
- HRT = 21 HOURS (YR-2040 MMF)
- MLSS = 3000 MG/L (RANGE = 2000 TO 4000 MG/L)
- F/M = 0.10 TO 0.20 (LBS INFLUENT BOD/LBS MLVSS)
- VOLUMETRIC LOAD = 10 TO 30 (LBS. INFLUENT BOD/KCF DAY)

 $\frac{\text{TRAINS 1 \& 2 RAS RECYCLE:}}{\text{DESIGN INFORMATION}} = 15 \text{ SCFM. FLOW} = 51 \text{ GPM. TARGET} = 1 \text{ Q}$ 

TRAINS 1 & 2 NITRATE RECYCLE (MLR): DESIGN INFORMATION

AIR NEEDED FOR NITRATE RECYCLE AIRLIFT PUMP = 61 SCFM. LOW = 203 GPM. TARGET = 4Q.

# = 0.19 MGD

BOD = 181 mg/L = (287 lbs/day) = 44 mg/L = (69 lbs/day)

Alkalinity = 314 mg/L

BOD = 250 mg/L = (454 lbs/day) = 118 mg/L = (216 lbs/day)

# CLARIFIER INFORMATION:

0.5Q TO 1.0Q

249 GAL/DAYSF 314 GAL/DAY/SF 603 GAL/DAY/SF 1008 GAL/DAY/SF

MONTHLY GEOMETRIC MEAN: 200 FC/100ML 400 FC/100 MI

CAPACITY OF 1 CHANNEL: CAPACITY OF 2 CHANNELS: 1.0 MGD

# AEROBIC DIGESTER

VOLUME: 15,000 GAL

MMF STORAGE AT 2.0% SOLIDS (WITH CARBON ADDITION) = 1.2 WEEKS

WATER

AND

SEWER

91 P

60

# WSEC COMMERCIAL PROVISION COMPLIANCE

# DOCUMENTATION REQUIREMENTS C103.6.3

C103.6.3
PROJECT CLOSE OUT DOCUMENTATION IS REQUIRED. CLOSE OUT DOCUMENTATION SHALL INCLUDE THE INTERIOR LIGHTING COMPLIANCE FORM PROVIDED ON THIS SHEET DEMONSTRATING COMPLIANCE WITH THE 20% LIGHTING REDUCTION CREDIT.

THERMAL RESISTANCE OF MECHANICAL EQUIPMENT PENETRATIONS.
C402.1.4
THROUGH-WALL PENETRATIONS AND CALCULATION OF TOTAL PERCENT SQUARE FOOT AREA OF PENETRATIONS ARE INCLUDED ON SHEET A1.2.

VERTICAL FENESTRATION MAXIMUM AREA.
C402.4.1 & C502.2.1
THIS BUILDING IS CONSIDERED A CONDITIONED SPACE. NO WINDOWS ARE PROPOSED ON THIS BUILDING. NO DOORS OR GARAGES WITH OPAQUE OR GLAZED WINDOWS ARE PROPOSED. THEREFORE, THE WINDOW-TO-WALL RATIO (WWR) OF THIS BUILDING IS ZERO.

# WSEC ENVELOPE COMPLIANCE FORM

U x A Calculation	NEW BUILDING	- FULLY CONI	DITIONED			COMPLIES	
paque Envelope Assemblies			PROPOSED			TARGET	
Roof/Ceiling	Assembly ID	Roof/Ceiling Assembly U-Factor	Net Area (SF)	UxA	Roof/Ceiling Assembly U-Factor	Net Area (SF)	UxA
Metal building (purlins)	Typical Roof Section	0.029	700.0	20.3	0.031	700.0 (1)	21.7
Walls	Assembly ID	Wall Assembly U-factor	Net Area (SF)	UxA	Wall Assembly U-factor	Net Area (SF)	UxA
Metal building (girts)	Typical Wall Section	0.048	1,710.0	82.1	0.050	1,710.0 (1)	85.5
Slab on Grade Floors			PROPOSED			TARGET	
Slab-on-grade Floors	Assembly ID	F-Factor	Perimeter Length (LF)	UxA	F-Factor	Perimeter Length (LF)	UxA
Unheated slab	STD_FL01	0.52	116.5	60,6	0.54	116.5 (1)	62.9
enestration Assemblies			PROPOSED			TARGET	
Opaque Doors	Assembly ID	Door Assembly U-Factor	Assembly Rough Opening (SF)	UxA	Door Assembly U-Factor	Assembly Rough Opening (SF)	UxA
Swinging	Door 101C	0.37	70.0	25.9	0.37	70.0 (1)	25.9
Garage - Glazed <14%	Overhead Garage Door	0.07	110.0	1.1	0.31	110.0 (1)	34.1

# INTERIOR LIGHTING COMPLIANCE


A STATE OF THE PARTY OF THE PAR	elect One)							
Building Area	Gross Interior Area (SF)	LPA (Watts/SF)		Total Wat (SF x LPA	ts Allowed ( x 0.8)		Total Proposed Wat By Building Area	ts
Workshop	(子童 650	0.91		473			400	
Add Fixtures (Select	One) ~	Proposed Lig	hting Pow	er Density	- Building Ar	ea		Hide Detail
The table to be the termination of the termination				Quantity of	Watts per	Total Linear	Watts per Linear	Total Watts Proposed (#F x WpF) or
The Day Congress of the Congre	Cine) ~  Fixture Type / Application	Proposed Ligi	hting Pow		Watts per Fixture (WpF)		Watts per Linear Foot (WpLF)	Total Watts Proposed (#F x WpF) or (LF x WpLF)
Add Fixtures (Select Fixture Category Individual Fixtures				Quantity of	Watts per	Total Linear	Colonia Colonia Colonia Allanda	Total Watts Proposed (#F x WpF) or




# BUILDING ENCLOSURE AIR LEAKAGE TESTING C103.2 & C402.5.1.2 & C402.5.1.2.1 BUILDING ENCLOSURE AIR LEAKAGE TESTING IS REQUIRED FOR WSEC COMPLIANCE. TESTING SHALL BE PERFORMED PER ASTM C779 (OR EQUIVALENT METHOD APPROVED BY THE CODE OFFICAL). THE TARGET LEAKAGE RATE IS 0.25 CFM/FT<sup>2</sup> (1.5 L/S\*M<sup>2</sup>) AT 0.3 IN WG (75 PA). AIR BARRIER BOUNDARY AREA CALCULATIONS ARE INCLUDED ON SHEET A1.2.

ation Assemblies			PROPOSED			TARGET		
Opaque Doors	Assembly ID	Door Assembly U-Factor	Assembly Rough Opening (SF)	UxA	Door Assembly U-Factor	Assembly Rough Opening (SF)	UxA	
Swinging	Door 101C	0.37	70.0	25.9	0.37	70.0 (1)	25.9	
Garage - Glazed <14%	Overhead Garage Door	0.07	110.0	7.7	0.31	110.0 (1)	34.1	

	Proposed Area	Proposed UxA	Target Area	Target UxA
Project Totals	2,707	197	2,707	230
	<u> </u>		2011	





B) RETAIN THE DUFF LAYER, NATIVE TOP SOIL, AND NATURAL VEGETATION IN AN UNDISTURBED STATE TO THE MAXIMUM DEGREE PRACTICABLE.

### ELEMENT 2: ESTABLISH CONSTRUCTION ACCESS

- A) LIMIT CONSTRUCTION VEHICLE ACCESS AND EXIT TO ONE ROUTE, IF POSSIBLE.
- B) STABILIZE ACCESS POINTS WITH A PAD OF QUARRY SPALLS, CRUSHED ROCK, OR OTHER EQUIVALENT BMPS, TO MINIMIZE TRACKING OF SEDIMENT ONTO PUBLIC ROADS.
- C) LOCATE WHEEL WASH OR TIRE BATHS ON SITE, IF THE STABILIZED CONSTRUCTION ENTRANCE IS NOT EFFECTIVE IN PREVENTING TRACKING SEDIMENT ONTO ROADS.
- D) IF SEDIMENT IS TRACKED OFF SITE, CLEAN THE AFFECTED ROADWAY THOROUGHLY AT THE END OF EACH DAY, OR MORE FREQUENTLY AS NECESSARY (FOR EXAMPLE, DURING WET WEATHER), REMOVE SEDIMENT FROM ROADS BY SHOVELING, SWEEPING, OR PICK UP AND TRANSPORT THE SEDIMENT TO A CONTROLLED SEDIMENT DISPOSAL AREA.
- E) CONDUCT STREET WASHING ONLY AFTER SEDIMENT IS REMOVED IN ACCORDANCE WITH THE ABOVE ITEM.
- F) CONTROL STREET WASH WASTEWATER BY PUMPING BACK ON-SITE, OR OTHERWISE PREVENT IT FROM DISCHARGING INTO SYSTEMS TRIBUTARY TO WATERS OF THE STATE.

### ELEMENT 3: CONTROL FLOW RATES

A) THIS ELEMENT IS NOT REQUIRED ON SITE THAT ARE THIS SMALL.

### ELEMENT 4: INSTALL SEDIMENT CONTROLS

- A) DESIGN, INSTALL, AND MAINTAIN EFFECTIVE EROSION CONTROLS AND SEDIMENT CONTROLS TO MINIMIZE THE DISCHARGE OF POLLUTANTS.
- B) CONSTRUCT SEDIMENT CONTROL BMPS (SEDIMENT, TRAPS, SILT FENCE, INLET PROTECTION, ETC.) AS ONE OF THE FIRST STEPS IN GRADING. THESE BMPS SHALL BE FUNCTIONAL BEFORE OTHER LAND DISTURBING ACTIVITIES TAKE PLACE.
- C) MINIMIZE SEDIMENT DISCHARGES FROM THE SITE, THE DESIGN, INSTALLATION AND MAINTENANCE OF EROSION AND SEDIMENT CONTROLS MUST ADDRESS FACTORS SUCH AS THE AMOUNT, FREQUENCY, INTENSITY AND DURATION OF PRECIPITATION, THE NATURE OF RESULTING STORMWATER RUNOFF, AND SOIL CHARACTERISTICS, INCLUDING THE RANGE OF SOIL PARTICLE SIZES EXPECTED TO BE PRESENT ON THE SITE.
- D) DIRECT STORMWATER RUNOFF FROM DISTURBED AREAS THROUGH A SEDIMENT REMOVAL BMP. BEFORE THE RUNOFF LEAVES A CONSTRUCTION SITE. RUNOFF FROM FULLY STABILIZED AREAS MAY BE DISCHARGED WITHOUT A SEDIMENT REMOVAL BMP.
- E) BMP C140 DUST CONTROL. CONTRACTOR SHALL KEEP DUST FROM CONSTRUCTION ACTIVITIES AND EXPOSED SOILS TO A MINIMUM.

# ELEMENT 5: STABILIZE SOILS

A) STABILIZE EXPOSED AND UNWORKED SOILS BY APPLICATION OF EFFECTIVE BMPS THAT PREVENT EROSION. APPLICABLE BMPS INCLUDE, BUT ARE NOT LIMITED TO: TEMPORARY AND PERMANENT SEEDING, SODDING, MULCHING, PLASTIC COVERING, EROSION CONTROL FABRICS AND MATTING, SOIL APPLICATION OF POLYACRYLAMIDE (PAM), THE FARLY APPLICATION OF GRAVEL BASE EARLY ON AREAS TO BE PAVED, AND DUST CONTROL B) CONTROL STORMWATER VOLUME AND VELOCITY WITHIN THE SITE TO MINIMIZE SOIL EROSION.

- C) SOILS MUST NOT REMAIN EXPOSED AND UNWORKED FOR MORE THAN THE TIME PERIODS SET FORTH BELOW TO PREVENT EROSION:
- DURING THE DRY SEASON (MAY 1 SEPT. 30): 7 DAYS
- DURING THE WET SEASON (OCTOBER 1 APRIL 30): 2 DAYS
- D) STABILIZE SOILS AT THE END OF THE SHIFT BEFORE A HOLIDAY OR WEEKEND IF NEEDED BASED ON THE WEATHER FORECAST.
- E) STABILIZE SOIL STOCKPILES FROM EROSION, PROTECTED WITH SEDIMENT TRAPPING MEASURES, AND WHERE POSSIBLE, BE LOCATED AWAY FROM STORM DRAIN INLETS, WATERWAYS AND DRAINAGE CHANNELS.
- F) MINIMIZE THE AMOUNT OF SOIL EXPOSED DURING CONSTRUCTION ACTIVITY.
- G) MINIMIZE THE DISTURBANCE OF STEEP SLOPES.
- H) PRESERVE TOPSOIL AND MINIMIZE COMPACTING OF THESE AREAS.

# ELEMENT 6: PROTECT SLOPES

- A) DESIGN AND CONSTRUCT CUT-AND-FILL SLOPES IN A MANNER TO MINIMIZE EROSION. APPLICABLE PRACTICES INCLUDE, BUT ARE NOT LIMITED TO, REDUCING CONTINUOUS LENGTH OF SLOPE WITH TERRACING AND DIVERSIONS, REDUCING SLOPE STEEPNESS, AND ROUGHENING SLOPE SURFACES (FOR EXAMPLE, TRACK WALKING).
- B) DIVERT OFF-SITE STORMWATER (RUN-ON) OR GROUND WATER AWAY FROM SLOPES AND DISTURBED AREAS WITH INTERCEPTOR DIKES, PIPES AND/OR SWALES. OFF-SITE STORMWATER SHOULD BE MANAGED SEPARATELY FROM STORMWATER GENERATED ON THE
- C) AT THE TOP OF SLOPES, COLLECT DRAINAGE IN PIPE SLOPE DRAINS OR PROTECTED CHANNELS TO PREVENT EROSION.
- D) PLACE EXCAVATED MATERIAL ON THE UPHILL SIDE OF TRENCHES. CONSISTENT WITH SAFETY AND SPACE CONSIDERATIONS.
- E) PLACE CHECK DAMS AT REGULAR INTERVALS WITHIN CONSTRUCTED CHANNELS THAT

# ELEMENT 7: PROTECT DRAIN INLETS

- A) PROTECT ALL STORM DRAIN INLETS MADE OPERABLE DURING CONSTRUCTION SO THAT STORMWATER RUNOFF SHALL NOT ENTER THE CONVEYANCE SYSTEM WITHOUT FIRST BEING FILTERED OR TREATED TO REMOVE SEDIMENT.
- B) CLEAN OR REMOVE AND REPLACE INLET PROTECTION DEVICES WHEN SEDIMENT HAS FILLED ONE—THIRD OF THE AVAILABLE STORAGE (UNLESS A DIFFERENT STANDARD IS SPECIFIED BY THE PRODUCT MANUFACTURER).

# ELEMENT 8: STABILIZE CHANNELS AND OUTLETS

- A) DESIGN, CONSTRUCT, AND STABILIZE ALL ON-SITE CONVEYANCE CHANNELS TO PREVENT FROSION
- B) PROVIDE STABILIZATION, INCLUDING ARMORING MATERIAL, ADEQUATE TO PREVENT EROSION OF OUTLETS, ADJACENT STREAM BANKS, SLOPES AND DOWNSTREAM REACHES AT THE OUTLETS OF ALL CONVEYANCE SYSTEMS.

# ELEMENT 9: CONTROL POLLUTANTS

A) DESIGN, INSTALL, IMPLEMENT AND MAINTAIN EFFECTIVE POLLUTION PREVENTION MEASURES TO MINIMIZE THE DISCHARGE OF POLLUTANTS.

- B) HANDLE AND DISPOSE OF ALL POLLUTANTS, INCLUDING WASTE MATERIALS AND DEMOLITION DEBRIS THAT OCCUR ON-SITE IN A MANNER THAT DOES NOT CAUSE CONTAMINATION OF STORMWATER.
- C) PROVIDE COVER, CONTAINMENT, AND PROTECTION FROM VANDALISM FOR ALL CHEMICALS, LIQUID PRODUCTS, PETROLEUM PRODUCTS, AND OTHER MATERIALS THAT HAVE THE POTENTIAL TO POSE A THREAT TO HUMAN HEALTH OR THE ENVIRONMENT. ON-SITE FUELING TANKS MUST INCLUDE SECONDARY CONTAINMENT. SECONDARY CONTAINMENT MEANS PLACING TANKS OR CONTAINERS WITHIN AN IMPERVIOUS STRUCTURE CAPABLE OF CONTAINING 110% OF THE VOLUME CONTAINED IN THE LARGEST TAKE WITHIN THE CONTAINMENT STRUCTURE. DOUBLE-WALLED TANKS DO NOT REQUIRE ADDITIONAL SECONDARY CONTAINMENT
- D) CONDUCT MAINTENANCE, FUELING, AND REPAIR OF HEAVY EQUIPMENT AND VEHICLES USING SPILL PREVENTION AND CONTROL MEASURES. CLEAN CONTAMINATED SURFACES IMMEDIATELY FOLLOWING ANY SPILL INCIDENT.
- F) DISCHARGE WHEEL WASH OR TIRE BATH WASTEWATER TO A SEPARATE ON-SITE TREATMENT SYSTEM THAT PREVENTS DISCHARGE TO SURFACE WATER, SUCH AS CLOSED-LOOP RECIRCULATION OR UPLAND APPLICATION, OR TO THE SANITARY SEWER, WITH LOCAL SEWER DISTRICT APPROVAL.
- F) APPLY FERTILIZERS AND PESTICIDES IN A MANNER AND AT APPLICATION RATES THAT WILL NOT RESULT IN LOSS OF CHEMICAL TO STORMWATER RUNOFF, FOLLOW MANUFACTURERS' LABEL REQUIREMENTS FOR APPLICATION RATES AND PROCEDURES
- G) USE BMPS TO PREVENT CONTAMINATION OF STORMWATER RUNOFF BY PH MODIFYING SOURCES. THE SOURCES FOR THIS CONTAMINATION INCLUDE, BUT ARE NOT LIMITED TO: BULK CEMENT, CEMENT KILN DUST, FLY ASH, NEW CONCRETE WASHING AND CURING WATERS, WASTE STREAMS GENERATED FROM CONCRETE GRINDING AND SAWING, EXPOSED AGGREGATE PROCESSES, DEWATERING CONCRETE VAULTS, CONCRETE PUMPING AND MIXER WASHOUT WATERS.
- H) ADJUST THE PH OF STORMWATER IF NECESSARY TO PREVENT VIOLATIONS OF WATER QUALITY STANDARDS.
- I) ASSURE THAT WASHOUT OF CONCRETE TRUCKS IS PERFORMED OFF-SITE OR II DESIGNATED CONCRETE WASHOUT AREAS ONLY. DO NOT WASH OUT CONCRETE TRUCKS ONTO THE GROUND, OR INTO STORM DRAINS, OPEN DITCHES, STREETS, OR STREAMS. DO NOT DUMP EXCESS CONCRETE ON-SITE, EXCEPT IN DESIGNATED CONCRETE WASHOUT AREAS. CONCRETE SPILLAGE OR CONCRETE DISCHARGE TO SURFACE WATERS OF THE STATE IS PROHIBITED
- J) OBTAIN WRITTEN APPROVAL FROM ECOLOGY BEFORE USING CHEMICAL TREATMENT OTHER THAN CO2 OR DRY ICE TO ADJUST PH.

- A) DISCHARGE FOUNDATION, VAULT, AND TRENCH DE-WATERING WATER, WHICH HAS SIMILAR CHARACTERISTICS TO STORMWATER RUNOFF AT THE SITE, INTO A SEDIMENT REMOVAL BMP BEFORE DISCHARGING OFFSITE.
- B) CLEAN, NON-TURBID DE-WATERING WATER, SUCH AS WELL-POINT GROUND WATER. CAN BE DISCHARGED TO SYSTEMS TRIBUTARY TO, OR DIRECTLY INTO SURFACE WATERS OF THE STATE PROVIDED THE DE-WATERING FLOW DOES NOT CAUSE EROSION OR FLOODING OF RECEIVING WATERS. DO NOT ROUTE CLEAN DEWATERING WATER THROUGH STORMWATER SEDIMENT PONDS.
- C) HANDLE HIGHLY TURBID OR OTHERWISE CONTAMINATED DEWATERING WATER SEPARATELY FROM STORMWATER.
- D) OTHER TREATMENT OR DISPOSAL OPTIONS MAY INCLUDE:
- TRANSPORT OFF-SITE IN A VEHICLE, SUCH AS A VACUUM FLUSH TRUCK, FOR LEGAL DISPOSAL IN A MANNER THAT DOES NOT POLLUTE STATE WATERS.
- ECOLOGY-APPROVED ON-SITE CHEMICAL TREATMENT OR OTHER SUITABLE TREATMENT TECHNOLOGIES.
- SANITARY OR COMBINED SEWER DISCHARGE WITH LOCAL SEWER DISTRICT APPROVAL, IF THERE IS NO OTHER OPTION.
- USE OF A SETTLING TANKS WITH OUTFALL TO A DITCH OR SWALE FOR SMALL VOLUMES OF LOCALIZED DEWATERING.

# FLEMENT 11: MAINTAIN BMPS

- A) MAINTAIN AND REPAIR ALL TEMPORARY AND PERMANENT EROSION AND SEDIMENT CONTROL BMPS AS NEEDED TO ASSURE CONTINUED PERFORMANCE OF THEIR INTENDED FUNCTION IN ACCORDANCE WITH BMP SPECIFICATIONS.
- B) REMOVE ALL TEMPORARY EROSION AND SEDIMENT CONTROL BMPS WITHIN 30 DAYS AFTER ACHIEVING FINAL SITE STABILIZATION OR AFTER THE TEMPORARY BMPS ARE NO LONGER NEEDED

# ELEMENT 12: MANAGE THE PROJECT

- A) PHASE LAND DISTURBANCE TO THE MAXIMUM DEGREE PRACTICABLE AND TAKE INTO ACCOUNT SEASONAL WORK LIMITATIONS.
- B) THIS PROJECT IS NOT REQUIRED TO OBTAIN A CONSTRUCTION STORMWATER GENERAL
- C) PROJECTS THAT DISTURB ONE OR MORE ACRES MUST HAVE SITE INSPECTIONS CONDUCTED BY A CERTIFIED EROSION AND SEDIMENT CONTROL LEAD (CESCL). PROJECT SITES DISTURBING LESS THAN ONE ACRE MAY HAVE A CESCL OR A PERSON WITHOUT CESCL CERTIFICATION CONDUCT INSPECTIONS. BY THE INITIATION OF CONSTRUCTION, THE SWPPP MUST IDENTIFY THE CESCL OR INSPECTOR, WHO MUST BE PRESENT ON—SITE OR
- D) THE CESCL OR INSPECTOR (PROJECT SITES LESS THAN ONE ACRE) MUST HAVE THE SKILLS TO ASSESS THE:
- SITE CONDITIONS AND CONSTRUCTION ACTIVITIES THAT COULD IMPACT THE QUALITY OF STORMWATER.
- EFFECTIVENESS OF EROSION AND SEDIMENT CONTROL MEASURES USED TO CONTROL THE QUALITY OF STORMWATER DISCHARGES.
- E) THE CESCL OR INSPECTOR MUST EXAMINE STORMWATER VISUALLY FOR THE PRESENCE OF SUSPENDED SEDIMENT, TURBIDITY, DISCOLORATION, AND OIL SHEEN. THEY MUST FVALUATE THE EFFECTIVENESS OF BMPS AND DETERMINE IF IT IS NECESSARY TO INSTALL MAINTAIN, OR REPAIR BMPS TO IMPROVE THE QUALITY OF STORMWATER DISCHARGES. BASED ON THE RESULTS OF THE INSPECTION, CONSTRUCTION SITE OPERATORS MUST CORRECT THE PROBLEMS IDENTIFIED BY:
- REVIEWING THE SWPPP FOR COMPLIANCE WITH THE 13 CONSTRUCTION SWPPF ELEMENTS AND MAKING APPROPRIATE REVISIONS WITHIN 7 DAYS OF THE INSPECTION.
- IMMEDIATELY BEGINNING THE PROCESS OF FULLY IMPLEMENTING AND MAINTAINING APPROPRIATE SOURCE CONTROL AND/OR TREATMENT BMPS AS SOON AS POSSIBLE, ADDRESSING THE PROBLEMS NOT LATER THAN WITHIN 10 DAYS OF THE INSPECTION, IF INSTALLATION OF NECESSARY TREATMENT BMPS IS NOT FEASIBLE WITHIN 10 DAYS, THE CONSTRUCTION SITE OPERATOR MAY REQUEST AN EXTENSION WITHIN THE INITIAL 10-DAY RESPONSE PERIOD.
- DOCUMENTING BMP IMPLEMENTATION AND MAINTENANCE IN THE SITE LOG BOOK (SITES LARGER THAN 1 ACRE).
- F) THE CESCL OR INSPECTOR MUST INSPECT ALL AREAS DISTURBED BY CONSTRUCTION

ACTIVITIES, ALL BMPS, AND ALL STORMWATER DISCHARGE POINTS AT LEAST ONCE EVERY CALENDAR WEEK AND WITHIN 24 HOURS OF ANY DISCHARGE FROM THE SITE. (FOR PURPOSES OF THIS CONDITION, INDIVIDUAL DISCHARGE EVENTS THAT LAST MORE THAN ONE DAY DO NOT REQUIRE DAILY INSPECTIONS. FOR EXAMPLE, IF A STORMWATER POND DISCHARGES CONTINUOUSLY OVER THE COURSE OF A WEEK, ONLY ONE INSPECTION IS REQUIRED THAT WEEK.) THE CESCL OR INSPECTOR MAY REDUCE THE INSPECTION FREQUENCY FOR TEMPORARY STABILIZED, INACTIVE SITES TO ONCE EVERY CALENDAR

# ELEMENT 13: PROTECT LOW IMPACT DEVELOPMENT BMPS

A) THERE ARE NO LID BMPS ON THIS SITE.

- 1. BMPS: BEST MANAGEMENT PRACTICES (BMPS) REFERRED TO ON THIS PLAN AND IN THESE NOTES SHALL BE CONSTRUCTED AND MAINTAINED AS DESCRIBED IN MOST RECENT VERSION OF THE DEPARTMENT OF ECOLOGY'S STORMWATER MANAGEMENT MANUAL FOR WESTERN WASHINGTON (SWMMWW) SECTION ON CONSTRUCTION STORMWATER POLLUTION PREVENTION.
- 2. EXTENT: THE EXTENT OF EROSION AND SEDIMENTATION CONTROL MEASURES IS DEPENDENT ON WEATHER CONDITIONS, SITE SLOPES, LENGTH OF TIME GROUND IS LEFT EXPOSED, AND THE AREA OF EXPOSED GROUND. THE CONTRACTOR SHALL AT ALL TIMES MINIMIZE THE RISK OF SITE EROSION BY CAREFUL SCHEDULING AND BY IMPLEMENTING AND MAINTAINING BMPS UNTIL THE SITE IS PERMANENTLY STABILIZED.
- VEGETATION: EXISTING VEGETATION SHALL BE PRESERVED WHERE ATTAINABLE.
- 4. ADJACENT PROPERTIES: PROPERTIES ADJACENT TO THE PROJECT SHALL BE PROTECTED FROM SEDIMENT DEPOSITION.
- 5. REMOVAL OF BMPS: ALL TEMPORARY EROSION AND SEDIMENT CONTROL BMPS SHALL BE REMOVED WITHIN 30 DAYS AFTER FINAL SITE STABILIZATION IS ACHIEVED OR AFTER THE TEMPORARY BMPS ARE NO LONGER NEEDED. TRAPPED SEDIMENT SHALL BE REMOVED OR STABILIZED ON-SITE. DISTURBED SOIL AREAS RESULTING FROM
- OTHER REQUIREMENTS: THE ENGINEER, OWNER, DEPARTMENT OF ECOLOGY, OR OTHER REQUIREMENTS. THE ENGINEER, OWNER, DEPARTMENT OF ECOLOGY, OR OTHER AGENCIES MAY REQUIRE BMPS IN ADDITION TO WHAT IS SHOWN ON THIS PLAN IF NECESSARY TO PREVENT VIOLATIONS OF SURFACE WATER QUALITY. THE CONTRACTOR SHALL IMPLEMENT THE BMPS AS REQUIRED.
- 7. THE IMPLEMENTATION OF THESE TESC PLANS AND THE CONSTRUCTION, MAINTENANCE, REPLACEMENT, AND UPGRADING OF THESE TESC FACILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR UNTIL ALL CONSTRUCTION IS COMPLETED AND APPROVED AND VEGETATION/FINAL SURFACING IS ESTABLISHED.

THE TESC FACILITIES SHOWN ON THIS PLAN MUST BE CONSTRUCTED IN

- CONJUNCTION WITH ALL CLEARING AND GRADING ACTIVITIES, AND IN SUCH A MANNER AS TO INSURE THAT SEDIMENT AND SEDIMENT LADEN WATER DO NOT ENTER THE DRAINAGE SYSTEM, ROADWAYS, OR VIOLATE APPLICABLE WATER STANDARDS.
- 9. THE TESC FACILITIES SHOWN ON THIS PLAN ARE THE MINIMUM REQUIREMENTS FOR ANTICIPATED SITE CONDITIONS. DURING THE CONSTRUCTION PERIOD, THESE ESC FACILITIES SHALL BE UPGRADED AS NEEDED FOR UNEXPECTED STORM EVENTS AND TO
- 10. OBTAIN PERMISSION AND/OR PERMIT APPROVAL AS REQUIRED FROM EASTSOUND WATER AND SEWER DISTRICT PRIOR TO ANY DISCHARGES TO THE SANITARY SEWER
- 11. CONVEYANCE BYPASS: IF REQUIRED, PROVISION FOR BYPASS OF STORMWATER CONVEYANCE SHALL BE PROVIDED. BYPASS SHALL BE INSTALLED FOR THE DURATION OF THE WORK. MATERIALS FOR BYPASS NEED NOT BE INSTALLED WHILE WORK IS IN PROGRESS AT A PARTICULAR LOCATION, BUT MATERIALS AND EQUIPMENT FOR IMMEDIATE INSTALLATION SHALL BE ON HAND. BYPASS SHALL BE IN PLACE WHILE SITE IS UNATTENDED FOR GREATER THAN 12 HOURS.
- 12. PUBLIC RIGHTS-OF WAY SHALL BE KEPT IN A CLEAN AND SERVICEABLE CONDITION AT ALL TIMES. IN THE EVENT MATERIALS ARE INADVERTENTLY DEPOSITED ON ROADWAYS, THE MATERIAL SHALL BE PROMPTLY REMOVED. MATERIALS ARE TO BE SWEPT AND REMOVED PRIOR TO ANY STREET FLUSHING. PUBLIC AND PRIVATE DRAINAGE WAYS SHALL BE PROTECTED FROM POLLUTION. NO MATERIAL IS TO BE DISCHARGED TO OR DEPOSITED IN STORMWATER SYSTEMS THAT MAY RESULT IN WOLLD ALL OF STATE OR SECRED. VIOLATION OF STATE OR FEDERAL WATER QUALITY STANDARDS.
- 13. ALL CATCH BASINS WITHIN THE PROJECT LIMITS SHALL BE CLEANED OUT AT THE COMPLETION OF THE PROJECT AND ANY MATERIAL REMOVED SHALL BE PROPERLY DISPOSED OF.
- 14. CONCRETE PROCESS WATER AND SLURRY FROM PAVEMENT CUTTINGS SHALL NOT BE ALLOWED TO ENTER ANY DRAINAGE CONVEYANCE. SLURRY/CUTTINGS SHALL NOT REMAIN ON PAVEMENT OVERNIGHT. ALL SAWCUTTING AND SURFACING OPERATIONS SHALL USE BMP C152 FOR POLLUTION PREVENTION.
- 15. PROJECT DESCRIPTION
- a.TOTAL PROJECT AREA. 0.08 ACRES
- b. TOTAL PROPOSED IMPERVIOUS AREA. 0.08 ACRES
- c.TOTAL PROPOSED AREA TO BE DISTURBED. 0.08 ACRES
- d.TOTAL VOLUME OF PROPOSED CUT/FILL. CUT = 0 CY, FILL = 0 CY. (ESTIMATED VOLUME BETWEEN EXISTING GROUND SURFACE AND PROPOSED FINISH GRADES FOR BASE BID AND ALL ALTERNATES. NO SHRINK OR SWELL FACTORS APPLIED.)
  VOLUMES ARE FOR TESC NARRATIVE ONLY AND ARE NOT INTENDED FOR BIDDING OR TAKE-OFF PURPOSES.
- 16. EXISTING SITE CONDITIONS
- a.DESCRIPTION OF EXISTING TOPOGRAPHY. EXISTING SLOPES VARY SLIGHTLY THROUGHOUT THE PROJECT SITE. MOST AREAS ARE FLAT TO SLOPED UP TO 2 PERCENT
- b.DESCRIPTION OF EXISTING VEGETATION. AREAS ALONG THE NORTH AND SOUTH PROPERTY LINES ARE GRASS TURF. THERE ARE NO TREES OR SHRUBS ON THE
- DESCRIPTION OF EXISTING DRAINAGE. RUNOFF FROM THE SITE FLOWS GENERALLY FROM SOUTHEAST TO NORTHWEST TO WHERE IT ENTERS A DITCH ON THE ADJOINING SITE ALONG THE NORTH BOUNDARY.

REVISIONS	BY	DATE	

# 18. ADJACENT AREAS

a.DESCRIPTION OF ADJACENT AREAS WHICH MAY BE AFFECTED BY SITE DISTURBANCE: LSTREAMS. NONE.

- LAKES. NONE
- WETLANDS, NONE,
- RESIDENTIAL AREAS. NONE.
- ROADS, CESSNA ROAD, UNNAMED AIRPORT ACCESS ROADS.
- 5 DESCRIPTION OF THE DOWNSTREAM DRAINAGE PATH LEADING FROM THE SITE TO THE RECEIVING BODY OF WATER (MINIMUM DISTANCE OF 400 YARDS). RUNOFF FROM THE SITE WILL CONTINUE WITH THE SAME PATTERN THAT EXISTS. RUNOFF WILL BE ROUTED TO A DITCH THAT IS JUST NORTHWEST OF THE SITE. RUNOFF IN THE DITCH IS CONVEYED NORTH THROUGH A SERIES OF DITCHES AND CULVERTS THROUGH PORT PROPERTY. IT APPEARS THAT THE OUTFALL MAY BE TO PUGET SOUND FURTHER TO THE NORTH.

### 19. CRITICAL AREAS

- G.DESCRIPTION OF CRITICAL AREAS THAT ARE ON OR ADJACENT TO THE SITE.

  THERE ARE NO CRITICAL AREAS WITHIN THE PROJECT SITE. THE SITE IS

  SURROUNDED BY DEVELOPMENT ON ALL SIDES. IT IS UNCLEAR IF THERE ARE CRITICAL AREAS NEAR THE SITE.
- b.DESCRIPTION OF SPECIAL REQUIREMENTS FOR WORKING IN OR NEAR CRITICAL AREAS. ALL WORK ON THIS PROJECT WILL BE DONE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL PERMITS AS APPLICABLE. NO KNOWN CRITICAL AREAS ARE WITHIN OR ADJACENT TO THE PROJECT LIMITS.

### 20. DESCRIPTION OF ONSITE SOILS

a.THE FOLLOWING SOIL DESCRIPTIONS WERE TAKEN FROM THE USDA NRCS WEB SOIL SURVEY (HTTP://WEBSOILSURVEY.NRCS.USDA.GOV/APP/). SOILS IN THE WORK AREAS ARE CLASSIFIED AS: -ROCHE-KILLEBREW COMPLEX. 2 TO 10 PERCENT SLOPES.

### 21. EROSION PROBLEM AREAS

NO EROSION PROBLEM AREAS ARE EXPECTED.

### 22. CONSTRUCTION PHASING.

- $\ensuremath{\mathtt{a}}.\ensuremath{\mathtt{CONSTRUCTION}}$  SEQUENCE. THE CONSTRUCTION SEQUENCE WILL GENERALLY BE
- INSTALL EROSION PREVENTION FACILITIES: SILT FENCE, CONSTRUCTION ENTRANCE, INLET PROTECTION;
- REMOVE PORTIONS OF THE PAVEMENT TO INSTALL UNDERGROUND AND ABOVE GROUND SEWER STRUCTURES. CLEAR AND GRADE AREAS FOR BUILDING ADDITION AND RETAINING WALL.
- INSTALL ABOVE AND BELOW GROUND SEWER STRUCTURES, BUILDING ADDITION, AND RETAINING WALL
- REMOVE REMAINDER OF PAVEMENT AND INSTALL STORMWATER CONVEYANCE
- · CLEAR NEW PAVING AREAS
- PAVE SITE WITH ASPHALT AND PROVIDE FINAL STABILIZATION TO LANDSCAPE AREAS.
- 6 CONSTRUCTION PHASING CONTRACTOR IS ENCOURAGED TO PHASE WORK SLICH THAT DISTURBED AREAS ARE OPENED UP, IMPROVEMENTS INSTALLED, AND PERMANENTLY STABILIZED IN SECTIONS SUCH TO MINIMIZE POTENTIAL FOR

# 23. CONSTRUCTION SCHEDULE

- a PROVIDE A PROPOSED CONSTRUCTION SCHEDULE. CONSTRUCTION IS EXPECTED. TO OCCUR STARTING IN SPRING OF 2025 AND ENDING IN WINTER OF 2027/2028.
- b.WET SEASON CONSTRUCTION ACTIVITIES. WET SEASON CONSTRUCTION ACTIVITIES ARE EXPECTED. INCREASED DILIGENCE WILL EMPLOYED TO PREVENT EROSION AND PROTECT DOWNSTREAM WATERS AND PROPERTIES FROM SEDIMENT. ALL WET SEASON HEIGHTENED TESC ACTIVITIES WILL BE IMPLEMENTED IN ACCORDANCE WITH THE SWMMWW.
- LPROPOSED WET SEASON CONSTRUCTION RESTRAINTS FOR ENVIRONMENTALLY SENSITIVE/CRITICAL AREAS. THERE ARE NO KNOWN ENVIRONMENTALLY SENSITIVE /CRITICAL AREAS WITHIN THE SITE, SO THERE ARE NO ADDITIONAL MEASURES TO

# 24. ENGINEERING CALCULATIONS

a.SEDIMENT PONDS/TRAPS. NONE USED.

b. DIVERSIONS. NONE ARE ANTICIPATED

c. WATERWAYS. NONE USED.

d.RUNOFF/STORMWATER DETENTION CALCULATIONS. NONE NEEDED.



**BID SET** 

WILSONENGINEERING Ш Z Ø



20

MCS


7 PHASE 2 Ś UPGRADE  $\mathsf{ER}$ ⋛ AND


PLANT TREATMENT

 $\simeq$ Ш ш  $\overline{S}$ ONNO **EWATER** Š WASTI S EĄ

. O  $\infty$ 0 P 7

DATE
1-27-2025
SCALE
AS SHOWN
JOB NUMBER





~ Ш

**∨** §

PHASE DISTRI PLANT UPGRADE **WATER** AND


TREATMENT SEWER

**EASTSOUND** WASTEWATER

6

14

0




### NOTES:

- 1. TIRES, SANDBAGS, OR EQUIVALENT MAY BE USED TO WEIGH DOWN PLASTIC SHEETING.
- 2. SEAMS BETWEEN SHEETS MUST OVERLAP A MINIMUM OF 12" AND BE WEIGHTED OR TAPED.
- 3. PLASTIC SHEETING SHALL HAVE A MINIMUM THICKNESS OF 6 MIL.
- 4. DUE TO RAPID RUNOFF CAUSED BY PLASTIC SHEETING, THIS METHOD SHALL NOT BE USED UPSLOPE OF AREAS THAT MIGHT BE ADVERSELY IMPACTED BY CONCENTRATED RUNOFF.
- 5. CONSTRUCT BERM OR SWALE AT TOP OF SLOPE AS DIRECTED BY THE CLEARING AND
- 6. CONSTRUCT DITCH AT BASE OF SLOPE IF NEEDED, AND DISCHARGE TO APPROVED LOCATION.



# PLASTIC COVERING FOR **SLOPES & STOCKPILES**


**NOT TO SCALE** 



- INSERT SHALL BE INSTALLED PRIOR TO CLEARING AND GRADING ACTIVITY, OR UPON PLACEMENT OF A NEW CATCH BASIN.
- 2. SEDIMENT SHALL BE REMOVED FROM THE UNIT WHEN IT BECOMES HALF
- SEDIMENT REMOVAL SHALL BE ACCOMPLISHED BY REMOVING THE INSERT, EMPTYING, AND RE-INSERTING IT INTO THE CATCH BASIN.



# **CATCH BASIN INSERT NOT TO SCALE**



COMPLY WITH REQUIREMENTS OF BMP C105: STABILIZATION CONSTRUCTION ENTRANCE FOUND IN VOLUME 2 OF THE STORMWATER MANAGEMENT MANUAL




TRACKCLEAN PLATE **NOT TO SCALE** 


BMP C208 - GEOTEXTILE ENCASED CHECK DAM

PURPOSE: GEOTEXTILE ENCASED CHECK DAMS MAY BE USED AS CHECK DAMS, FOR PERIMETER PROTECTION, FOR TEMPORARY SOIL STOCKPILE PROTECTION, FOR DROP INLET PROTECTION, OR AS A TEMPORARY INTERCEPTOR DIKE.

INSTALLATION: INSTALL WITH ENDS CURVED UP TO PREVENT WATER FROM FLOWING AROUND INSTALLATION: INSTALL WITH ENDS CURVED UP TO PREVENT WATER FROM FLOWING AROUND ENDS. THE FABRIC FLAPS AND CHECK DAM UNITS ARE ATTACHED TO THE GOUND WITH WIRE STAPLES. WIRE STAPLES SHOULD BE NO. 11 GAUGE AND SHOULD BE 200MM TO 300MM IN LENGTH. WHEN MULTIPLE UNITS ARE INSTALLED, THE SLEEVE OF FABRIC AT THE END OF THE UNIT SHALL OVERLAP THE ABUTTING UNIT AND BE STAPLED. CHECK DAMS SHOULD BE LOCATED AND INSTALLED AS SOON AS CONSTRUCTION WILL ALLOW AND SHOULD BE PLACED PERPENDICULAR TO THE FLOW OF WATER. WHEN USED AS CHECK DAMS, THE LEADING EDGE MUST BE SECURED WITH ROCKS, SANDBAGS, OR A SMALL KEY SLOT AND STAPLES. IN THE CASE OF GRASS-LINED DITCHES AND SWALES, CHECK DAMS AND ACCUMULATED SEDIMENT SHALL BE REMOVED WHEN THE GRASS HAS MATURED SUFFICIENTLY TO PROTECT THE DITCH OR SWALE UNLESS THE SLOPE OF THE SWALE IS GREATER THAN 4 PERCENT. THE AREA BENEATH THE CHECK DAMS SHALL BE SEEDED AND MULCHED IMMEDIATELY AFTER DAM REMOVAL. THE CHECK DAMS SHALL BE SEEDED AND MULCHED IMMEDIATELY AFTER DAM REMOVAL

MAINTENANCE: CHECK DAMS SHALL BE MONITORED FOR PERFORMANCE AND SEDIMENT ACCUMULATION DURING AND AFTER EACH RUNOFF PRODUCING RAINFALL. SEDIMENT SHALL BE REMOVED WHEN IT REACHES ONE HALF THE HEIGHT OF THE DAM. ANTICIPATE SUBMERGENCE AND DEPOSITION ABOVE THE TRIANGULAR SILT DAM AND EROSION FROM HIGH FLOWS AROUND THE EDGES OF THE DAM. IMMEDIATELY REPAIR ANY DAMAGE OR ANY UNDERCUTTING OF THE DAM.





- 1. GEOTEXTILE ENCASED CHECK DAMS SHALL MEET THE REQUIREMENTS OF STANDARD SPECIFICATIONS 8-01.3(6)A AND 9-14.5(4).
- 2. INSTALL THE SLOPED ENDS OF THE CHECK DAM A MINIMUM OF 3" HIGHER THAN THE TOP OF THE CHECK DAM IN THE CHANNEL TO ENSURE THAT WATER FLOWS OVER THE DAM AND NOT AROUND IT.
- 3. FLAT BOTTOM DITCH DESIGN SHOWN, CHECK DAM INSTALLATION DETAILS ARE SIMILAR FOR "V" BOTTOM DITCHES.
- 4. PERFORM MAINTENANCE IN ACCORDANCE WITH STANDARD SPECIFICATION 8-01.3(15).

THE CONTRACTOR SHALL BE RESPONSIBLE FOR UPDATING COVERAGE UNDER THE DOE'S "CONSTRUCTION STORMWATER GENERAL PERMIT". CONTACT MELINDA WILSON, PERMIT ADMINISTRATOR AT DOE (360-870-8290), EMAIL: MELINDA.WILSON@ECY.WA.GOV) FOR



GEOTEXTILE ENCASED CHECK DAM



BID SET

DATE
1-27-2025
SCALE
AS SHOWN
JOB NUMBER

. O 0 16

**DISTR** UPGRADE WATER PLANT AND TREATMENT SEWER **EASTSOUND** WASTEWATER

DRAWN

§ ~

PHASE

**Z**z

~

Ш

FILTER FABRIC MATERIAL, ATTACH FABRIC TO POSTS OR MESH WITH LOOPS OR STAPLES BY 4. STD OR BETTER -WIRE MESH -FILTER FABRIC PROVIDE 34" TO 11/9"
WASHED GRAVEL ON BOTH
SIDES OF FENCE & TRENCH

2" X 2" X 14 GAGE WIRE MESH OR EQUAL


BOTTOM OF FILTER-FABRIC BURIED IN 4" X 4" TRENCH

NOTE: SEE WSDOT STANDARD PLAN I-30.10-02 OR I-30.15-02. FOR HIGH VISIBILITY FENCE, SEE WSDOT STANDARD PLAN I-30.16-01 OR I-30.17-01.

FILTER FABRIC FENCE NOT TO SCALE

**NOT TO SCALE** 





THIS SHEET SHOWS BOTH EXISTING AND PROPOSED CONDITIONS. FOR EXISTING CONDITIONS ONLY SEE SHEET CO.1.

# CONSTRUCTION NOTES:

NOTE: ALL CONSTRUCTION PHASING STEPS SHALL BE COORDINATED WITH THE OWNER AND ENGINEER.

- (1) EXISTING BUILDING OVER DEWATERING SYSTEM.
- (2) EXISTING BUILDING OVER TRAIN 1 AND TRAIN 2.


# PROPOSED CONSTRUCTION SEQUENCE INFO:

CRITICAL PATH FOR THIS PROJECT WILL BE CONTROLLED BY THE FOLLOWING 3 STAGES OF

- STAGE 1
  A. TAKE TRAIN 1 OFFLINE: SPRING 2025
- B. PROVIDE TEMPORARY AIR PIPING FROM NEW BLOWER (#3) TO TRAIN 2: SPRING 2025
- C. CONFIGURE TEMPORARY 208/120V POWER TO TRAIN 2 (LIGHTING, CLARIFIER, RECEPTACLES,
- D. TRAIN 1 EXISTING BUILDING REMOVAL (INCLUDING ALL EXIST. BLOWER EQUIPMENT): SPRING
- 2025

  E. TAKE SLUDGE DEWATERING EQUIPMENT OFFLINE AND BUILD PROTECTIVE PLYWOOD ENCLOSURES AROUND ALL EXISTING EQUIPMENT IN THE DEWATERING BUILDING: SUMMER 2025 (SEE DEWATERING BUILDING EQUIPMENT PROTECTION PLAN ON SHEET A1.4)
- F. REMOVE AND REPLACE DEWATERING BUILDING: SUMMER/FALL 2025
- A. TRAIN 1 NEW CONCRETE: WINTER/SPRING 2025 & 2026
- B. TRAIN 1 NEW EQUIPMENT INSTALLATION: SPRING/SUMMER/FALL 2026
- C. TRAIN 1 START UP: SUMMER/FALL/WINTER 2026
- A. TAKE TRAIN 2 OFFLINE: AFTER STAGE 2 IS COMPLETED: FALL/WINTER 2026
- B. DISCONTINUE AND ABANDON THE TEMPORARY 208/120V POWER TO TRAIN 2: FALL/WINTER (ALL OTHER RESIDUAL 208/120V POWER NEEDS ARE TO BE SUPPLIED VIA NEW SERVICES)
- C. TRAIN 2 EXISTING BUILDING REMOVAL: FALL/WINTER 2026.
- D. TRAIN 2 NEW CONCRETE: WINTER/SPRING 2027.
- E. TRAIN 2 NEW EQUIPMENT INSTALLATION: SPRING/SUMMER 2027.
- F. TRAIN 2 START UP: SUMMER/FALL 2027.

NOTE: ALL OTHER WORK ITEMS ARE TO BE COMPLETED IN A TIMELY MANNER. CONTRACTOR TO CONSIDER WEATHER AND WORKLOAD WHEN SCHEDULING NON CRITICAL PATH WORK ITEMS. EVERYTHING IS TO BE COMPLETED WITHIN THE AGREED CONTRACT TIME PERIOD.





**BID SET** 

Zž 馬馬 WILSONENGINEERING, ш Z



MCS


DISTRICT S S PHASE WATER


AND


SEWER

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE **EASTSOUND** 

91 9 0 OF. 18








# PIPE IDENTIFICATION LEGEND EXISTING 8" EXISTING EFFLUENT (DI GRAV.) EXISTING 4" BUILDING SEPTIC (SCH. 80 PVC GRAV.) SLOPE = 2% MIN. 8" TRAIN 2 INFLUENT (DI GRAV.) SLOPE = 0.4% MIN. 8" TRAIN 1 INFLUENT (DI GRAV.) SLOPE = 0.4% MIN. 2" WAS (SCH. 80 PVC GRAV.) SLOPE = POSITIVE DRAINAGE THROUGHOUT 8" TRAIN 2 EFFLUENT (DI GRAV.) SLOPE = 0.4% MIN. (CONNECT TO EXISTING) EXISTING 1" YARD HYDRANTS (3) LOCATIONS 8" TRAIN 1 EFFLUENT (DI GRAVITY) SLOPE=0.4% MIN. (CONNECT TO 8 EXISTING) 6" BASIN 1 AIR (MATERIAL PER SPEC 33 31 00) 6" BASIN 2 AIR (MATERIAL PER SPEC 33 31 00) NOTE: CONTRACTOR TO FIELD CUT AND MODIFY EXISTING PIPE STUB AS NEEDED TO PROVIDE ROOM FOR PROPOSED FITTINGS 6" VERTICAL ELBOW (MATERIAL PER SPEC 33 31 00) (12) 1" 2W WATER LINE (HDPE) RELOCATION OF BLADDER TANKS AND NEW SHELTER (SEE DTL 1/C6.6) EX SS DRAIN FROM EX VERTICAL SCREW PRESS TO REMAIN PROPOSED STORM DRAIN PIPING (TYP), SEE SHEET C2.1 8" GATE VALVE FOR TRAIN 1 ISOLATION 4" INFLUENT PUMP STATION DISCHARGE PORT

- 1) SEE SHEET CO.1 FOR EXISTING CONDITIONS.
- 2) SEE SHEETS C2.1—C2.2 FOR GRADING, STORM DRAINAGE, AND PIPING.






**BID SET** 


AND WATER DISTRICT NAS V PHASE COUNTY WASTEWATER TREATMENT PLANT UPGRADE -SEWER **EASTSOUND** 91


 $\sim$ 

 $\Box$ 

P







INFLUENT DISCHARGE PORT & SLUDGE BOX PLAN

HORIZONTAL SCALE

IDENTIFICATION LEGEND

(2) CORE NEW HOLE DIRECTLY INTO WETWELL WALL

ALL CAMLOCK ACCESSORIES/FITTINGS ARE TO BE STAINLESS STEEL. PROVIDE FITTINGS AS NEEDED FOR WATER TIGHT ASSEMBLY.

6 20 CY SLUDGE BOX WITH SELF-LEVELING COVER SYSTEM

7 NEW PORTABLE DAVIT CRANE

SLUDGE BOX TRENCH DRAIN PER

C6.4

9 NEW DEWATER BUILDING PER SHEETS A1.1-A1.3

NEW 8"-THICK CONCRETE PAD SLOPING TO CENTERED TRENCH DRAIN PER (10)

NEW CONC STEPS TO EX EQ PAD @ 1.00% SLOPE FOR DRAINAGE. 6" EMBEDMENT BELOW FG.

CONCRETE CRANE ANCHOR AND DAVIT CRANE BASE PER DTL 3, SHEET C6.6

PROPOSED INFLUENT DISCHARGE PORT (4" CAMLOCK AND COVER)

COMPOSITE UTILITY VAULT WITH TRAFFIC RATED LID PROVIDED BY OWNER

5 AKALINITY STATION SHELTER PER

C6.3

12 MATCH RIM ELEV OF ALL EX VAULTS

CAREFULLY SLOPE CONCRETE AWAY FROM DOORWAY AT 0.8% SLOPE MIN. IF POSITIVE SURFACE SLOPE CAN NOT BE ACHIEVED, CONTACT THE ENGINEER.

GRADE BREAK

Call 811 two business days before you dig

DISTRICT S &S PHASE SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE **AND WATER** SEWER **EASTSOUND** 

91


OF

23

2

 $\Box$ 

JGC DRAWN BY MCS



HORIZONTAL SCALE

INFLUENT DISCHARGE PORT & SLUDGE BOX PROFILE

(A)

IDENTIFICATION LEGEND

1 CONCRETE CRANE ANCHOR AND DAVIT CRANE BASE PER DTL 3, SHEET C6.6

2 CORE NEW HOLE DIRECTLY INTO WETWELL WALL

3 SLUDGE BOX TRENCH DRAIN

PROPOSED 4" SCH 80 PVC TEE AND DROP PIPE AS SHOWN. PROVIDE RESTRAINTS FOR WATER TIGHT CONNECTION SUITABLE FOR 100 PSI SURGE PRESSURE APPLICATIONS

PROPOSED INFLUENT DISCHARGE PORT (4" CAMLOCK W/ LOCKING CAP)

5 ALL CAMLOCK ACCESSORIES/FITTINGS ARE TO BE EITHER ALUMINUM OR STAINLESS STEEL. PROVIDE FITTINGS AS NEEDED FOR WATER TIGHT ASSEMBLY

6 COMPOSITE UTILITY VAULT WITH TRAFFIC RATED LID PROVIDED BY OWNER AND INSTALLED BY CONTRACTOR

7 PROPOSED FIBER OPTICS CONDUIT

8 PIPE SUPPORT PER DTL 5, SHEET C6.2

9 NEW DEWATER BUILDING NORTH WALL

10 20 CY SLUDGE BOX WITH SELF-LEVELING COVER SYSTEM

\(\frac{11}{12}\) PORTABLE DAVIT CRANE PER SPEC\(\frac{12}{12}\) SLUDGE BOX CRANE SYSTEM (SEE SHEET C5.4)\(\frac{13}{13}\) SECONDARY CONVEYOR (SEE SHEET C5.4)

EASTSOUND SEWER AND WATER DISTRICT

SAN JUAN COUNTY

WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2

INFLUENT DISCHARGE PORT & SLUDGE BOX PROFILE

91

P

24

9


 $\dot{\mathbf{C}}$ 

JGC DRAWN BY MCS


WICSON ENGINEERING

WILSONENGINEERING, COM







10.	REVISIONS	BY	DATE	









DENT	IFICATION LEGEND
1	(2)-90° VERTICAL BENDS TRANSITION TRAIN 1 AERATION PIPE UNDERGROUND & REDIRECT FLOW EAST.
2	90° HORIZONTAL BEND
3	(2)-90° VERTICAL BENDS TRANSITIONS TRAIN 1 AERATION PIPE ABOVE GRADE.
4	TRAIN 1 AIR HEADER (CATWALK NOT SHOWN IN PROFILE)
(5)	45° HORIZONTAL BEND (TYP)
6	FINISHED GRADE (VARIES, ~23.15')
7	TRAIN 2 INFLUENT PIPE (12"Ø DI)
8	EXISTING BLOWER
9	CARBON FEED SHELTER PER SPEC
(10)	TRAIN 2 AIR HEADER (CATWALK NOT SHOWN IN PROFILE)
(11)	PROPOSED TRENCH DRAIN (SEE SHEET C2.1)
(12)	4" STORM DRAIN @ 0.7% MIN
(13)	TYPE 1 CB (SEE SHEET C2.1)
(14)	PIPE SUPPORT




SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2 **EASTSOUND SEWER AND WATER DISTRICT** 91  $\infty$ 

OF

26

C

WILSONENGINEERING.COM




三 元 WILSONENGINEERING. Ш Z ø


STORM DRAINAGE PLAN


GRADING


OF


DATE 1-27-2025 SCALE AS SHOWN JOB NUMBER 2023-123 91





















DRAINAGE NOTE
ROUTE 4"Ø FOOTING DRAIN FROM THE
NEW DEWATERING BUILDING TO THE
DEWATER SUMP PUMP STATION.
FOOTING DRAIN PER 3 52.2



AND WATER DISTRICT PHASE 2 SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE -**EASTSOUND SEWER** 

> 91 P

> 36

4

**DEWATER SUMP PUMP STATION SECTION** 

HORIZONTAL SCALE



EX ASPHALT—PAVING **DEWATER SUMP PUMP STATION PLAN** 

10

HORIZONTAL SCALE

DEWATERING PS STARTER PANEL PER

EX 4'Ø DEWATERING-PUMP STATION

NEW DEWATERING BUILDING

CABLE HANGER ANCHORED
TO ECCENTRIC CONE

EX LADDER-

TRENCH DRAIN (REFER TO C2.1 FOR ADDITIONAL

-2"ø PVC SCH 40

ELECTRICAL CONDUIT

(1)-6"Ø CORING INTO EX MH & GROUT AROUND NEW PIPES


-PIPE, SUPPORT


-2'X2'X2.5' CONC DAVIT CRANE BASE


W/ SOCKET MOUNT

(TYP)

—EX DIGESTER WALL







SLUDGE BOX AND COVER SYSTEM - SOUTH ELEVATION VIEW

SLUDGE BOX AND COVER SYSTEM - EAST ELEVATION VIEW

## SHEET NOTES:

- SHEET NOTES:

  1) ANY CONDUIT OR OTHER CONNECTION FOR MOTION FAILURE ALARM AND LEVEL SENSOR TO BE FLEXIBLE TO ALLOW LIFTING OF COVER.

  2) ALL SUPPORT MEMBERS ARE TO BE LEVELED AND ANCHORED INTO CONCRETE FLOOR PER MANUFACTURER RECOMMENDATIONS.

  3) ALL ANCHORING HARDWARE IS TO BE STAINLESS STEEL.
- 4) ANCHOR SIZE AND EMBEDMENT DEPTH IS TO BE PER MANUFACTURER RECOMMENDATIONS.



**BID SET** 

WILSONENGINEERING.COM

DRAWN B

WASF

PHASE

ı

COUNTY WASTEWATER TREATMENT PLANT UPGRADE

91


P

38

SEWER

**EASTSOUND** 

 $\mathbf{C}$ 



HORIZONTAL SCALE

KEYED NOTES

1 = NEW 20 CY SLUDGE CONTAINMENT BOX PER SPECS

 $\langle 2 \rangle$  = NEW LEVEL-LOADER LID FOR SLUDGE BOX PER SPECS

 $\langle \overline{15} \rangle$  = APPROX LOCATION OF EX 6" PVC STORM DRAIN

(16) = support beam for secondary screw conveyor per (3) (52.1)



3 = NEW CRANE FOR LEVEL-LOADER LID

4 = secondary conveyor to discharge directly into level loader hopper via connected flexible chute

5 = FLEXIBLE CHUTE

6 = TRENCH DRAIN PER SPECS TO CONNECT TO EX 6" VERTICAL STUB. CONCRETE ENCASEMENT AROUND TRENCH PER STRUCTURAL

7 = EXISTING DEWATERING SCREW PRESS

8 = EXISTING WAS PUMPS FOR TRAINS 1, 2, & 3

9 = EXISTING SS INFLUENT PUMP STATION VAULT

 $\overleftarrow{10}$  = EXISTING PRESSATE LINE DISCHARGES INTO EX PUMP STATION VAULT

11 = NEW 8"-THICK CONCRETE SLAB PER  $\frac{4}{C6.3}$ 



 $\langle 12 \rangle$  = EX CLEANOUT TO PRESSATE LINE. ENSURE LID IS FLUSH WITH TOP OF NEW CONCRETE SLAB.

(13) = CONTRACTOR TO FRAME AND FLASH AROUND WALL PENETRATION FOR SECONDARY CONVEYOR EQUIPMENT.

14 = NEW HOIST FOR LEVEL-LOADER LID



DISTRICT

**AND WATER** 

SEWER,

**EASTSOUND** 

VASF

PHASE

WASTEWATER TREATMENT PLANT UPGRADE

91


P

39

Call 811 two business days before you dig

**BID SET** 

 $\infty$  $\mathbf{\nabla}$ 



KEYED NOTES

1 = NEW 20 CY SLUDGE CONTAINMENT BOX PER SPECS

2 = NEW LEVEL-LOADER LID FOR SLUDGE BOX PER SPECS

3 = NEW CRANE FOR LEVEL-LOADER LID

4 = SECONDARY CONVEYOR TO DISCHARGE DIRECTLY INTO LEVEL LOADER HOPPER VIA CONNECTED FLEXIBLE CHUTE

(5) = STAINLESS STEEL TRIPOD TO SUPPORT SECONDARY CONVEYOR

6 = TRENCH DRAIN PER SPECS TO CONNECT TO EX 6"
VERTICAL STUB. CONCRETE ENCASEMENT AROUND
TRENCH PER STRUCTURAL

7 = NEW SECONDARY CONVEYOR CONNECTS TO PRIMARY CONVEYOR CHUTE

8 = EX PRIMARY CONVEYOR

9 = EXISTING SS INFLUENT PUMP STATION VAULT

 $\fbox{10}$  = existing pressate line discharges into ex pump station vault

 $\langle 11 \rangle$  = NEW 8"-THICK CONCRETE SLAB PER  $\langle 4 \rangle$ 

 $\langle 12 \rangle$  = EX CLEANOUT TO PRESSATE LINE. ENSURE LID IS FLUSH WITH TOP OF NEW CONCRETE SLAB.

(13) = CONTRACTOR TO FRAME AND FLASH AROUND WALL PENETRATION FOR SECONDARY CONVEYOR EQUIPMENT.

 $\boxed{14}$  = SUPPORT BEAM FOR SECONDARY SCREW CONVEYOR PER  $\boxed{\frac{3}{52.1}}$ 

(15) = APPROX LOCATION OF EX 6" PVC STORM DRAIN

 $\overline{\mbox{16}}$  = STAINLESS STEEL CHUTE FROM PRIMARY CONVEYOR TO SECONDARY CONVEYOR





DISTRICT **V**AS PHASE COUNTY WASTEWATER TREATMENT PLANT UPGRADE **AND WATER** 

SEWER

**EASTSOUND** 

2

91

40


WILSON ENGINEERING


JGC
DRAWN BY
MCS
CHECKED BY


EASTSOUND SEWER AND WATER DISTRICT


SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2

WILSONENGINEERING.COM









Call 811 two business days before you dig

91  $\mathbf{\nabla}$ P  $\mathbf{\nabla}$ **BID SET** 4

C6.3

6' CONCRETE WHEEL STOP

-NO. 5 REBAR (2 PER WHEEL STOP) MCS

§ ~ DISTRIC PHASE PLANT UPGRADE WATER AND

TREATMENT

SEWER **EASTSOUND** WASTEWATER

. O

P

42

FINISH GRADE AND SURFACING IS TO 24" CAST IRON FRAME AND COVER, SEE NOTE 1. MATCH SITE PLAN - CONCRETE COLLAR. WATERTIGHT SEAL (TYP.). SEE NOTE 2. SEE NOTE 3. #4 REBAR LOOP 6" X 6" NON-SHRINK - CONCRETE CIRCULAR ADJUSTMENT SECTIONS

- CONCRETE CIRCULAR EXTENSION AS REQUIRED

AS REQUIRED.

4" SS FLOOR DRAIN (TYPICAL) 1% SLOPE (MIN) CONCRETE SLAB

TYPICAL FLOOR DRAIN

**NOT TO SCALE** 

NOTES:

SEE NOTE 2.

WATERTIGHT SEAL

GROUT AROUND BASE OF

RISER FOR STABILIZATION.

1. MANHOLE FRAME AND COVER SHALL BE PLACED AT GRADE AND LEVEL

2. ASPHALTIC SEALANT SHALL BE USED, RAMNEK OR EQUAL, TO PROVIDE WATERTIGHT SEAL BETWEEN TANK AND RISER AND GRADE RINGS.

3. 12" WIDE BY 8" THICK STEEL REINFORCED CONCRETE COLLAR INSTALLED AROUND RISERS IN ALL TRAFFIC RATED AREAS.

TRAFFIC RATED RISER AND LID DETAIL

**NOT TO SCALE** 

-MOUNT "STATE DISABLED PARKING PERMIT REQUIRED" SIGN TO SIDE OF BUILDING EDGE OF SIDEWALK-FLUSH WITH ASPHALT -WHEEL STOP PER HANDICAP SYMBOL FOR EACH-HANDICAP PARKING SPACE 9.0' MIN "VAN" LABEL FOR EACH VAN-HANDICAP SPACE, (PAVEMENT 5' MIN MARKING & SIGN POST) STALL STRIPE - 4" WIDE, WHITE -ACCESS AISLE - 24" WIDE STRIPES WITH 24" GAPS, WHITE

\*\* STRIPING SHALL BE THERMOPLASTIC MATERIAL (NOT PAINT) AND CONFORM TO WSDOT 8-22 AND SJCC 18.30.630(A)(4)

> PARKING STALL STRIPING **NOT TO SCALE**

> > SIDEWALK

DRIVE REBAR FLUSH-WITH TOP OF WHEEL STOP


C6.2

SIDE VIEW


FRONT VIEW


WHEEL STOP

**NOT TO SCALE** 



**NOT TO SCALE** 





- 3. TRACER WIRE CONNECTIONS AT THE TRACER WIRE BOX SHALL BE WRAPPED WITH CORROSION RESISTANT TAPE.
- 5. CONTRACTOR SHALL PERFORM A CONDUCTIVITY/LOCATE UPON COMPLETION OF THE INSTALLATION.

4. LOOP 18"-24" OF EXTRA TRACER WIRE AT BOTH THE PIPE AND THE TRACER WIRE BOX.

- 6. TRACER WIRE IS TO BE PROVIDED FOR ALL NEW WATER PIPING. BOXES TO BE LOCATED NEXT TO ALL BUILDINGS OR STRUCTURES WHERE PIPE ENTERS. FINAL LOCATIONS TO BE SUBMITTED TO THE ENGINEER.

**NOT TO SCALE** 

TRACER WIRE LOCATER BOX DETAIL

Call 811 two business days before you dig **BID SET** 

NOTE: PROVIDE 1/4" NEOPRENE CUSHION LINER IN ALL PIPE

SUPPORTS.

. O

P

43

TREATMENT WASTEWATER AS SHOWN

-PASSING PIPE

TOP OF FLOOR

STANDARD WEIGHT

316 STAINLESS STEEL PIPE SLEEVE

FILL ANNULAR SPACE WITH— WATERPROOF DOW CORING 732 RTV SILICONE SEALANT. JOINT SHALL BE

1/4" THICK x 2" HIGH SEEP RINGCENTERED

6

IN SLAB-

FLOOR SLEEVE DETAIL

WATERTIGHT.

SEEP RING -STANDARD WEIGHT 316 STAINLESS STEEL PIPE SLEEVE PLUS 1" MIN PASSING PIPE, SIZE AS SHOWN

- FILL ANNULAR SPACE WITH WATERPROOF DOW CORING 732 RTV SILICONE SEALANT. CONCRETE WALL JOINT SHALL BE WATERTIGHT.


> PIPE SLEEVE DETAIL **NOT TO SCALE**





**BID SET** 

- 1. TO INSURE PROPER SUPPORT AND STABILITY, AFTER FINAL HEIGHT ADJUSTMENT IS ATTAINED, APPLY TACK WELDS TO BOTH SUPPORT CUPS AND EXTENSION PIPE.
- 2. MATERIAL: 100% 304 STAINLESS STEEL.
- 3. FIELD PAINT AS SPECIFIED.
- 4. SUPPORT: STANDON MODEL C92 ADJUSTABLE PIPE SADDLE CLAMP SUPPORT OR EQUAL.



PIPE SUPPORT DETAIL **NOT TO SCALE** 

5

# MEDIUM-DUTY CONCRETE PAVEMENT DETAIL **NOT TO SCALE**

COMPACTED SUBGRADE

TO 95% OPTIMUM DENSITY (ASTM D1557).

- <u>CONTROL JOINT</u>, 1/4" X 1" TOOLED JOINT MAX CONTROL JOINT SPACING 12-FEET O.C. EACH WAY. MATCH EXISTING SCORING PLAN.

BROOM FINISH, SMOOTH BORDER FINISH, TYPICAL. (FINISH TO MATCH ADJACENT PAVING)

· <u>EXPANSION JOINT</u> 1/2" WIDE BY FULL DEPTH PRE—MOLDED JOINT FILLER.

THRUST BLOCK TABLE MINIMUM BEARING AREA AGAINST UNDISTURBED SOIL IN SQUARE FEET

12

20

32

9

16

24

-GROUND LINE

5

8

13

-2-1" DIA. RODS EXCEPT

FOR 2" PVC, SEE NOTE 6

AS DIRECTED BY ENGINEER

TRENCH BOTTOM

SEE NOTE 6

.3

PIPE

12"

16"

20"

16


29

45

MAX EXPANSION JOINT SPACING 36 FEET O.C. EACH WAY. MATCH EXISTING SCORING PLAN.

- EXISTING SURFACE OR PROPOSED STRUCTURE

NOIE: SET BARS ON ADOBE BLOCKS OR CHAIRS BEFORE CONCRETE PLACEMENT — DO NOT PULL UP INTO PLASTIC CONCRETE





CONCRETE WALKWAY

(6" THICK MIN)

#3@12" OC

2" OF COMPACTED — CRUSHED SURFACING TOP COURSE.






(PARTIAL RESTRAINT MUST BE PROVIDED BY PIPELINE BEYOND VALVE)

- 1. SQUARE FEET OF CONCRETE THRUST BLOCK AREA IS BASED ON 200 P.S.I. INTERNAL PRESSURE, A SOIL SAFE BEARING OF 3000 POUNDS PER SQUARE FOOT AND A FACTOR OF SAFETY OF 1.5.
- 2. BEARING AREA MUST BE ADJUSTED FOR INTERNAL PRESSURES AND LOWER SOIL BEARING
- 3. CONCRETE BLOCKING SHALL BE CAST IN PLACE AND HAVE A MINIMUM OF 1/4 SQUARE FOOT BEARING AGAINST THE FITTING.
- 4. BLOCK SHALL BEAR AGAINST FITTINGS ONLY AND SHALL BE CLEAR OF JOINTS TO PERMIT TAKING UP OR DISMANTLING JOINT.
- 5. THE CONTRACTOR SHALL INSTALL BLOCKING WHICH IS ADEQUATE TO WITHSTAND FULL TEST PRESSURE AS WELL AS TO CONTINUOUSLY WITHSTAND OPERATING PRESSURE UNDER ALL CONDITIONS OF

VERTICAL BEND

- 6. STAINLESS STEEL BANDING SHALL BE USED AT 2" PVC VERTICAL BENDS INSTEAD OF 1" RODS. CONTACT ENGINEER FOR SIZING OF THRUST BLOCK AND DETAILS.
- 7. ALL BENDS, TEES & CROSSES SHALL INCLUDE RESTRAINED JOINTS (ROMAC GRIPPER) AS WELL AS THRUST BLOCKING.





`PIPE CLAMP, 1/4" THICK MIN. STAINLESS STL. BAR SIZE TO FIT PIPE.

**VERTICAL PIPE BRACE** 

NOT TO SCALE

WATER AND TREATMENT **SEWER EASTSOUND** WASTEWATER

DATE
1-27-2025
SCALE
AS SHOWN
JOB NUMBER
2023-123 . O  $\infty$ 9 P

4-1/2" I.D.ø (MIN) CAST IRON VALVE BOX -3-1/2"Ø BERNTSEN FLAT BRONZE CONCRETE SURVEY MARKER #C35FB. SEE DETAIL BELOW. - CONCRETE PAD **BURIED VALVES (TYP.)** (2.5'x2.5'x4" THICK)

**BURIED VALVE IDENTIFICATION LEGEND (C1.3)** 

(16) 8" GATE VALVE FOR TRAIN 1 ISOLATION


4" GATE VALVE FOR INFLUENT PS DRAIN PIPE CONNECTION

#### BURIED VALVE LABELING SCHEDULE

1/4" TALL BERNTSEN STANDARD TEXT STYLETO BE STAMPED BY BERNTSEN. THE TEXT
"VALVE #" IS TO BE OFFSET AS SHOWN TO
ALLOW ROOM FOR THE ENGRAVED ONE OR
TWO DIGIT VALVE NUMBER PRECEDING IT TO
BE CENTERED WITHIN THIS LINE OF TEXT.
THIS TEXT TO REMAIN THE SAME PER EACH
VALVE LABEL MARKER VALVE LABEL MARKER.

NOTES:
1) 14 BRONZE VALVE LABELING
MARKERS TO BE FURNISHED AND
INSTALLED AT LOCATIONS ACCORDING TO

2) SHEET C2.4 & C2.5 IS SCHEMATIC AND IS NOT INTENDED TO SHOW PRECISE LOCATIONS OF THE VALVES TO BE MARKED.



3-1/2"Ø BERNTSEN FLAT BRONZE CONCRETE SURVEY MARKER #C35FB.


1/4" BERNTSEN STANDARD OUTSIDE TEXT STYLE. TO BE STAMPED BY BERNTSEN. THIS TEXT TO REMAIN THE SAME PER EACH VALVE LABEL MARKER.

1/4" TALL TEXT TO BE ENGRAVED. STYLE TO MATCH BERNTSEN'S. DIGITS CHANGE PER EACH VALVE LABEL MARKER. TEXT IS TO READ THE VALVE NUMBER DIGIT(S) FROM THE VALVE NUMBER COLUMN IN THE VALVE LABELING SCHEDULE ON THIS SHEET.

1/4" TALL TEXT TO BE ENGRAVED. STYLE TO MATCH BERNTSEN'S. TEXT CHANGES PER EACH VALVE LABEL MARKER. TEXT IS TO READ THE DESCRIPTION THAT CORRESPONDS WITH THE VALVE NUMBER COLUMN IN THE VALVE LABELING SCHEDULE ON THIS SHEET. TEXT IS TO BE CENTERED IN THIS LINE AS SHOWN.

1/4" BERNTSEN STANDARD OUTSIDE TEXT HEIGHT AND STYLE. TO BE STAMPED BY BERNTSEN. THIS TEXT TO REMAIN THE SAME PER EACH VALVE


## TYPICAL BURIED VALVE LABEL MARKER **NOT TO SCALE**



**GRAVEL SURFACING SECTION NOT TO SCALE** 

4" COMPACTED DEPTH, HMA CLASS-1/2": PG 58H-22 (TWO 2" LIFTS) HMA PER WSDOT 5-04, 91% MIN. DENSITY, COMMERCIAL CLASSIFICATION THICKENED EDGE ALONG
OUTSIDE PERIMETER OF PAVING.
NOT REQUIRED IF ABUTTING 4" COMPACTED DEPTH, CRUSHED-SURFACING BASE COURSE, PER WSDOT 9-03.9(3) FXISTING PAVEMENT COMPACTED SUBGRADE: SUITABLE APPROVED SUBGRADE OR GRAVEL -12" COMPACTED DEPTH, GRAVEL BASE PER WSDOT 9-03.10. BORROW MIN 95% OPTIMUM DENSITY

STANDARD ASPHALT SECTION-FOR AREAS WITH NO CURB



ASPHALT CONCRETE PAVEMENT WITH THICKENED EDGE

HEAVY-DUTY CONCRETE PAVEMENT DETAIL


**NOT TO SCALE** 


**BID SET** 

Call 811 two business days

two business days before you dig

**NOT TO SCALE** 







12" MIN PER (2)  $\oplus$ **GRASS AREAS GRAVEL OR PAVED AREAS** 

> TYPICAL TRENCHING & BACKFILL NOT TO SCALE


- KEYED NOTES
- A. HYDROSEED EXPOSED AREAS.
- B. SEE SURFACING PLAN, SHEET C2.2
  AT A MINIMUM:
  GRAYEL: NEW CRUSHED SURFACING TOP COURSE
  (CSTC) LAYER PER WSDOT 9-03.9(3).
  PAYED: HMA CL 1/2" APPLIED IN 2 LIFTS MIN. TO
  THICKNESS MATCHING EX. SECTION (4" MIN.) PER WSDOT 5-04.2, WITH 2" CSTC LAYER BELOW. HOWEVER, FINAL SURFACING WORK IS TO BE COMPLIANT WITH THE SURFACING PLAN AND THE SPECIFIED DETAILS.
- C. NEW TOPSOIL LAYER MIN 4".
- D. 2" METALLIC DETECTOR TAPE 8" TO 12" BELOW FINISH GRADE.
- E. BANK RUN GRAVEL BACKFILL PER WSDOT 9-03.19 COMPACTED TO 95% MAX. DENSITY INSIDE RIGHT-OF-WAY.
- F. PIPE ZONE GRAVEL BEDDING PER WSDOT 9-03.12(3) COMPACTED TO 95% MAX. DENSITY.
- G. UNDISTURBED NATIVE MATERIAL.
- H. SELECT NATIVE BACKFILL COMPACTED TO 95% MAX. DENSITY.
- #10 AWG INSULATED TRACER WIRE ON NONMETALLIC PIPE (IN ADDITION TO 2" DETECTOR TAPE)




POWER SUPPLY (SEE NOTE 2)



TYPICAL EQUIPMENT PAD NOT TO SCALE



TRENCH DRAIN DETAIL NOT TO SCALE



STANDARD FRAME WSDOT STANDARD DETAIL B30.10-00 CASTING TYPE B



HERRINGBONE GRATE WSDOT STD PLAN B-30.50-00 INSTALL WHERE ROAD SLOPE 4% OR LESS



**CATCH BASIN CASTING TYPES NOT TO SCALE** 



**BID SET** 

91

DRAWN F

S &

PHASE

COUNTY WASTEWATER TREATMENT PLANT UPGRADE

DISTRIC

WATER

AND

SEWER

**EASTSOUND** 

OF.




**EASTSOUND** WASTEWATER


9 46

REFER TO WSDOT STANDARD PLAN NUMBER B-5.20-03 FOR ADDITIONAL INFORMATION


PIPE ALLOWANCES	
PIPE MATERIAL	MAXIMUM INSIDE DIAMETER (INCHES)
REINFORCED OR PLAIN CONCRETE	12"
ALL METAL PIPE	15"
CPSSP* (STD. SPEC. SECT. 9-05.20)	12"
SOLID WALL PVC (STD. SPEC. SECT. 9-05.12(1))	15"
PROFILE WALL PVC (STD. SPEC. SECT. 9-05.12(2))	15"

\*CORRUGATED POLYETHYLENE STORM SEWER PIPE





# **CATCH BASIN TYPE 1 NOT TO SCALE**



GENERAL NOTE: FIELD DETERMINE DAVIT CRANE LOCATION; FOR BEST ACCESS.

TYPICAL MEDIUM-DUTY DAVIT CRANE DETAIL **NOT TO SCALE** 

#### NOTES:

1) AS ACCEPTABLE ALTERNATIVES TO THE REBAR SHOWN IN THE PRECAST BASE SECTION, FIBERS (PLACED ACCORDING TO THE STANDARD SPECIFICATIONS), OR WIRE MESH HAVING A MINIMUM AREA OF 0.12 SQUARE INCHES PER FOOT SHALL BE USED WITH THE MINIMUM REQUIRED REBAR SHOWN IN THE ALTERNATIVE PRECAST BASE SECTION. WIRE MESH SHALL NOT BE PLACED IN THE KNOCKOUTS.

2) THE KNOCKOUT DIAMETER SHALL NOT BE GREATER THAN 20" (IN). KNOCKOUTS SHALL HAVE A WALL THICKNESS OF 2" (IN) MINIMUM TO 2.5" (IN) MAXMUM. PROVIDE A 1.5" (IN) MINIMUM GAP BETWEEN THE KNOCKOUT WALL
AND THE OUTSIDE OF THE PIPE.
AFTER THE PIPE IS INSTALLED,
FILL THE GAP WITH JOINT MORTAR IN ACCORDANCE WITH STANDARD SPECIFICATION SECTION 9-04.3.


3) THE MAXIMUM DEPTH FROM THE FINISHED GRADE TO THE LOWEST PIPE INVERT SHALL BE 5' (FT).

4) THE FRAME AND GRATE MAY BE INSTALLED WITH THE FLANGE DOWN, OR INTEGRALLY CAST INTO THE ADJUSTMENT SECTION WITH FLANGE UP.

5) THE PRECAST BASE SECTION MAY HAVE A ROUNDED FLOOR, AND THE WALLS MAY BE SLOPED AT A RATE OF 1 : 24

6) THE OPENING SHALL BE MEASURED AT THE TOP OF THE PRECAST BASE SECTION.

7) ALL PICKUP HOLES SHALL BE GROUTED FULL AFTER THE BASIN HAS BEEN PLACED.



2. THE KNOCKOUT SHALL NOT BE GREATER THAN 26" (IN), IN ANY DIRECTION. KNOCKOUTS SHALL HAVE A WALL THICKNESS OF 2" (IN) MINIMUM TO 2.5" (IN) MAXIMUM. PROVIDE A 1.5" (IN) MINIMUM GAP BETWEEN THE KNOCKOUT WALL AND THE OUTSIDE OF THE PIPE. AFTER THE PIPE IS INSTALLED, FILL THE GAP WITH JOINT MORTAR IN ACCORDANCE WITH STANDARD SPECIFICATION SECTION 9-04.3. 3. THE MAXIMUM DEPTH FROM THE FINISHED GRADE TO THE LOWEST PIPE INVERT SHALL BE 5' (FT). 4. THE FRAME AND GRATE MAY BE INSTALLED WITH THE FLANGE DOWN OR INTEGRALLY CAST INTO THE ADJUSTMENT SECTION WITH FLANGE UP. 5. THE PRECAST BASE SECTION MAY HAVE A ROUNDED FLOOR, AND THE WALLS MAY BE SLOPED AT A RATE OF 1 : 24 OR STEEPER. 6. THE OPENING SHALL BE MEASURED AT THE TOP OF THE PRECAST BASE SECTION. ONE #3 BAR FOR EACH -6"(IN) HEIGHT INCREMENT, SPACED EQUALLY 7. ALL PICKUP HOLES SHALL BE GROUTED FULL AFTER THE BASIN HAS BEEN PLACED. RECTANGULAR ADJUSTMENT SECTION St. S. #3 BAR EACH CORNER #3 BAR HOOP 18" (IN) MIN. REDUCING SECTION #3 RAR BASED ON WSDOT STD PLAN B05 40-03 01/26/17 (SEE NOTE 1)


NOTES:

AS ACCEPTABLE ALTERNATIVES TO THE REBAR SHOWN IN THE PRECAST BASE SECTION, FIBERS (PLACED ACCORDING TO THE STANDARD SPECIFICATIONS), OR WIRE MESH HAVING A MINIMUM AREA OF 0.12 SQUARE INCHES PER FOOT, SHALL BE USEI WITH THE MINIMUM REQUIRED REBAR SHOWN IN THE ALTERNATIVE PRECAST BASE

ALTERNATIVE PRECAST BASE SECTION

# TYPE 1L CATCH BASIN DETAILS NOT TO SCALE

PRECAST BASE SECTION




SHELTER EXTERIOR ELEVATION 4 NOT TO SCALE




BID SET

AS SHOWN JOB NUMBER 2023–123

. O P





KEYED NOTES

1 = 2" WAS FROM TRAIN #1

2 = 2" WAS FROM TRAIN #2

 $\boxed{3}$  = 2" WAS FROM TRAIN #3

 $\langle 4 \rangle$  = 2" SLUDGE FROM DIGESTER

 $\langle 5 \rangle$  = SOLENOID VALVE (TYP)

6 = GATE VALVE (2" TYP)

 $\langle 7 \rangle$  = WAS PUMP (TYP)

B = (1)-90° VERT BEND TRANSITIONS DIGESTER WAS PIPE ABOVE GRADE. (1)-90° BEND CONNECTS DIGESTER WAS PIPE TO TRAINS 1-3 WAS PIPE.

9 = (1)-90° 2" VERT BEND (1)-2" GATE VALVE (1)-90° 3" VERT BEND

10 = (2)-3" 90° VERT BENDS TRANSITION SCREW PRESS INFLUENT PIPE BELOW GRADE AND NORTH.

11 = NEW STRUCTURAL FOOTING (TYP)

(12) = ELECTRICAL PANELS (SEE SHEET E1.1)

(13) = APPROX LOC OF EX VERTICAL SCREW PRESS CONTROL PANEL

(14) = (2)-2" 90" VERT BEND TRANSITIONS DIGESTER INFLUENT PIPE BELOW GRADE.

= EX METAL BUILDING COLUMN AND FOOTING (TYP, TO BE REMOVED)

(16) = NEW YARD HYDRANT PROVIDED BY OWNER TO BE CONNECTED TO EX BURIED VALVE BY CONTRACTOR AFTER NEW BUILDING IS ERECTED

= EX EXPOSED CONCRETE VAULT TO REMAIN

(18) = 2'X2' CONCRETE PAD FOR BACK-UP POLYMER UNIT (MATCH ELEV OF WAS PUMP PAD)

(19) = EX SAWCUT TO BE REPAVED

20 = APPROX LOC OF EX VERTICAL SCREW PRESS TO REMAIN

(SEE SHEET A1.1)

22 = PROPOSED SECONDARY CONVEYOR

NOTE
PIPE GALLERY IS EXISTING, CONSTRUCTED IN
PHASE 1. THE NEW DEWATERING BUILDING
WILL BE ERECTED AROUND THE EXISTING
PIPING AND SCREW PRESS.

Call 811 two business days before you dig

**BID SET** 

PHASE

VILSON GINEERING

JGC DRAWN BY MCS

NAS V

DISTRICT

**WATER** 

AND

SEWER

WILSONENGINEERING.COM


SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE

**EASTSOUND** 

91 P

48

C



#### KEYED NOTES

- 1 = TEE INTO WAS PUMP #1
- 2 = TEE INTO WAS PUMP #2
- $\boxed{3}$  = TEE INTO WAS PUMP #3
- $\boxed{4}$  = INFLUENT FROM TRAINS 1, 2, & 3 MERGE
- 5 = INFLUENT FROM DIGESTER
- 6 = DISCHARGE FROM WAS PUMP #1
- 7 = DISCHARGE FROM WAS PUMP #2
- $\langle 8 \rangle$  = DISCHARGE FROM WAS PUMP #3
- 9 = WAS PUMP PER SPEC 22 13 36
- 10 = SOLENOID VALVE
- $\langle 11 \rangle$  = 2" PVC UNION
- (12) = 2" BALL VALVE (TYP)
- $\langle 13 \rangle$  = INFLUENT FROM TRAIN 1, 2, & 3
- $\boxed{14}$  = EFFLUENT TO DIGESTER
- (15) = 2" BALL VALVE BEFORE AND AFTER SOLENOID VALVE ON EACH INFLUENT LINE FROM TRAINS 1, 2, & 3
- 16 = EX FLOW METER TO DIGESTER
- 17 = EFFLUENT TO DEWATERING SKID
- (18) = 2"ø FEMALE CAMLOCK & CAP
- (19) = PIPE TRANSITIONS FROM 3" TO 2"Ø
- $\langle 20 \rangle$  = 2" BALL VALVE ON BOTH INLET AND OUTLET PIPING FOR PUMPS #1 & #3
- (21) = EX PIPE SUPPORT (TYP), EX GALV STEEL STRUTS MUST BE REPLACED WITH 304 SST AND ANCHORED TO THE NEW CONCRETE FLOOR AFTER REPAIRING EX SAWCUT.

NOTE
PIPE GALLERY IS EXISTING, CONSTRUCTED IN
PHASE 1. THE NEW DEWATERING BUILDING
WILL BE ERECTED AROUND THE EXISTING
PIPING AND SCREW PRESS.

SON ERENGE WILSONENGINEERING.COM





JGC DRAWN BY MCS

WASF

DISTRICT PHASE

WATER

AND

**SEWER** 


COUNTY WASTEWATER TREATMENT PLANT UPGRADE

**EASTSOUND** 

91 OF.

49

Call 811 two business days before you dig



MCS \ \ \ PHASE TREATMENT PLANT UPGRADE N COUNTY
WASTEWATER 1

91

OF.

1 = EX CONCRETE SLAB TO REMAIN (TYP)

2 = GUTTERS, DOWNSPOUTS, CONNECTING TO STORM SYSTEM AS SHOWN ON

 $\boxed{3}$  = NEW CONCRETE STEMWALL FOOTING PER

 $\boxed{4}$  = SOUTH WALL RECEDES 2.0'. SEE  $\boxed{\frac{-}{\text{A1.1}}}$ 


5 = WALL PENETRATION & FLASHING FOR SECONDARY CONVEYOR. CONTRACTOR TO ENSURE AIR—TIGHT SEAL.


THERMAL RESISTANCE OF MECHANICAL EQUIPMENT PENETRATIONS CALCULATIONS

SIX SIDE AIR BARRIER BOUNDARY AREA CALCULATION:

TOTAL WALL AREA = 1902.5 SF SUM THROUGH-WALL PENETRATIONS = (12.5 SF) SUM DOOR & GARAGE AREA = (180 SF) NET WALL AREA = 1710 SF

TOTAL PERCENT AREA OF WALL PENETRATION (12.5 SF / 1710 SF) \* 100% = 0.73%





WILSONENGINEERING.COM

JGC DRAWN BY MCS

washi - PHASE 2


SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE


91 P


21

A













HORIZONTAL SCALE

NOTE: CONTRACTOR SHALL PROVIDE PRE—ENGINEERED METAL BUILDING WITH SIMILAR COLUMN AND BRACING LAYOUT.







WILSONENGINEERING.COM


BUILDING INTERIOR ELEVATIONS

6


OF.

TEMPORARY PLYWOOD SHELLS
CONTRACTOR TO CONSTRUCT TEMPORARY PROTECTIVE PLYWOOD SHELLS AROUND ALL EXISTING EQUIPMENT IN THE DEWATERING BUILDING. PROTECTIVE PLYWOOD SHELLS ARE TO BE INSTALLED AND APPROVED PRIOR TO DEWATERING BLDG DEMOLITION WORK. DIMENSIONS SHOWN ARE APPROXIMATE. CONTRACTOR SHOULD VERIFY LENGTH, WIDTH, AND HEIGHT OF EXISTING EQUIPMENT FOR PROTECTIVE SHELLS.

PROVIDE ACCESS TO EQUIPMENT, AS NEEDED. IN PARTICULAR, THE WAS PUMP IS TO REMAIN ON-LINE AND OWNER ACCESS TO WAS PUMP, PIPING, AND VALVING IS TO BE MADE AVAILABLE THROUGHOUT THE ENTIRE STAGE 1 INTERIM PERIOD. IN ADDITION, ALL PROTECTIVE PLYWOOD SHELLS ARE TO BE COMPLETELY REMOVED AFTER THE NEW DEWATERING BUILDING STRUCTURE IS ERECTED.



SOUTH ELEVATION



EAST ELEVATION

## PROTECTIVE SHELLS PLAN & PROFILE





DISTRICT

AND WATER

SEWER

**EASTSOUND** 

A

VASF


PHASE


SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE

91 P

53


Call 811 two business days before you dig





## EX LAB ROOM WALL - NORTH ELEVATION





# EX LAB ROOM WALL - SOUTH ELEVATION



#### EQUIPMENT TO REMAIN

- 7 = EX DISTILLER TO BE RELOCATED
- 8 = ANALYTICAL BALANCE TO REMAIN
- 9 = EX SCALE STAND TO REMAIN
- (10) = EX SIDE TABLE TO REMAIN

 $\overline{\left(11\right)}$  = EX DISHWASHER TO BE REMOVED

 $\langle 12 \rangle$  = FUME HOOD BASE TO BE REPLACED

(13) = EX SHELF TO BE REMOVED (TYP)

(14) = EX FUME HOOD TO REMAIN

NOTE:

ALL DIMENSIONS OF EXISTING CABINETS AND APPLIANCES ARE APPROXIMATE.

JGC DRAWN BY MCS

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2

JAILE
1-27-2025
SCALE
AS SHOWN
JOB NUMBER
2023-123

A2.1

91


P

54

EASTSOUND SEWER AND WATER DISTRICT



PLOT SETTINGS: AutoCAD PDF (General Documentation).pc3, ANSI full bleed B (17.00 x 11.00 Inches), Portrait, 1:2, WE APWA_UNSCREENED.ctb W:\2023\2023\2023-123 ESWD WWTP UPGRADE PHASE 2 - DESION\DWG\VZ0020_2023-123 A2.1-A2.3 LAB UPGRADES.DWG - 1/28/Z025 9:12 AM -		Matthew Strittmatter
PLOT SETTINGS: AutoCAD PDF (General Documentation).pc3, ANSI full bleed B (17.00 x 11.00 Inches), W: \2023\2023-123 ESWD WWTP UFGRADE PHASE 2 - DESIGN\DWG\V2020_2023-123 A2.1-A2.3 LAB	/A_UNS	UPGRADES.DWG - 1/28/2025 9:12 AM - Matthew
PLOT SETT W:\2023\;	Ψ	2023—123 ESWD WWTP UPGRADE PHASE 2 — DESIGN\DWG\V2020_2023—123 A2.1—A2.3 LAB
	PLOT SET	W: \2023



FLOOR

EXISTING EXISTING

ROOM NAME

LAB

BASE

6" RB

WALL


EX GWB

PAINT

EX TILE


CEILING

PAINT



## LAB ROOM WALL - NORTH ELEVATION





## LAB ROOM WALL - SOUTH ELEVATION



### KEYED NOTES

- $\boxed{1}$  = REFRIGERATOR
- $\langle 2 \rangle$  = BOD INCUBATOR
- $\boxed{3}$  = DRYING OVEN
- $\langle 4 \rangle$  = DESICCATOR
- $\langle 5 \rangle$  = AUTOCLAVE
- $\langle 6 \rangle$  = FC INCUBATOR
- $\overline{7}$  = MICROSCOPE
- $\langle 8 \rangle$  = ANALYTICAL BALANCE
- 9 = SPECTROPHOTOMETER
- (10) = WALL-MOUNTED 50" TV
- (11) = 30" DEEP STAINLESS STEEL COUNTER WITH INTEGRAL 6" BACKSPLASH

MONITOR (SEE ELECTRICAL)

- $\langle 12 \rangle$  = DISTILLER
- $\boxed{13}$  = EX FUME HOOD TO REMAIN
- (14) = DUAL BASIN UNDERMOUNTED EPOXY SINK, INTEGRAL DRAINBOARD AT COUNTER, CONNECT TO EX PLUMBING
- $\langle 15 \rangle$  = DISHWASHER
- (16) = STANDING 48"x30" WORKSTATION (2 TOTAL)
- $\langle 17 \rangle$  = WALL-MOUNTED SHELF (STAINLESS STEEL)
- $\langle 18 \rangle$  = MUFFLE FURNACE
- (19) = UPPER CABINET WITH UNDER CABINET LIGHTING (TYP)
- 20 = EX SCALE STAND TO REMAIN
- $\langle 21 \rangle$  = 6" RUBBER WALL BASE (TYP)
- $\langle 22 \rangle$  = 24"-WIDE ACID STORAGE CABINET
- 23 = 24"-WIDE SOLVENT STORAGE CABINET

## NOTE:

SEE SHEET A2.3 FOR LAB EQUIPMENT SCHEDULES

Call 811 two business days two business days before you dig

**BID SET** 

ACT BSC CMU CP FRP GWB PLY PT# RB SC SRC

RUBBER SEALED CONCRETE SLIP RESISTANT COATING

DISTRICT PHASE WASTEWATER TREATMENT PLANT UPGRADE WATER AND SEWER, **EASTSOUND** 

SON SERVING

JGC DRAWN B

§ **∼** 

Z

WILSONENGINEERING.COM



DATE
1-27-2025
SCALE
AS SHOWN
JOB NUMBER
2023-123

91 OF. 7  $\triangleleft$ 55

	1 - Matthew Strittmatter
4	-
_UNSCREENED.c	42 3 1 AB LIPGRANES NWG = 1/28/2025 9:12 AM
APWA.	30/
-	- 1/2
ΜŘ	٢
2	ES DWG
Ξ.	ř
trait	28
Po	=
s)	Ā
che	٣
드	C 4 -
1.00	A21-A23
×	4
7.00	-123
(17.00	2003-
ш	20
pleed	1 V2020 2023-123 421-42 3 1 4B
₫	2
ANS	2
ANS	ĺ.
503	PHASE 2 - DESIGN/DWG/V3
(-)	1
aţio	C
ent	ΔSF
L D	ď
å	H
D	745
ène	<u>a</u>
۳	ΔL
PDF	Š
P	SW.
toc	7
GS: AutoC	23-123 FSWN WWTP LIPGRANF PL
è.	2 3

				LAB EQUIP	MENT SCHEDU	LE			
KEY	TYPE OF EQUIPMENT/INSTRUMENT	MANUFACTURER	MODEL NUMBER	SOURCE	DEPTH (IN)	WIDTH (IN)	HEIGHT (IN)	ELECTRICAL	MECHANICAL
1	REFRIGERATOR	THERMO SCIENTIFIC	TSV18CPSA	FCIC	32.79	29.53	66.61	115 V, 60 HZ, 1.1 A	VERIFY
2	BOD INCUBATOR	THERMO SCIENTIFIC	PR205745R	FCIC	24.5	24	34.5	115 V, 60 HZ, 9.5 A, NEMA 5-15 PLUG	N/A
3	DRYING OVEN	QUINCY LAB INC	20GC	EXISTING	15.25	15	21.5	115 V, 60 HZ, 6.95 A	N/A
4	DESSICATOR	NALGENE	38090	FCIC	12	12	18	N/A	N/A
(5)	AUTOCLAVE	TUTTNAUER	2340M	FCIC	21.5	20	14.4	120 V, 60HZ, 12 A	VERIFY
6	FECAL COLIFORM INCUBATOR	THERMO SCIENTIFIC	TSCOL19	FCIC	15.5	24.9	9.8	120/230 V, 60 HZ, 9-10.5 A	N/A
7	MICROSCOPE	ACCU-SCOPE	EXC-123-PH	FCIC	10	7.8	14.5	N/A	N/A
8	ANALYTICAL BALANCE	METTLER TOLEDO	XS 104	EXISTING	12.7	10.4	17.8	N/A	N/A
9	SPECTROPHOTOMETER	HACH	DR6000 UV VIS	FOIO	18.1	19.7	8.5	110-240 VAC, 60 HZ	N/A
(12)	STILL	THERMO SCIENTIFIC	MP-1	FCIC	9.75	18	34	120 V, 60 HZ, 9 A	WATER AND DRAIN CONNECTION
(13)	FUME HOOD	LABCONCO	224660	EXISTING	25	47	54	115 VOLTS, 60 HZ, 1 A, DOMESTIC	VERIFY
(15)	GLASSWARE WASHER	LABCONCO	401001000	FCIC	27.7	24.1	32.1-36	115 V, 60 HZ, 16 A, 1P	VERIFY
(16)	STANDING DESK (X2)	UPLIFT	UPL922-MAPLE-48x30	FCIC	30	48	22.6-48.7	100-240 V, 60 HZ, 400W MAX	N/A
(18)	MUFFLE FURNACE	THERMO SCIENTIFIC	FB1315M	FCIC	13	9	14	120 V, 60 HZ, 8.9 A	VERIFY
	MICROSCOPE CAMERA	ACCU-SCOPE	AU-300-HDS	FCIC	-	-	_		
	COLORIMETER	HACH	DR300	EXISTING	HANDHELD			BATTERY POWERED	N/A
	PH PROBE	НАСН	PHC101	EXISTING	HANDHELD			N/A	N/A
	DO PROBE	HACH	LBOD101	EXISTING	HANDHELD			N/A	N/A
	DO/PH METER	HACH	HQ2200	EXISTING	HANDHELD			N/A	N/A

FOIO = FURNISHED BY OWNER & INSTALLED BY OWNER FCIC = FURNISHED BY CONTRACTOR & INSTALLED BY CONTRACTOR



DATE
1-27-2025
SCALE
AS SHOWN
JOB NUMBER
2023-123 91 A2.3 P **BID SET** 99

WIESON ENGINEERING

JGC
DRAWN BY
MCS
CHECKED BY

EASTSOUND SEWER AND WATER DISTRICT

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2

LAB SCHEDULES & TYPES

WILSONENGINEERING, COM

#### **GENERAL ABBREVIATIONS HVAC ABBREVIATIONS** ABOVE FINISHED FLOOR BRAKE HORSEPOWER BOD BOTTOM OF DUCT BUILDING BRITISH THERMAL UNIT CUBIC FEET PER MINUTE BRITISH THERMAL UNITS PER HOUR DMPR DAMPER CAPACITY CONDENSATE EXHAUST AIR FΑ EXHAUST FAN COLUMN CONNECT; CONNECTION EXHAUST GRILLE CONSTRUCTION EXH **EXHAUST** COORDINATE GR GRILLE DEGREE OUTSIDE AIR DIAMETER OUTSIDE AIR TEMPERATURE DIMENSION OAT DISCHARGE SP STATIC PRESSURE DIVISION DOWN DIFFERENTIAL PRESSURE T. TSTAT THERMOSTAT TRANSFER GRILLE DRAWING UMC UNIFORM MECHANICAL CODE **EFFICIENCY** UNIT HEATER ELEVATION; ELEVATOR UV UNIT VENTILATOR FNTFRING VENT VENTILATE: VENTILATION FOUIPMENT VOLUME DAMPER **FAHRENHEIT** FL00R WASHINGTON STATE ENERGY CODE FEET; FOOT; FEET OF WATER(PRESS) GENERAL CONTRACTOR GENERAL HEIGHT; HIGH HORSE POWER

AFF

BLDG

BTUH

CAP

COL

COND

CONN

CONST

COORD

DEG

DIA

DIM

DN DP

EΑ

EFF

ELEV

FNT

FOUIP

FLR

FT

GC

GEN

ΗZ

IRC IFC

IN

KW

MAX

MBH

Ν

OC.

OD

OPP

PD

PSI

QTY

RPM

SCHED

SPEC

TEMP

TYP

VAR

VEL

VOL

PRESS

MECH

HERTZ

KILOWATT

MAXIMUM

NORTH

PHASE

PRESSURE

QUANTITY

SOUTH

SCHEDULE

**SPECIFICATION** 

TEMPERATURE

TYPICAL

VARIABLE

VELOCITY

VOLUME

ON CENTER

PRESSURE DROP

POUNDS PER SQUARE INCH

REVOLUTIONS PER MINUTE

INTERNATIONAL BUILDING CODE

INTERNATIONAL MECHANICAL CODE

THOUSAND BRITISH THERMAL UNITS PER HOUR

MECHANICAL; MECHANICAL CONTRACTOR

OUTSIDE DIAMETER; OVERALL DIMENSION

INTERNATIONAL FIRE CODE


LENGTH; LONG (DIM)

DWG

DISCH

## **HVAC DUCTWORK LEGEND**

SINGLE LINE DUCTWORK INDICATES VIEW DIMENSION LESS THAN 12 INCHES



## **GENERAL CONSTRUCTION NOTES**

1. PLANS ARE DIAGRAMMATIC AND DO NOT SHOW ALL BRANCHES, VALVES, SPECIALTIES AND

Zz

<u>~</u>

Ш

Ш

Z

Ō

Z

DISTRIC

WATER

AND

SEWER

**EASTSOUND** 

||€ ~

PHASE

UPGRADE

PLANT

TREATMENT

WASTEWATER

1-24-2025 SCALE AS SHOWN JOB NUMBER

9

9

OF

57

WILSONENGINEERING

## 2021 WASHINGTON STATE ENERGY CODE NOTES

- PROVIDE POST CONSTRUCTION COMMISSIONING AND COMPLETION REQUIREMENTS IN ACCORDANCE WITH SECTION C408 AND ACCORDING WITH THE CONTRACT DOCUMENTS. SEE SPECIFICATION SECTIONS 23 05 00 AND ALL OTHER APPLICABLE SPECIFICATION
- PROVIDE CLOSE OUT DOCUMENTATION AND TRAINING OF BUILDING OPERATIONS PERSONNEL FOR ALL MECHANICAL COMPONENTS IN ACCORDANCE WITH SECTION C103.6. SEE SPECIFICATIONS FOR MORE INFORMATION.
- EACH SUPPLY AIR OUTLET AND ZONE TERMINAL DEVICE SHALL BE EQUIPPED WITH MEANS FOR AIR BALANCING PER SECTION C408.2.2.1. SEE SPECIFICATIONS FOR DETAILS.
- BALANCE ALL HVAC SYSTEMS IN ACCORDANCE WITH SECTION C408.2.2, GENERALLY ACCEPTED ENGINEERING STANDARDS AND IN ACCORDANCE WITH THE CONTRACT DOCUMENTS. SEE SPECIFICATION SECTION 23 05 93 AND ALL OTHER APPLICABLE SPECIFICATION SECTIONS.
- ALL DUCTWORK SHALL BE CONSTRUCTED AND ERECTED PER THE INTERNATIONAL MECHANICAL CODE 2021 EDITION. SEE SECTION C403.10.2 OF THE 2021 WASHINGTON STATE ENERGY CODE AND SPECIFICATIONS FOR MORE INFORMATION.
- ALL NEW DUCTWORK IS LOW PRESSURE.
- ALL DUCTS AND PLENUMS THAT ARE PART OF AN HVAC SYSTEM SHALL BE THERMALLY INSULATED IN ACCORDANCE WITH TABLE C403.10.1.1 OR C403.10.1.2. SEE SPECIFICATIONS FOR MORE INFORMATION.
- ALL PIPING SERVING AS PART OF A HEATING OR COOLING SYSTEM SHALL BE THERMALLY INSULATED IN ACCORDANCE WITH TABLE C403.10.3. SEE SPECIFICATIONS FOR MORE
- PROVIDE CONTROLS IN ACCORDANCE WITH SECTION C403.4 AND IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.

## **GENERAL LEGEND**



DETAIL/DRAWING REFERENCE

SECTION REFERENCE

CONSTRUCTION NOTE

REVISION SYMBOL

POINT OF CONNECTION

4////

BOLD LINE WEIGHT INDICATES NEW WORK

LIGHT LINE WEIGHT INDICATES EXISTING WORK SLASHED LINE INDICATES EXISTING WORK TO

## DRAWING INDEX

MECHANICAL LEGEND, ABBREVIATIONS AND GENERAL NOTES

DEWATERING BUILDING MECHANICAL PLAN H1.0

MECHANICAL SCHEDULES








## **GENERAL NOTES**

1. EXHAUST FAN EF-1 INTENDED TO OPERATE 24/7. PROVIDE BACK DRAFT DAMPERS ON LOUVERS L-1 AND L-2.

## **CONSTRUCTION NOTES**

- PROVIDE AND LABEL DISCONNECT SWITCH FOR EF-1. LOCATE 42" AFF.
- PROVIDE THERMOSTAT. LOCATE 42"
- 3> PROVIDE INTAKE LOUVER 48" AFF.
- PROVIDE EXHAUST LOUVER 13'-6" AFF
- PROVIDE EXHAUST FAN. LOCATE FAN 14'-7" AFF.
- 6 PROVIDE UNIT HEATER. LOCATE HEATER 7'-6" AFF. HEATER SETPOINT TO BE 45° F FOR FREEZE PROTECTION.
- AIR PRESSURE SENSING SWITCH FOR PROOF OF AIR FLOW. PROVIDE CLEVELAND CONTROLS MODEL AFS-222 OR APPROVED EQUAL.



## DEWATERING BUILDING MECHANICAL PLAN










**BID SET** 

AND WATER DISTRICT PHASE


WILSONENGINEERING

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE -SEWER.


EASTSOUND



## **NORTH ELEVATION**



**SOUTH ELEVATION** 




# **CONSTRUCTION NOTES**

INSTALL EXHAUST LOUVER 13'-6" AFF


2 INSTALL INTAKE LOUVER 48" AFF.

INSTALL UNIT HEATER 7'-6" AFF WITH FACTORY WALL MOUNTING BRACKET.

SUPPORT AND BRACE DUCTWORK AND EXHAUST FAN FROM STRUCTURE ABOVE.



**WEST ELEVATION** 



**EAST ELEVATION** 



**BID SET** 





WASTEWATER TREATMENT PLANT UPGRADE – PHASE 2 EASTSOUND SEWER AND WATER DISTRICT

91

Q.

59

H2.0

WILSONENGINEERING.COM

								Ε	XHAUST	FAN SC	HEDULE								
CALL	_OUT										FAN							BASIS OF DE	ESIGN
						ר ווייר	E.S.P (IN WC)			MOTOR [3]				ELECTRICAL [2	]		MAX SOUND LEVEL		
TYPE	MARK	LOCATION	FAN TYPE	SERVICE	CFM	DRIVE TYPE	[1]	RPM	SPEED	HP	BHP	٧	HZ	ø	МОР	MCA	(DBA)	MANUFACTURER	MODEL
EF	1	DEWATERING	INLINE	DEWATERING	1110	DIRECT	0.50	1612	1612	⅓	1/4	115	60	1	20	9	55	GREENHECK FAN	SQ-100

SCHEDULE NOTES:
[1] STATIC PRESSURE EXTERNAL TO FAN.
[2] SINGLE POINT CONNECTION AND UNIT PROVIDED WITH INTEGRAL DISCONNECT
[3] PROVIDE ECM MOTOR WITH FAN MOUNTED DIAL.

						AIR	TERMINAI	SCHED	ULE							
		AIRFLOW C LIMITS (		NOMIN	AL SIZE		NECK DIMENSION	S		MAX TSP				BASIS OF DE	SIGN	NOTES
							FOR RECT.	ANGULAR		DROP (IN.						NOTES
CALLOUT	AIR TERMINAL DESCRIPTION	MAXIMUM	MINIMUM	LENGTH	WIDTH	DIAMETER	LENGTH	WIDTH	MAX NC	W.G.)	MATERIAL	OPD	FINISH	MANUFACTURER	MODEL	ı
EG-1	SIDEWALL MOUNTED EXHAUST GRILLE	200	0	10"	8"	-	10"	8"	20	0.02	STEEL	NO	#26 WHITE	TITUS	350RL	[1]

SCHEDULE NOTES:
[1] PROVIDE WITH BALANCING DAMPER ON BRANCH CONNECTION.

							UNIT I	HEATER	SCHEDL	JLE					
CAL	LOUT			F.	AN				ELECT	RICAL			BASIS	OF DESIGN	
					MOTOR HP	CAPACITY (KW)						OPERATING WEIGHT			
TYPE	MARK	LOCATION	SERVICE	CFM	(W)	[4]	STAGES	٧	HZ	ø	AMPS	(LBS)	MANUFACTURER	MODEL	NOTES
UH	1	DEWATERING	FREEZE PROTECTION	825	35	12.5	1	480	60	3	15	46.5	KING	KB4812-3MP-B2	[1][2][3]

[1] PROVIDE WITH WALL MOUNTING BRACKET

[2] PROVIDE WITH INTEGRAL DISCONNECT SWITCH
[3] PROVIDE WITH WALL THERMOSTAT AND LOW VOLTAGE CONTROL KIT.
[4] ELECTRIC RESISTANCE HEAT PER 2021 WSEC SECTION C403.1.4, EXCEPTION 15.

					L	.OUVER			
	CALL	OUT			SIZE		BASIS	OF DESIGN	
	TYPE	MARK	SERVICE	WIDTH (IN)	HEIGHT (IN)	MINIMUM FREE AREA (FT <sup>2</sup> )	MANUFACTURER	MODEL	NOTES
	L	1	EXHAUST	30	30	2.6	RUSKIN	ELBD375E	[1]
Ī	L	2	INTAKE	30	30	2.35	RUSKIN	ELBD375I	[1][2]

SCHEDULE NOTES:
[1] PROVIDE WITH INSECT SCREEN.
[2] PROVIDE WITH FILTER RACKS





EASTSOUND SEWER AND WATER DISTRICT SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2 91 0 H3. Q.

09

- -- GENERAL NOTES --DESIGN BASIS: Designed in accordance with the 2021 International Building
- 2. RISK CATEGORY: III (per IBC Table 1604.5)
- 3. DESIGN DEAD / LIVE LOADS
- Floor Live Load: 100 PSF Typica Roof Dead Load: 15 PSF Typical (Incl. Framing)
- Roof Live Load: 20 PSF Typical
- 4. DESIGN SNOW LOADS (ASCE 7-16)
- Ground Snow Load: Pg = 20 PSF Flat Roof Snow Load: Pf = 25 PSF
- Minimum Uniform Roof Snow Load = 25 PSE (unreducible)

- DESIGN WIND LOADS (ASCE 7-16)
   V = 105 MPH / V(asd) = 81 MPH
   Exposure: C / Internal Pressure Coefficient: +/- 0.18
   Components & Cladding: Components and cladding-wind pressures to be used for the design of exterior components and cladding (by others) shall be determined in accordance with ASCE 7 and the IBC.
- 6. DESIGN SEISMIC LOADS (ASCE 7-16)
- Site Class = D
- Seismic Design Category = D / Importance le = 1.25 Ss = 1.13a / S1 = 0.40a
- Sds = 0.79g / Sd1 = 0.51a
- Sds = 0.79g / Sd1 = 0.51g
  Building System: Bearing Wall System
  SFRS: Light frame (cold-formed steel) wall with wood panels
  Response Modification Factor Used: R = 6.5
  Seismic Response Coefficient: Cs = 0.152
  Design Base Shear: V = 3.2 kips ASD
  Abbein Beachters Existed Laborate Faces Procedure

- 7. QUALITY: Contractor shall ensure high standards of workmanship throughout, with strict adherence to the contract documents and all governing codes and
- 8. DESIGN RESPONSIBILITY: Kingworks is responsible only for the design of the primary structural system as shown in the contract documents. Design of all secondary structure or non-structural elements are by others.
- 9. DISCREPANCIES: Notify Wilson Engineering immediately of any discrepancies between these notes, the contract drawings, the specification, or the governing code. Wilson Engineering shall reply in writing. Any related work performed by the Contractor prior to receiving a reply from Wilson Engineering is at the Contractor's Contractor prior to receiving a reply from Wilson Engineering is at the Contractor's sole risk. For purposes of bidding, the most stringent of the conflicting documents of the conflicting do
- 10. VERIFICATIONS: Verify all existing conditions; verify all dimensions in the field; verify architectural, mechanical and electrical openings for size, location and number; notify Wilson Engineering of any discrepancies, substandard existing conditions, or conditions not included in or contrary to the Contract Documents prior to shop drawing submittal or construction.
- 11. DRAWING COORDINATION: Coordinate the structural drawings with drawings from all other disciplines (including but not limited to Architectural, Civil, Mechanical, and Electrical).
- 12. COMPLETED FORM: The structure shown in these drawings is designed to be COMPLETED FORM: The structure shown in these drawings is designed to stable and to resist the loads above only in a fully completed form. Contractor shall ensure that the structure is adequately braced and shored during construction for all temporary loads until all elements are in place, and shall ensure that temporary loadings do not exceed the allowable capacity of any structural elements both before and after these elements are in place.
- 13. MEANS AND METHODS: Contractor is solely responsible for site safety coordination, procedures, construction methodology, shoring, bracing, sequencing, and all other means and methods of construction except where
- 14. PROTECTION AND BRACING: Contractor is solely responsible for the protection of existing buildings, utilities, streets, equipment, etc. during construction. Provide temporary bracing and protection as required.
- 15. SCALING: Do not scale drawings. See architectural and civil drawings for dimensions, and notify Wilson Engineering of any discrepancies
- 16. ALTERATIONS: Any holes or other alterations to the structure which are not specifically detailed on the Contract Drawings shall be submitted to the engineer for approval
- 17. LOAD COORDINATION: The design of all pre-engineered components shall include provisions for precise locations and weights of all mechanical units and other concentrated loads. Concentrated loads are not necessarily indicated on the Structural Drawings, and must be coordinated by the General Contractor, who shall also inform Wilson Engineering of any significant loads not shown in the contract documents. The Contractor shall assume full responsibility for coordination of weights locations. Banger spacings methods of state-thment and coordination of weights, locations, hanger spacings, methods of attachment and seismic bracing of all mechanical units, sprinklers, pipes, ductwork, and other niscellaneous MFP assemblies
- 18. MEP CONNECTIONS TO STRUCTURE: Unless specifically shown otherwise in INIET CONNECTIONS TO STRUCTURE: Unless specifically shown otherwise the Contract Documents, all anchorage, support, and seismic bracing of mechanical and electrical equipment, piping, ceilings, fixtures and other non-structural components shall be designed by a Washington State Licensed Professional Engineer and Installed by the Contractor. The engineer shall be retained by the Contractor, and the Contractor is responsible for all associated engineering, component, and installation costs. Design shall be per ASCE 7 Chapter 13.
- DELIVERY, STORAGE AND HANDLING: All products shall be delivered, stored and handled according to the Manufacturer's recommendations and installation instructions. Protect all items from damage, moisture, corrosion, or other deterioration before, during and after installation
- 20. COPYRIGHT: These drawings, and all designs shown within these drawings, are copyrighted by Kingworks Structural Engineers. Duplication is not permitted without written permission. The designs shown herein are intended for this project only and may not be used on any other project or for any other purpose.

#### -- SUBMITTALS --

- GENERAL: Provide PDF of all submittals to Wilson Engineering. Allow two
  weeks for review, Submittals will be reviewed for general conformance to the
  contract documents. Responsibility for adherence to the contract documents lies
  solely with the Contractor, including but not limited to dimensions, sizes, connections, and quantities.
- CONTRACTOR REVIEW: Contractor shall review, mark, and stamp all submittals before submittal to Wilson Engineering. Unreviewed or unstamped submittals will be returned to the Contractor without review.
- RESUBMITTALS: Resubmittals shall have all revisions clearly identified with drawing clouds" and revision dates. KW shall not be responsible for review of
- SHOP DRAWINGS: To include typical and unique conditions and all connections, shall be submitted to the Structural Engineer of Record for the following products prior to fabrication. Shop drawings shall clearly demonstrate the Contractor's understanding of the contract documents, The following shall be considered minimum structural submittals for this project:

  Concrete Reinforcing Steel (incl. vaul elevations)

  Concrete Mix Designs (confirm fc prior to construction)

- Light Gauge Steel Framing
- DEFERRED SUBMITTALS: Shall be designed by a Washington State Licensed Professional Engineer (Structural Engineer where required by jurisdiction). Submittals shall clearly indicate all loads and reactions to be imposed on the primary structure. Submittals shall include all components and connections required to perform the work. Where the Contract Documents indicate member or required to perform the work. Where the Contract Documents indicate member or connection qualities and/or quantities, these shall be considered a minimum and remain the design responsibility of the component engineer to increase as required to satisfy load and deflection requirements. Deferred submittals shall include calculation set. Both the calculation set and all related shop drawings of the deferred submittal shall be sealed prior to submission. Wilson Engineering shall forward deferred submittals to the Bulking Official where required. The following shall be considered Deferred Submittals on this project: Grund Improvements
- 6. SUBMITTAL REVIEW COMMENTS: Engineer marks and comments on shop drawings and other submittals are a normal and expected part of the submittal process, and are not to be used as a basis for change orders except in cases where these marks result in or derive from substantial changes to the Contract Drawings. Time required to revise and resubmit any submittal shall be considered inherent to the submittal review process and shall not be deemed a change order If discrepancies are discovered between the submittals and the Contract Documents (either before, during, or after submittal review), the Contract shall

#### -- SPECIAL INSPECTIONS, TESTING, AND STRUCTURAL OBSERVATION -

GENERAL: A special inspection agency shall be retained by the owner to perform inspections according to IBC Chapter 17. The following scheduled structural respections according to the chapter 17. The rollowing screedules statutal as special inspection and testing regimen shall be cross-referenced with the IBC and its referenced standards for more specific requirements and exceptions. Special inspection and test reports shall be submitted to the Building Official, Wilson Engineering, and Kingworks in accordance with IBC 1704.2.4

#### -- STRUCTURAL SPECIAL INSPECTION SCHEDULE --REFERENCE (2021 (C=continuous STRUCTURAL ITEM 1705 2 1705 13 1 1 STEEL - Cold-Formed Steel 1705.12.2, 1705.13.3, AWS D1.3 CONCRETE 1705.3, ACI 318-19 26.13 - Reinf Placement P (and prior to all pours) Table 1705.3. ACI 318-19 26 6 2 Anchor Placement P (and prior to all pours) Table 1705.3 - Concrete Placement Table 1705.3 Per ACI 318-19 26.12 Table 1705.3 - Concrete Testing - Formwork & Curing - Erection of Precast Table 1705.3 Members POST-INSTALLED Table 1705.3 ANCHORS See ICC-ES report Epoxy or Adhesive chors Used in Horizontal or Overhead Position - All Other Anchors (except where C reg'd See ICC-ES report Installed in Hardened by ICC-ES report) Concrete WOOD SHEATHED SHEAR WALLS 705.13.3 - Shearwalls (nailing, P (not reg'd when thickness, grade, blocking, fasteners are in single top and bottom fastening, sill bolts, holdowns) row and spaced greate than 4" o/c) SOILS & FOUNDATIONS 1705 6 Table 1705 6 · Subgrade Adequacy P (beneath fill and/or Table 1705.6 - Fxcavation Depth Table 1705 6 - Fill Materials Table 1705 6 - Fill Placement & Table 1705.6 Compaction

- 2. NONSTRUCTURAL COMPONENTS: Nonstructural components are also subject NUNSI HUCI UKALCOMPONENTS: Nonstructural components are also subjeto special inspection for conformance to the Seismic Design Requirements of
  ASCE 7-16 Chapter 13. The support and seismic bracing of nonstructural
  components shall be designed by a Washington State Licensed Engineer, who
  shall be retained by the Contractor. Nonstructural components subject to seismi
  design and periodic special inspection requirements of ASCE 7-16 and IBC
  Chapter 17 include (but are not limited to) the following:

  Architectural components (IBC 1705.13.5)

  Nonstructural components (IBC 1705.14.2)
  - Nonstructural components (IBC 1705.14.2)

  - MEP Components (IBC 1705.13.6)
  - Reference the architectural, electrical, and mechanical drawings and/o specifications for additional special inspection and testing requirements
- 3. STRUCTURAL OBSERVATION: KW will perform Structural Observation if/as required by IBC 1704.6. Structural Observation is for intermittent review of general conformance to the design intent and shall be in addition to (not replacing) the third-party special inspection regimen.

#### -- FOUNDATIONS & SUBGRADE --

- 1. SOIL ALLOWABLE BEARING PRESSURE: 2500 PSF (x 1.33 when subjected to wind
- GEOTECHNICAL REPORT: Reference GeoEngineers geotechnical report dated September 7, 2021 for subgrade preparation, backfill, compaction, wet weather work, and other recommendations. All provisions of the geotechnical report shall be enacted
- 3. GEOTECHNICAL VERIFICATION: The Owner shall retain a geotechnical inspection agency to inspect the excavations and confirm that the provisions of the Geolechnical Report are followed. All recommendations of the geotechnical inspector shall be followed and communicated with the design team via inspection report. Contractor shall coordinate this inspection effort with the Owner.
- 4. UTILITIES: Utilities are not to pass through or beneath footings, stemwalls, and other concrete work on grade except as shown in specific details.
- MISCELLANEOUS VERIFICATIONS: Verify sizes, slopes and locations of tunnels, electrical cells, pits, pipes, floor drains, trenches and floor recesses with architectural, mechanical and electrical contractors.
- 6. ALIGNMENT: All footings shall be centered below columns and walls, unless
- 7. BACKFILL: Do not backfill against below-grade walls until strength has been achieved and floor framing is in place.
- 8. FROST PROTECTION: Maintain minimum 1'-0" soil cover, measured from finished grade to the bottom of the footing, for perimeter wall foundations and isolated exterior foundations.
- EXCAVATION SLOPE: Excavation slope shall not exceed that permitted by local regulation, except as specifically approved by the geotechnical engineer.

#### -- REINFORCED CONCRETE --

- 1. REFERENCED STANDARDS: Reinforced concrete shall conform to the requirements of the following documents, except as modified in these drawings.
- ACI 301-16 "Standards Specifications for Structural Concrete ACI 318-19 "Building Code Requirements for Structural Concrete"
- 2. MATERIALS Conform to following concrete material schedule requirements:

## -- CONCRETE MATERIAL SCHEDULE -

- 1						
		f'c (PSI)	W/CM (MAX)	COARSE AGG (MAX)	AIR CONTENT	MIN FLY ASH AND/OR SLAG
	BLDG FOUNDATIONS / STEMWALLS	4500	0.45	1"	SEE NOTES	20%
	EXTERIOR SOG & EQUIPMENT PADS	5000	0.45	3/4"	6%	30%
	INTERIOR SOG & EQUIPMENT PADS	3500	0.55	3/4"	-	20%
	HYDRAULIC STRUCTURES (SEE ADDT'L REQ BELOW)	4500	0.45	3/4"	SEE NOTES	20%

- Required concrete strength "f'c" shall be evaluated at 28 days (56 days OK for fly
- Required concrete strength "fc" shall be evaluated at 28 days (56 days OK for fly ash or slag concrete). Cementitious Materials: Provide Type II. Blended Hydraulic Cement per ASTM C595 for hydraulic structures. Provide Type 10 rtl Cement per ASTM C150 (Type III OK for Precast) for all else. Cementitious materials for use in concrete exposed to soil or weather must meet or exceed the \$1 exposure class per ACI 318-19 Table 19.3.2.1. Fly Ash: Class F per ASTM C618, Slag: GGBF Slag per ASTM C989, Grade 100 minimum. Ali Entrainment: Provide air entrainment per concrete mix table \*/- 1.5%, all other locations exposed to weather shall have air entrainment of 6% (+/- 1.5%). Typical Reinforcing Steef. ASTM A615, Grade 75 for Train #1 and #2 (H) bars, Grade 60 for all else.

- Mixes for hydraulic structures shall also satisfy the following: Shrinkage reducing admixture per ASTM C494 shall be added so that test mixes shall demonstrate shrinkage of no more than 400 microstrain at 7 days.
- Air percentage shall be per the manufacturer of the shrinkage reducing
- Hydraulic structure concrete shall contain a minimum of 500 pounds of cementitious materials per cubic yard.

  For hydraulic structures, the requirement for stone aggregate shall not be
- 3. SPLICES: All reinforcing steel lap splices are to be per typical schedule unless noted
- CONTINUITY: Horizontal reinforcing steel in walls and wall footings shall be continuous
  around corners, same size and spacing. At intersections of walls or footings, extend all
  bars as far as possible into continuous element and terminate with standard hook.
- 5. CLEAR COVER: Provide clear cover from outermost reinforcing to surface of concrete in accordance with the following unless noted otherwise:
- Elements cast against and permanently exposed to earth: 3" cl Elements formed and exposed to earth or weather: 2" clr (#6-#18), 1 1/2" clr (#3-#5)
- 6. ACCESSORIES: Provide all accessories, chairs, spacer bars and supports necessary to secure steel In accordance with ACI Code of Standard Practice.
- 7. CHAMFER: Chamfer all exposed corners and edges above grade per Wilson
- 8. FORM STRIPPING: Do not strip forms until concrete has reached adequate strength.
- 9. SLEEVES / OPENINGS: Furnish and place all sleeves and openings as shown on the
- 10. REINFORCING FABRICATION: All reinforcing shall be shop fabricated. Exception: #3 or #4 bars may be field bent one time in any location, do not rebend or restraighten 11. HOOKS: All hooked bars shall be a standard shop fabricated hook with bend radii and
- length per ACI 318, unless noted otherwise. 12. TESTING: Test cylinders shall be taken by qualified personnel according to ACI 318-19
- 13. WEATHER PROVISIONS: Observe all ACI recommendations for hot or cold weather concreting cure slabs using an approved curing compound or wet cure system per ACI recommendations, with special consideration for slag and fly ash concrete as appropriate.
- 14. CONSTRUCTION JOINTS: All construction joint locations shall be submitted to the Architect for approval. Roughen joints to 1/4-inch minimum amplitude, remove all laitance. Soak joint continuously for 2 hours minimum, then remove all standing water, immediately prior to second pour. Unless noted otherwise, all reinforcing shall be spliced/continuous across the construction joints.

#### -- ANCHORAGE TO CONCRETE --

- MATERIALS (unless noted otherwise in the drawings)
   Concrete must cure for a minimum of 21 days prior to drilling any holes or placing
  - Anchor type shall be according to the drawings. All post-installed anchors
  - installed in concrete shall have ICC-ES reports demonstrating IBC compliance for use in cracked concrete and for seismic loading. Substitutions not permitted without written permission by KW.
    - Pre-approved Epoxy for post-installed threaded rod or reinforcing in concrete base material: HILTI HIT-RE 500 V3 or Simpson SET-3G.
  - Pre-approved "Screw Anchors" in concrete base material: HILTI KH-EZ or Simpson Titen HD or DEWALT/Powers Screw-Bolt+
  - installed or Cast-in-Place Threaded Rod (Anchor): ASTM A36 Post-installed Reinforcing: ASTM A615 Grade 60
- 2. EMBEDMENT: Anchor embedment in base material shall be per the drawings, which shall govern over the typical values shown below. Where not otherwise indicated, provide embedment as follows:

   Epoxy to Concrete: Min Embed = 12 x (Rod/Bar Ø) for 5/8\*Ø (#5) or smaller, 14 x (Rod/Bar Ø) for 3/4\*Ø (#6) or larger

   S crew Anchor to Concrete: Min Embed = 9 x (Anchor Ø)

   Cast-In-Place Anchor: Min Embed = 7\* to top of embedded washer or hook

- 3. INSTALLATION: Post-installed anchor hole diameter, drilling depth, cleaning and installation procedure shall be in accordance with the current Manufacturer's Printed Installation Instructions (MPI) provided in the ICC/ES report. Holes shall be drilled with rotohammer equipment and dry. Core-drilled holes are no permitted unless specifically
- 4 COLD-WEATHER INSTALLATION: Do not use enoxy or adhesive anchors outside of their rated temperature range. Contact the Structural Engineer for alternate if the base material temperature may be less than 40 degrees during installation or curing.
- CAST-IN-PLACE ANCHORS: Cast-in-place anchors shall have nut and washer at embedded end, UON. Anchors shall be affixed to the form to prevent movement du pouring, vibration, or se-lup and shall not b "stabbed" into wet concrete or grout. Verify adequate length of exposed thread to fully engage all attached work.
- FINISHES: All anchors used at exterior or where subject to moisture shall be hot-dip galvanized per ASTM A153 or stainless steel, including matching washers and nuts.
- 7. REINFORCEMENT LOCATIONS: All post-installed anchors shall be located to avoid drilling into reinforcement, unless specifically approved by the Engineer. Reinforcement shall be placed with consideration for locations of post-installed anchors. Do not damage reinforcing during drilling operations.

#### -- COLD-FORMED STEEL FRAMING --

- REFERENCED STANDARD: All work shall conform to AISI S100-16.
- 2. MATERIALS: All cold-formed steel members and accessories shall be galvanized (G90), and shall be from same manufacturer as required by compatibility
- 3. YIELD STRENGTH: Minimum yield strength shall be as follows:
- 16 gauge (54 mil) and heavier: fy=50 ks
  18 gauge (43 mil) and lighter: fy=33 ksi
- STUD INSTALLATION: Plumb, align and securely attach studs to the flange or web of both upper and lower tracks. Bear studs firmly against inside track web before stud and track attachment. Provide top and bottom tracks of the same gauge or heavier than
- 5. CONNECTORS: Connector types shall be as indicated in the drawings; submit alternates of equal strength for review. Cold-formed steel connectors shall be installed in accordance with manufacturer's guidelines.
- 6. JOINING: Multiple studs shall be joined by welds 3/4" long each edge @ 12" O.C., or by (2) rows #8 @ 12" O.C. each edge of web when joined back to back. Space rows of screws as far apart as possible.
- SPLICES: Splices in studs are not permitted. At track splices, butt-weld full section or splice with overlapping section at least 12" long with (6) #8 screws to each lapped flange section. 8. MINIMUM CONNECTION: Minimum connection of piece-to-piece in all cold-formed steel, where no other connection is shown, is (2) #8 screws or (2) 1" x 1/8" fillet welds
- place connections symmetrically. 9. STUD BRACING: Each face of studs shall be braced against rotation and weak axis
- buckling by one of the following methods:

  OPTION A (BRIDGING): Approved manufactured bracing system utilizing stud punching and special hardware. Submit desired system for Kingworks approval.
- Vertical spacing between bridging rows shall be 4<sup>1</sup>-0" o/c maximum.

  OPTION B (SHEATHING): Minimum 5/8" GWB permanent sheathing with #8 screws at not more than 12" o/c, plus bridging per Option A on any face not sheathed. This option may not be used unless sheathing is applied to both faces during initial construction and may not be used if the sheathing is subject to change or removal due to tenant improvement or other owner uses.
- WELDING: Cold-formed steel welding requirements are as follows:
   Conform to the requirements of AWS D1.3-2018, "Structural Welding Code

- Sheet Steer. All welds shall be flux-cored arc welding process, unless otherwise approved. Use only pre-qualified weld procedures. Welding shall be carefully controlled to eliminate burn-through. Burn-through will be cause for rejection of weld. Repair or replace all burn-through damaged pieces. Bring pieces into firm contact before welding.
- 11. SCREWS: All screws shall be self-tapping and self-drilling in compliance with ASTM C1513, SAEJ78, and ICC-ES AC118,
- Screws shall have a Type II coating in accordance with ASTM B633 and have
- Screws shall have a 1 ype II coating in accordance with AS IM Bods and nave tested resistance to hydrogen embrittlement. Steel-to-steel screws shall have a minimum projection of 3 threads through the last joined by of material. No gap shall be permitted between joined piles. Screws shall have a minimum center to center spacing and edge distance of three times the screw diameter unless noted otherwise on the drawings. Tighten screws per manufacture recommendations. Stripped screws or holes are to be considered ineffective and shall be replaced with screws of the next larger diameter.

## -- STRUCTURAL STEEL --

- REFERENCED STANDARDS: Fabrication, erection and dimensional tolerances of structural steel members shall be in accordance with AISC 303-16 "Code of Standard Practice for Steel Buildings and Bridges" and ASTM A6.
- Wide Flange and WT shapes: ASTM A992, fy=50 ksi. Hollow Structural Sections (HSS): A500 Grade C, Rectangular fy= 50 ksi. Round fv=46 ksi.
- Welding Electrodes: E70XX Anchor Rods: ASTM F1554 Grade 36
- Angles / Channels / Plates / Rods / Miscellaneous: ASTM A36 3. WELDING: All welding to be performed by qualified welders and shall onform to A.W.S. D1.1.
- GALVANIZING: All steel elements and fasteners exposed to the exterior shall be hot-dip galvanized in accordance with ASTM A153/A123, unless a suitable exterior grade paint system is indicated
- GALVANIZING REPAIR: Repair all damage to hot-dip galvanized coating by hot-stick or high-zinc paint method in accordance with ASTM A780. Where welding of galvanized steel is required, all galvanizing on the area of steel to be welded, plus 3/4-inch each side of the welded area, shall be ground off prior to welding; affected area shall be repaired per ASTM A780.
- 6. ERECTION: Contractor shall comply with all current OSHA/WISHA requirements concerning steel erection. This may require additional bolts, shims, guys, bracing, and other elements that are not detailed in the Contract Documents but remain the Contractor's responsibility to
- BOLT SPECIFICATION: All bolted connections shall conform to the current "RCSC Specification for Structural Joints Using High-Strength Bolts".
- BOLT INSTALLATION: Bolts shall be snug-tightened (-ST). "-ST" bolts shall be tightened as needed to bring all plies of the connection into firm contact, achieved by a few impacts of an impact wrench or the full effort of an iron worker using an ordinary spud wrench
- 9. BOLT HOLES: Bolt holes in steel shall be 1/16" larger than bolt liameter, except where specifically detailed otherwi
- GROUT: Grout for baseplates, sleeves, and embedded steel shall be GROUT: Grout for baseplates, steeves, and embedded steel shall be an approved nonshrink cementitious grout containing natural aggregates delivered to the job site in factory prepackaged containers requiring only the addition of water. The minimum 28-day compressive strength shall be at least 1000 psi higher than the supporting concrete strength, UON. Grout shall be mixed, applied, and cured strictly in accordance with the manufacturer's printed instructions. For grouting under base plates, grout shall be proportioned as a flowable mix. When a flowable mix does not provide the required strength, an epoxy grout shall be used. Grout thickness shall be per the typical details.

#### -- WOOD FRAMING --

- REFERENCED STANDARD: All work shall conform to 2021 IBC
- EXTERIOR WOOD PROTECTION: Provide flashings, sealants, and inishes per Wilson Engineering in order to protect all exterior wood surfaces from moisture.
- 3. SHEATHING: Place roof sheathing with face grain oriented in the SHEATHING: Place roof sheathing with face grain oriented in the direction of span. Offset adjacent rows of sheathing panels by 24" minimum, with all panel ends bearing on joists, beams, or walls. Install wall sheathing in either the horizontal or up-right orientation. Adjust all sheathing layouts so that no panel is less than 24" in length or width. Where edges are not required to be blocked per schedule, provide Simpson PSCA clips at spacing per catalog recommendation. All sheathing shall be APA rated, with type/blocking/fastening per the following schedule. Provide 1/8" gaps between abuttion sheet eddes, vioical. veen abutting sheet edges, typical
- SHEATHING FASTENING: Minimum fastening per the following schedule shall apply at all locations, except where larger screws and/or smaller spacing are required by plans or details. Shearwall astening is shown by schedule on the plans. Where "boundary fastening" (BF) and/or "edge fastening" (EF) are referenced in these drawings, panel edge values per the schedule shall apply. Blocking for edges shall be per the typ wall detail.

## -- WOOD SHEATHING SCHEDULE --

USE	TYPE	BLOCK EDGES	MIN EDGE NAILING	MIN FIELD NAILING
Shearwalls	7/16" OSB	Yes	Per SW Sched (EF)	#8 @ 12"
Other Sheathed Walls	7/16" OSB	No	#8 @ 6"	#8 @ 12"
Roof	7/16" PLY	No	#8 @ 6" (BF)	#8 @ 12"



**BID SET** 

 $\alpha$ Ш WILSONENGINEERING. ш Z G Z ш

Zż

KINGWORKS STRUCTURAL **ENGINEERS** 

Verify Scale:

 $\simeq$ Ś F  $\overline{\Box}$ 

UPGRADE ᆸ

 $\overline{\circ}$  $\frac{1}{2}$  $\supset$ ō Ñ

 $\simeq$ 

××

61


S

EĄ

6 OF

S





3 CONVEYOR SUPPORT NOT TO SCALE

		CF:	S SHEAR WALL S	CHEDULE		
WALL		SHEATHING	SCREW SIZE	SCREW SPACING,	SCREW SPACING.	
TYPE	SHEATHING TYPE (MIN)	APPLIED TO	(MIN)	PANEL EDGES	FIELD	SILL BOLTING
SW-3	7/16" OSB	1 - SIDE	#8	3" OC	12" OC	1/2" BOLT @ 24" OC
SW-6	7/16" OSB	1 - SIDE	#8	6" OC	12" OC	1/2" BOLT @ 48" OC

[1] STRUCTURAL SHEATHING SHALL CONSIST OF APA RATED 7/16" (MIN) SHEATHING [2] STEEL SHEETS MAY BE INSTALLED EITHER PARALLEL OR PERPENDICULAR TO FRAMING, PROVIDE 1/8" GAP BETWEEN ALL ABUTTING HORIZONTAL SHEET EDGES. LAYOUT SHEETS TO ENSURE 32" MIN SHEET DIMENSION

[2] STEEL SHLLT IS MAN DE MISTALLED TENT AND ASSETT TO ENSURE 32" MIN SHEET DIMENSIS AT ANY LOCATION.

(3) SHEATHING SHALL EXTEND FULL HEIGHT OF SHEARWALL AND TO THE FURTHEST EXTENTS OF EACH SHEARWALL ENDPOST, UNLESS SPECIFICALLY NOTED OTHERWISE.

(4) ALL SHEATHING EDGES SHALL BE ATTACHED TO FRAMING MEMBERS OR BLOCKING. BLOCKING SHALL CONSIST OF STUD SECTIONS SAME AS WALL STUDS OR 43-MIL x 1-1/2" CONTINUOUS FLAT STRAPPING.

(5) SEE TYPICAL DETAILS FOR TRACK FASTENING AT SHEARWALLS.

(6) SCREWS SHALL BE INSTALLED NO CLOSER THAN 3/8" TO EDGE OF SHEET OR BASE MATERIAL.


(7) SW "EDGE FASTENING" (EF) INDICATED ON DETAILS ELSEWHERE SHALL BE EQUAL TO PANEL EDGE FASTENING SHOWN ABOVE.


(8) SCREWS IN THE FIELD ARE INSTALLED 12" OC UNO

(9) WALL STUDS AND TRACK SHALL BE ASTM A1003 STRUCTURAL GRADE 50 TYPE H FOR 54 MILS AND GREATER OR ASTM A1003 STRUCTURAL GRADE 33 TYPE H FOR MIL THICKENS OF 33 OR 43.


[10] FASTENIES TO HAVE MINIMUM HEAD DIAMETER OF 0.285IN AND MEET ASTMC1513.

**FOOTING SCHEDULE** REINFORCING DESCRIPTION MARK SIZE DEPTH DETAIL REE (2) #4 CONT. LONGITUDINAL CONT. STEMWALL FOOTING 1/S2.2 1'-6"





2 DEWATERING BUILDING - ROOF FRAMING PLAN



**BID SET** 

62

91 OF.

**S**2.

**Z** <sup>0</sup> **z** 

Z

KINGWORKS STRUCTURAL ENGINEERS


Verify Scale:

DISTRIC

PHASE

WILSONENGINEERING.






NOT TO SCALE


- WALL REINF CONFIGURATION NOTES

  1. SEE STRUCTURAL NOTES FOR REQUIRED CLEARANCES.
  2. WALL REINFORCING SHALL BE PER PLANS
  3. IN TWO LAYER WALLS LOCATE WALL (V) BARS OUTBOARD
- OF WALL (H) BARS (UON).
  4. IN SINGLE LAYER WALLS LOCATE WALL (V) BARS AT THE WALL CENTERLINE (UON). 5. ALL WALL (V) REINFORCING SHALL BE CONTINUOUS FULL HEIGHT (UON) AND DOWELED TO FOUNDATION PER TYP
- DETAILS. 6. WALL (H) BARS SHALL USE THE TOP BAR LAP LENGTHS.



WALL CORNER - SINGLE LAYER REINF WALL INTERSECTION - SINGLE LAYER REINF

6 TYP CONCRETE WALL REINFORCING AT CORNERS & INTERSECTIONS NOT TO SCALE



BOTTOM OF DRAIN MUST BE BELOW BOT OF BASE

- NOTE


  1. DRAIN PIPES MUST DISCHARGE BY GRAVITY OR MECHANICAL MEANS TO AN APPROVED DRAINAGE SYSTEM THAT COMPLIES w/ THE INTERNATIONAL PLUMBING CODE

- W/ THE INTERNATIONAL PLUMBING CODE.
  2. MINIMUM SLOPE FOR DRAIN PIPE RIUNS IS 0.25%
  3. DO NOT CONNECT FOUNDATION DRAIN SYSTEMS TO RAIN LEADERS OR DOWN SPOUTS.
  4. PROVIDE APPROVED CLEANOUTS FOR ALL DRAIN PIPE AT ENDS, CORNERS, AND NO MORE THAN 120'-0" ON CENTER.
  5. SEE CIVIL DRAWINGS FOR GRADES, DISCHARGE POINTS, AND OTHER REQMTS. ALSO SEE GEOTECH REPORT FOR ADDITIONAL REQMTS.
- REUMIS.

  S UBMIT A FOUNDATION DRAINAGE PLAN TO THE ARCHITECT FOR REVIEW.

  DRAIN ROCK/BASE MATERIAL SHALL CONSIST OF GRAVEL OR STONE WITH LESS THAN 10% OF MATERIAL PASSING THROUGH A NUMBER 4 SIEVE.
- 3 TYP FOUNDATION DRAINS NOT TO SCALE


NOTE: DETAIL APPLIES TO ROUGH OPENINGS 2'-0" WIDE OR LESS



(5) TYP SMALL OPENING HEADER

NOT TO SCALE

- PROVIDE SLEEVES WILD Z-LARGER I HAN PIPE OD. CENTER PIPE AND WRAP W. COMPRESSIBLE MAILERIAL.
   ADJACENT PENETRATIONS THROUGH STEMWALL SHALL BE SPACED TO PERMIT 6" MIN REMAINING
  CONCRETE BETWEEN THEM. IF CLOSER PENETRATION SPACING IS REQUIRED, OR IF ANY TYP REINF
  REQUIRES INTERRUPTION, SUCH LOCATIONS SHALL BE CLEARLY INDICATED ON THE SUBMITTED
  REINFORCING SHOP DRAWINGS; THE ENGINEER SHALL REVIEW THE SHOP DRAWING FOR ADEQUACY AND
  ADD REINFORCING AS REQUIRED. FOR BIDDING PURPOSES ONLY, INCLUDE (2) ADD'L #4 x 6"0" ON EACH SIDE
  OF EACH MULTIPLE-PIPE PENETRATION.
   FIGURE BELOW SHOWS ACCEPTABLE PENETRATION LOCATIONS THROUGH STEM OR BELOW FTG:




(2) TYP FOOTING PENETRATIONS

NOT TO SCALE

NOTE


1. PROVIDE SLEEVES w/ ID 2" LARGER THAN PIPE OD, CENTER PIPE AND WRAP w/ COMPRESSIBLE MATERIAL.



INTERIOR

EXTERIOR INTERIOR 800T200-43 w/ #10 EA SIDE EA STUD, SPLICE PER PANEL FASTENING PER SHEAR WALL SCHEDULE. #8 @ 6" OC EDGE FASTENING & 12" OC FIFLD FLSEWHERE TO JAMB THICKNESS AT SHEAR WALLS, BLOCK PANEL EDGES w/ 1.5"x43-MIL STRAP TYP EXTERIOR STUD WALL 800S162-43 @ 16" OC 7/16" OSB SHEATHING TYP SILL BOLT & BPS1/2-6 WASHER, BOLT DIA. & SPACING PER SHEARWALL SCHEDULE, 1/2" DIA. @ 48" OC ELSEWHERE, SILL BOLT OPTIONS: OPTION.1: HDG CAST-IN-PLACE ANCHOR RODS WITH 2" HOOK OR HEADED BOLT, 7" MIN EMBEDMENT #10 EA SIDE EA STUD OPTION 2: MECHANICALLY GALVANIZED SIMPSON TITEN HD ANCHORS, 3-1/2" MIN EMBEDMENT STEMWALL PER OPTION 3: HDG EPOXY ANCHOR RODS PER STRUCT. NOTES, 5" MIN EMBEDMENT TYP DETAIL

7 TYP EXTERIOR CFS WALL NOT TO SCALE



(4) TYP DOOR HEADER NOT TO SCALE

EXTERIOR

(GL

9 2 OF. **S**2. **BID SET** 63

Ζž

 $\alpha$ 

Ш

ш

Z

Ü

KINGWORKS

**ENGINEERS** 

Verify Scale:

DISTRI

WATER

AND

SEWER

OUND

Ñ

S

PHASE


UPGRADE

PLANT

WASTEWATER

STRUCTURAL

WILSONENGINEERING.




CONSTRUCTION JOINT

NOTES

1. FOR CONC STRENGTHS NOT INDICATED,
USE NEXT LOWEST TABULATED 16 VALUE.
2. PROVIDE 2 12° SIDE COVER AND 2° END
COVER FOR HOOKS.
3. TABULATED VALUES ARE APPLICABLE
FOR GRADE 60 UNCOATED REINF BARS.

	STANDARD HOOK EMBEDMENT (Ldh)
	CONC DESIGN STRENGTH (fc)
BAR SIZE	4,500 PSI
#3	6"
#4	7"
#5	9"
#6	10"
#7	12"
#8	14"





PARTIAL PLAN

3 TYP TRAIN HORIZONTAL BAR LAPS NOT TO SCALE

### 4,500 PSI CONCRETE

(2) TYP CONCRETE REINFORCING DEVELOPMENT / SPLICE LENGTHS NOT TO SCALE

OPNG

	DEVELOPMENT LENGTHS (Ld)		LEN	SPLICE GTHS _s)
BAR SIZE	TOP	OTHER	TOP	OTHER
#3	16 in	12 in	18 in	16 in
#4	20 in	15 in	24 in	20 in
#5	28 in	22 in	36 in	28 in
#6	20 in	30 in	50 in	20 in

(5) TYP LARGE PENETRATIONS IN CONCRETE

NOT TO SCALE

(2) #5x4'-0" AT EA CORNER, (1) EA FACE, LOCATE TO INT OF TRIM BARS, TYP

-PIER I ENGTH

NOTES
1. DETAIL APPLIES TO ALL OPENINGS WITH EITHER HEIGHT OR WIDTH GREATER THAN 2-0".
2. Ld IS DEVELOPMENT LENGTH PER TYPICAL DETAIL.
3. REINFORCING SHOWN ABOVE IS TYP MINIMUM. OMIT ADDED REINFORCEMENT ABOVE WHEN SPECIAL REINFORCING INDICATED ON PLANS OR DETAILS EXCEEDS THIS REINFORCING.
4. CONTRACTOR SHALL VERIEY ALL OPENINGS NOT SHOWN IN THE STRUCTURAL DRAWINGS WITH THE STRUCTURAL DRAWINGS

TRIM BARS A.A. EA OPNG, TYP EA FACE OF WALL

OPNG.

HOOK BARS PER TYP DTL WHERE Ld EXTENSION NOT FEASIBLE, TYP

WHERE PIER LENGTH IS 2'-0"
OR LESS, PROVIDE EXTRA
TRIM BARS AS SHOWN AND #4
CLOSED TIES AT 6" OC

(2-#5 UON)

- NOTES

  1. TABULATED VALUES ARE APPLICABLE FOR GRADE 60 UNCOATED REINF BARS.

  2. BAR C/C SPACING MUST BE GREATER THAN TWICE THE BAR DIAMETER AND COVER GREATER THAN ONE BAR DIAMETER.


  3. "TOP" BARS ARE DEFINED AS HORIZONTAL BARS WITH MORE THAN 12 INCHES OF FRESH CONCRETE CAST BELOW THE BARS, INCLUDING WALL HORIZONTALS.

  4. AT LOCATIONS WHERE Ld IS CALLED OUT BUT CANNOT BE ACHIEVED, EXTEND BAR
- BUT CANNOT BE ACHIEVED, EXTEND BAR AS FAR AS POSSIBLE AND PROVIDE STANDARD HOOK PER TYP DETAIL.

#4 NOSING BAR, 1-1/2" CLR A.A., TYP (E) SLAB FOR UTILITIES CABINET NOTES:

1) SEE CIVIL DRAWING FOR WHERE DETAIL APPLIES
2) LENGTH OF STAIR TO MATCH LENGTH OF (E) 12" RUN TYP SLAB, APPROX, 80" SLAB-ON-GRADE PER C**İ**VİL #3 DOWEL W/ STD HOOK, (1) AT 4" FROM EA END OF STAIR AND AT 18" OC BTWN, DRILL & EPOXY PER STRUCT. (3) #4 AT BOTTOM INSPECTION NOT REQUIRED BASE COURSE PER CIVIL 6" MIN UNDER STAIR CUT AS STEEP AS POSSIBLE AND FARTH FORM SUBGRADE PREP PER STRUCT, NOTES


7 STAIR-ON-GRADE AT CABINET NOT TO SCALE



NOTES
1. DETAIL APPLIES TO D= 9° OR LESS.
2. IF MINIMUM CLR SPACING CANNOT BE ACHIEVED, REINFORCE AROUND COMBINED EXTENTS PER TYP LARGE OPENING DETAIL.

(4) TYP SMALL PENETRATIONS IN CONCRETE NOT TO SCALE

# <u>NOTE</u>: SEE PLANS AND STRUCTURAL NOTES FOR REQUIRED CLEARANCES OF REINF IN WALL.



**BID SET** 

1) TYP TRAIN CONCRETE WALL REINFORCING TO MAT SLAB NOT TO SCALE

2

 $\sim$ S 91

P

9

Zÿ

~

Ш

ш

Z

Ü

KINGWORKS

STRUCTURAL ENGINEERS

Verify Scale:

DISTRICT

WATER

AND

SEWER

**EASTSOUND** 

PHASE

UPGRADE


PLANT

TREATMENT

WASTEWATER


DET

WILSONENGINEERING.COM



REVISIONS	BY	DATE





**ELECTRICAL DEMOLITION SITE PLAN** 

HORIZONTAL SCALE

## **DEMOLITION GENERAL NOTES:**

- 1. PROVIDE SELECTIVE ELECTRICAL DEMOLITION OF EXISTING ELECTRICAL EQUIPMENT WHERE SHOWN ON CIVIL PLANS.
- 2. ALL DEMOLITION WORK REQUIRED UNDER THIS CONTRACT IS NOT SHOWN ON THE DRAWINGS
- THE CONTRACTOR SHALL INSPECT THE EXISTING SITE AND INSTALLATIONS PRIOR TO BIDDING AND SHALL DETERMINE THE WORK REQUIRED TO PROVIDE COMPLETE DEMOLITION AS SHOWN OR WITHIN THE INTENT OF THE CONTRACT DOCUMENTS.
- EXISTING EQUIPMENT, SYSTEMS, AND MATERIALS REMOVED DURING DEMOLITION SHALL BE MADE AVAILABLE FOR INSPECTION AND DECISION AS TO WHETHER THE OWNER WILL RETAIN POSSESSION. ITEMS SELECTED FOR RETENTION SHALL BE TURNED OVER TO THE OWNER. THESE ITEMS SHALL BE DELIVERED TO A LOCATION ON THE PREMISES SELECTED BY THE OWNER.
- 5. ALL MATERIAL NOT SELECTED FOR RETENTION BY THE OWNER AND DEBRIS SHALL BE LEGALLY DISPOSED OF BY THE CONTRACTOR.
- 6. SEE CIVIL DRAWING C0.6 FOR ADDITIONAL DEMOLITION REQUIREMENTS.

## **DEMOLITION KEY NOTES:**

- PROTECT EXISTING ELECTRICAL EQUIPMENT IN EXISTING DEWATERING BUILDING. PROVIDE DEMOLITION AND COMPLETE REPLACEMENT OF DEWATERING BUILDING PER CIVIL DRAWINGS AND SPECIFICATIONS.
- PROVIDE SELECTIVE DEMOLITION OF ELECTRICAL EQUIPMENT FOR TREATMENT TRAINS NO.1 AND NO.2. REMOVE ALL LED LIGHTING FIXTURES FOR RE-USE IN NEW DEWATERING BUILDING OR RETURN TO OWNER.
- \$\langle 3 \rangle\$ REMOVE EXISTING BLOWER ELECTRICAL EQUIPMENT INCLUDING BLOWER MOTORS, ELECTRICAL CONDUIT AND CONNECTIONS AND CONTROLS.
- REMOVE EXISTING 208Y/120V ELECTRICAL PANELS AFTER NEW CONSTRUCTION AND INSTALLATION OF NEW PANELS. PROVIDE TEMPORARY POWER PROVISIONS TO MAINTAIN POWER TO REQUIRED EQUIPMENT AND LIGHTING DURING CONSTRUCTION.
- DS PROVIDE SELECTIVE ELECTRICAL DEMOLITION OF POWER CIRCUITS IN EXISTING LABORATORY DURING REMOVAL OF EXISTING CABINETRY AND LAB EQUIPMENT. D6 REMOVE EXISTING EXTERIOR WALL PACK LIGHTING FIXTURES, PROTECT FOR RE-INSTALLATION ON NEW DEWATERING BUILDING.



**BID SET** 

BZ DISTRICT NAS V PHASE WASTEWATER TREATMENT PLANT UPGRADE WATER SITE AND ELECTRICAL DEMOLITION SEWER .

**EASTSOUND** 

01-24-2025 SCALE

EO.


AS SHOWN JOB NUMBER 2023-123

9

AREA CLASSIFICATION SITE PLAN

HORIZONTAL SCALE

## AREA CLASSIFICATION LEGEND:





BZ

VASi

PHASE

SITE PLAN

CLASSIFICATION

AREA

91

89

DISTRICT

WATER

AND

SEWER A

## **GENERAL NOTES:**

- AREA CLASSIFICATIONS BASED ON NFPA 820, STANDARD FOR FIRE PROTECTION IN WASTEWATER TREATMENT AND COLLECTION FACILITIES, 2024 EDITION.
- 2. ELECTRICAL INSTALLATION IN CLASSIFIED AREAS SHALL COMPLY WITH THE REQUIREMENTS OF NFPA 70, NATIONAL ELECTRICAL CODE, AND OTHER STATE AND AGENCY REQUIREMENTS AS REQUIRED BY THE AUTHORITY HAVING JURISDICTION.

## **CLASSIFIED AREA NOTES:**

- (1) INFLUENT PUMP STATION: PRIMARILY RESIDENTIAL SEWER CLASS I, DIV 2 PER NFPA 820-2024 TABLE 4.2.2, ROW 10a. EXTENT OF CLASSIFIED LOCATION: WITHIN ENCLOSED SPACE.
- ©2> BELOW GRADE METERING VAULT WITH CLOSED PIPING SYSTEM: CLASS I, DIV 2 PER NFPA 820-2024 TABLE 4.2.2 ROW 34a. EXTENT OF CLASSIFIED LOCATION: WITHIN ENCLOSED SPACE PLUS 3' AROUND VENTS.

- C6 EFFLUENT FLOW METER VAULT: UNCLASSIFIED PER NFPA 820-2024 TABLE 5.2.2.27.
- DEWATERING BUILDING WITH DEWATERING PRESS: UNCLASSIFIED PER NFPA 820-2024 TABLE 6.2.2, ROW 12a WITH TYPE 'C' VENTILATION, CONTINUOUSLY VENTILATED AT 6 AIR CHANGES PER HOUR AND IN ACCORDANCE WITH NFPA 820-2024 CHAPTER 9.
- (29) LEVEL LODOR SYSTEM: CLASS I, DIV 2 PER NFPA 820-2024. EXTENT OF CLASSIFIED LOCATION: WITHIN ENCLOSED BIN SPACE, 18" ABOVE AND 10' HORIZONTALLY AROUND TOP OF STORAGE BIN.
- OFFICE BUILDING AND BLOWER BUILDING: UNCLASSIFIED.
- DEWATERING SUMP PUMP: UNCLASSIFIED PER NFPA 820-2024 TABLE 5.2.2.21



**BID SET** 

COUNTY
WASTEWATER TREATMENT PLANT UPGRADE **EASTSOUND** 01-24-2025 SCALE AS SHOWN JOB NUMBER 2023-123 EO.



C4 UV DISINFECTION UNITS: UNCLASSIFIED PER NFPA 820-2024 TABLE 5.2.2.26.

C5 2W PUMP STATION: UNCLASSIFIED PER NFPA 820-2024 TABLE 5.2.2.21.



3 AREA 300 - BIOTREATMENT SYSTEMS:

AREA 400 - EFFLUENT/UV SYSTEM:

NO ELECTRICAL WORK ANTICIPATED.

6 AREA 600 - PLANT DRAIN SYSTEM:
NO ELECTRICAL WORK ANTICIPATED.

7 AREA 700 - BLOWER BUILDING:

NEW SLUDGE CONVEYOR, LEVEL LODER AND HOIST SYSTEM. NEW DEWATERING SUMP PUMP WITH CONTROL PANEL.

- ALL CONDUIT ROUTING IS NOT SHOWN, AND WHERE SHOWN, IS SCHEMATIC. ELECTRICAL CONTRACTOR SHALL DETERMINE THE BEST ROUTING PATH AND CIRCUIT COMBINATIONS BASED ON FIELD CONDITIONS AND ELECTRICAL CODES.
- 2. EQUIPMENT LOCATIONS AND ARRANGEMENT ARE SCHEMATIC. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT MANUFACTURER FOR DETAILED CONNECTION REQUIREMENTS AND PROVIDE MATERIALS AND INSTALLATION FOR A COMPLETE AND OPERATIONAL SYSTEM.
- 3. ELECTRIC HAND HOLES ARE NOT SHOWN ON THESE PLANS BUT SHALL BE REQUIRED TO MEET CODE AND AS SPECIFIED IN DIVISION 26. COORDINATE ALL FINAL LOCATIONS WITH ENGINEER.

SUMMARY OF ELECTRICAL AND CONTROLS WORK BY PROCESS AREA:

AREA 100 - 2W SYSTEM:
 CONSTRUCTION OF NEW ENCLOSURE FOR 2W BLADDER TANKS AND PRESSURE SENSOR. PROVIDE NEW RECEPTACLE AND HEAT TAPE FOR EXPOSED WATER PIPING. RELOCATE PRESSURE SENSOR TO NEW LOCATION AS SHOWN ON CIVIL

AREA 200 - INFLUENT:

PROVIDE UPGRADES TO EXISTING INFLUENT CONTROL PANEL INCLUDING NEW DIGITAL DISPLAY IN INFLUENT CONTROL PANEL FOR TRAIN NO.1 FLOW DISPLAY, PANEL MODIFICATIONS AND NEW AC UNIT.

AREA 500 - BIOSOLIDS FACILITY:
 CONSTRUCTION OF NEW DEWATERING BUILDING INCLUDING POWER AND LIGHTING, VENTILATION SYSTEM, PLC CONTROL PANEL, NEW ELECTRICAL PANELS AND TRANSFORMER, GAS SENSORS AND OTHER ITEMS SHOWN ON THE PLANS.

AREA 800 - CONTROL BUILDING:

• ELECTRICAL UPGRADES FOR LAB RENOVATION INCLUDING NEW CABINETRY, LAB EQUIPMENT AND POWER RECEPTACLES.

NEW CIRCUIT BREAKER AND 480V FEEDER FROM EXISTING MCC TO NEW DEWATERING BUILDING.
EXTEND 480V POWER FROM EXISTING MCC TO TRAINS #1 AND #2 CONTROL PANELS.
EXTEND POWER AND CONTROL CIRCUITS TO NEW EQUIPMENT AS REQUIRED.

SCADA SYSTEM ADDITIONS FOR ALL NEW PHASE 2 PROJECT COMPONENTS.

PROVIDE ALL ELECTRICAL AND CONTROLS FOR THE COMPLETE REPLACEMENT OF TRAINS NO.1 AND NO.2 INCLUDING NEW PROVIDE ALL ELECTRICAL AND CONTROLS FOR THE COMPLETE REPLACEMENT OF TRAINS NOT. I AND NOT. INCLUDIC CLARIFIER DRIVES, MISTAKERS, INSTRUMENTATION, CONTROLS, LIGHTING AND POWER DISTRIBUTION.
INSTALL LOCAL CONTROL PANELS FROM MANUFACTURERS, POWER FEEDERS FROM MCC, CONTROL WIRING AND RACEWAY TO NEW PLC CONTROL PANEL LOCATED IN NEW DEWATERING BUILDING.









BZ

DISTRICT § ~

PHASE WATER

ELECTRICAL AREA

AND

SEWER

WASTEWATER TREATMENT PLANT UPGRADI

**EASTSOUND** AS SHOWN JOB NUMBER 2023-123

Call 811 two business days before you dig

**BID SET** 

# PROCESS AREA DESIGNATIONS

100 - 2W SYSTEM

200 - INFLUENT

300 - BIOTREATMENT SYSTEM/CLARIFIERS

400 - EFFLUENT/UV SYSTEM


500 - BIOSOLIDS FACILITIES


600 - PLANT DRAIN SYSTEM


700 - BLOWER BUILDING

800 - CONTROL BUILDING









## **GENERAL NOTES:**

- ALL CONDUIT ROUTING IS NOT SHOWN, AND WHERE SHOWN, IS SCHEMATIC. ELECTRICAL CONTRACTOR SHALL DETERMINE THE BEST ROUTING PATH AND CIRCUIT COMBINATIONS BASED ON FIELD CONDITIONS AND ELECTRICAL CODES.
- EQUIPMENT LOCATIONS AND ARRANGEMENT ARE SCHEMATIC. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT MANUFACTURER FOR DETAILED CONNECTION REQUIREMENTS AND PROVIDE MATERIALS AND INSTALLATION FOR A COMPLETE AND OPERATIONAL SYSTEM.
- PANEL AND RACEWAY RATINGS: WET AND CORROSIVE ENVIRONMENT ALL EQUIPMENT PANELS SHALL BE T316 STAINLESS STEEL NEMA 4X. SUPPORTS AND HARDWARE SHALL BE 1316 STAINLESS STEEL. EXPOSED RACEWAY INSIDE DEWATERING BUILDING AND EXTERIOR SHALL BE ALUMINUM, STAINLESS STEEL OR OCAL. ROUTE CONDUIT UNDERGROUND WHERE POSSIBLE; OVERHEAD WHERE REQUIRED.
- BRANCH CIRCUITS NOT SHOWN ON CONDUIT SCHEDULE SHALL BE SIZED AS REQUIRED BY NEC.

UH-1 UNIT HEATER

480V THREE PHASE 12.5 KW

INTEGRAL

DISCONNECT

ELECTRICAL CONTRACTOR SHALL PROVIDE THE COMPLETE INSTALLATION OF ALL HVAC ELECTRICAL EQUIPMENT AND CONTROLS AS SHOWN ON MECHANICAL SHEETS. PROVIDE DISCONNECTING MEANS WHERE INDICATED OR REQUIRED BY CODE.

## **CLASSIFIED AREA NOTES:**

DEWATERING BUILDING WITH DEWATERING PRESS: UNCLASSIFIED PER NFPA 820-2024 TABLE 6.2.2, ROW 12a WITH TYPE 'C' VENTILATION, CONTINUOUSLY VENTILATED AT 6 AIR CHANGES PER HOUR AND IN ACCORDANCE WITH NFPA 820-2024 CHAPTER 9.

## **KEY NOTES:**

- INSTALL H2S GAS DETECTOR FURNISHED IN PROJECT PHASE 1, WIRE TO DEWATERING BUILDING PLC CONTROL PANEL FOR 24VDC POWER AND 4-20 ma SIGNAL. SMC MODEL 5100-05-IT.
- INSTALL COMBUSTIBLE GAS DETECTOR FURNISHED IN PROJECT PHASE 1, WIRE TO DEWATERING BUILDING PLC CONTROL PANEL FOR 24VDC POWER AND 4-20 MA SIGNAL. DETCON MODEL FP-524D-316SS.

VENTILATION WARNING LIGHT

EF-1

EXHAUST

**FAN 120V** 

<sup>1</sup>/<sub>3</sub> HP

-C-LBN

-(C-LBS)

P-EF1

VENTILATION WARNING LIGHT BOX - SOUTH ENTRANCE

(S-AE1)

-(C-VCP)

P-DWCP

DWCP

DEWATERING BUILDING PLC CONTROL PANEL

PROVIDE NEW AIR FLOW SWITCH PER MECHANICAL. WIRE TO VENTILATION CONTROL PANEL.



7	_		
CELES WASHINGS WASHINGS	mossonel	The state of the s	01/24/2025

		SI SI SI SI SI SI SI SI SI SI SI SI SI S	01/24
DRAWN BY	BZ	CHECKED BY	BZ

Ann.				
BZ	DRAWN BY	BZ	CHECKED BY	BZ
	TON			

DISTRICT N ASI

PHASE WATER

ELECTRICAL

COUNTY WASTEWATER TREATMENT PLANT UPGRADE BUILDING

AND

SEWER **EASTSOUND** 

9

П

Call 811 two business days before you dig

**BID SET** 

TOXIC GAS DETECTOR (H2S) 1

EXPLOSIVE GAS (2) DETECTOR

EXHAUST FAN

DISCONNECT VCP

VENTILATION CONTROL PANEL

LPDW

HPDW POWER PANEL 480V 3 PHASE

LIGHTING PANEL

(P-VCP)-

DEWATERING BUILDING - HVAC ELECTRICAL PLAN

HEATER THERMOSTAT INSTALL PER MECHANICAL



C-AFS

P-UH1

C-UH1

L-1

INTAKE

LOUVER

SCALE: 1" =2' AT FULL SCALE					
2	Q	2	4		
SCALE			FEET		

1)12

- 1. ROUTE ALL BRANCH CIRCUITS TO LIGHTING PANEL(S) CIRCUIT SHOWN ON THE PLANS. ALL CONDUIT ROUTING IS NOT SHOWN. ELECTRICAL CONTRACTOR SHALL DETERMINE THE BEST ROUTING PATH AND CIRCUIT COMBINATIONS BASED ON FIELD CONDITIONS AND ELECTRICAL CODE.
- 2. BRANCH CIRCUITS NOT SHOWN ON CONDUIT SCHEDULE SHALL BE SIZED AS REQUIRED BY NEC.

# WASHINGTON STATE ENERGY CODE NOTES:

- INTERIOR POWER ALLOWANCE FOR WORKSHOP DESIGNATION: GROSS INTERIOR AREA=650 SF. LIGHTING POWER ALLOWANCE=0.91 W/SF. TOTAL WATTS ALLOWED (SF X LPA X 0.8)=473. TOTAL PROPOSED WATTS BY BUILDING AREA=400 ASSUMING 10 FIXTURES AT 40W EACH.
- 2. PROJECT CLOSEOUT DOCUMENTATION SHALL INCLUDE WSEC COMPLIANCE REPORTS PER WSEC SECTION C103.6.3

# **KEY NOTES:**

LPDW

LIGHTING PANEL 208Y/120V

RE-INSTALL TWO LED WALL PACKS REMOVED DURING DEMOLITION, AND PROVIDE TWO NEW MATCHING WALL PACKS FOR NEW DEWATERING BUILDING. COORDINATE MOUNTING HEIGHTS OVER NEW DOORS BASED ON DOOR SUBMITTALS. PROVIDE PHOTOCELL ON EXTERIOR OF BUILDING FOR AUTOMATIC EXTERIOR LIGHTING CONTROL.

WIRE EMERGENCY LIGHTS TO INTERIOR LIGHTING CIRCUIT.

PROVIDE DUAL TECHNOLOGY OCCUPANCY SENSORS FOR INTERIOR LIGHTING, QUANTITY AND LOCATIONS AS REQUIRED TO COVER ALL OCCUPIED AREAS. COMPLY WITH WASHINGTON STATE ENERGY CODE REQUIREMENTS.

PROVIDE NEW V-HOOK AND SUSPENDED MOUNTING OPTIONS FOR EXISTING LED STRIP FIXTURES REMOVED DURING DEMOLITION. RE-INSTALL LED STRIP LIGHTS IN NEW DEWATERING BUILDING. COORDINATE MOUNTING LOCATIONS TO AVOID ROLL UP DOOR, VENTILATION DUCTWORK AND OTHER EQUIPMENT. ALL HARDWARE SHALL BE STAINLESS STEEL.







DISTRICT

**SEWER AND WATER** 

**EASTSOUND** 


N AS


PHASE

COUNTY WASTEWATER TREATMENT PLANT UPGRADE

LIGHTING


BUILDING






<u>(1)</u>

⊗ os (3)



DEWATERING BUILDING - LIGHTING PLAN





**BID SET** 

AS SHOWN JOB NUMBER 2023-123 6 П

TYPE OF EQUIPMENT/INSTRUMENT	MANUFACTURER	MODEL NUMBER	PURCHASED?	DEPTH (IN)	WIDTH (IN)	HEIGHT (IN)	ELECTRICAL	MECHANICAL	COMMENTS
PH PROBE	HACH	PHC101	4/1/2023				N/A	N/A	
COLORIMETER/SPECTROPHOT	<b>ФМ</b> АВн	DR300	1/1/2020				BATTERY POWERED	N/A	
ANALYTICAL BALANCE	METTLER TOLEDO	XS 104	1/23/2020	12.7	10.4	17.8	N/A	N/A	REQUIRES SOLID BASE AND "CALM" ENVIRONMENT.
DO PROBE	HACH	LBOD1Ø1	6/1/2023				N/A	N/A	
DO/PH METER	HACH	HQ2200	6/1/2023				N/A	N/A	
DRYING OVEN	QUINCY LAB	20GC	9/1/2022				115 V, 60 HZ, 6.95 A	N/A	
FUME HOOD	LABCONCO	224660	Q4 2023	25	47	54	115 VOLTS, 60 HZ, 1 A, DOMESTIC	VERIFY	
SPECTROPHOTOMETER	HACH	DR6000 UV VIS	PHASE I	18.1	19.7	8.5	110-240 VAC, 60 HZ	N/A	
BOD INCUBATOR	THERMO SCIENTIFIC	PR205745R	PHASE II	24.5	24	34.5	115 V, 60 HZ, 9.5 A, NEMA 5-15 PLUG	N/A	UNDER-COUNTER MODEL.
FECAL COLIFORM INCUBATOR	THERMO SCIENTIFIC	TSCOL19	PHASE II	15.5	24.9	9.8	120/230 V, 60 HZ, 9-10.5 A	N/A	NEEDS TO INCLUDE SS PETRI DISH RACK.
AUTOCLAVE	TUTTNAUER	2340M	PHASE II	21.5	20	14.4	120 V, 60HZ, 12 A	VERIFY	
REFRIGERATOR	THERMO SCIENTIFIC	TSV18CPSA	PHASE II	32.79	29.53	66.61	115 V, 60 HZ, 1.1 A	VERIFY	MIN CLEARANCES 4 IN. ON SIDES, 4 IN. AT BACK, 11 IN. ON TOP.
STILL	THERMO SCIENTIFIC	MP-1	PHASE II	9.75	18	34	120 V, 60 HZ, 9 A	WATER AND DRAIN CONNECTION	
MICROSCOPE	OLYMPUS	CX33 W/ EP50 CAMERA SYSTEM	PHASE II	8.3	15.6	17	N/A	N/A	
MUFFLE FURNACE	THERMO SCIENTIFIC	FB1315M	PHASE II	13	9	14	120 V, 60 HZ, 8.9 A	VERIFY	
DESSICATOR	NALGENE	38090	PHASE II	12	12	18	N/A	N/A	FITS 230 MM DESICATOR PLATE.
GLASSWARE WASHER	LABCONCO	401001000	PHASE II	27.7	24.1	32.1-36	115 V, 60 HZ, 16 A, 1P	VERIFY	REQUIRES DEDICATED 20A CIRCUIT.
STANDING DESK (X2)	UPLIFT	UPL922-MAPLE 48x30	PHASE II	30	48	22.6-48.7	100-240 V, 60 HZ, 400W MAX	N/A	V2-COMMERCIAL C-FRAME

		OFFICE PANEL 208Y/120V 3-PH,4W 125A SQ-D NQOB 30 CKT
<b>⊕</b> -SCALE	ABOVE COUNTER GFCI STRIP RECEPTACLE (TYP OF 3)  SCADA SYSTEM MONITOR  SCADA SYSTEM MONITOR  STANDING WORKSTATION  STANDING WORKSTATION	
EXISTING MUF- FUME HOOD FURN DRYING OVEN	STAINLESS COUNTER INCUBATOR  DISHWASHER  DISTILLER  DISTILLER  DISTILLER  DISTILLER  DISTILLER  DISTILLER  DISTILLER  DISTILLER	

- 1. ROUTE ALL BRANCH CIRCUITS TO LIGHTING PANEL(S) CIRCUIT SHOWN ON THE PLANS. ALL CONDUIT ROUTING IS NOT SHOWN, ELECTRICAL CONTRACTOR SHALL DETERMINE THE BEST ROUTING PATH AND CIRCUIT COMBINATIONS BASED ON FIELD CONDITIONS AND ELECTRICAL CODE.
- 2. BRANCH CIRCUITS NOT SHOWN ON CONDUIT SCHEDULE SHALL BE SIZED AS REQUIRED BY NEC.

# **KEY NOTES:**

PANEL · OFFICE

208Y/120V, 3Ph, 4W

DESCRIPTION /

LOCATION

OFFICE LIGHTS - NORTH (5)

OFFICE RECEPTACLES - SOUTH

LAB LIGHTS (7)

11 NEW - DISHWASHER

17 NEW - DISTILLER

21

23

27

19 NEW - AUTOCLAVE

13 NEW - STANDING DESK X2

15 NEW - MUFFLE FURNACE

**NEW - INCUBATOR** 

SCADA MONITOR

**NEW - REFRIGERATOR** 

TOTAL CONNECTED LOAD:

TOTAL CONNECTED LOAD:

TOTAL CONNECTED LOAD:

G GENERAL (NON-CONTINUOUS)

C CONTINUOUS (GENERAL LOAD)

R RECEPTACLES - ≥ 10 kVA

< 10 kVA

LM LARGEST MOTOR

WH WATER HEATER

N NON-COINCIDENT

TOTAL

K KITCHEN

H HEATING

M MOTORS

MAX PHASE CONNECTED LOAD:

TOTAL CONNECTED LOAD (3 x MAX):

25 NEW - DRYING OVEN

SPARE

- ROUTE NEW POWER CIRCUITS FROM EXISTING OFFICE PANEL TO NEW AND EXISTING RECEPTACLE LOCATIONS. ROUTE RACEWAY OVERHEAD IN CRAWL SPACE AND INSIDE WALLS; ALL ELECTRICAL RACEWAY SHALL BE CONCEALED.
- 2 ADD NEW CIRCUIT BREAKERS TO EXISTING PANEL FOR NEW LABORATORY CIRCUITS AND EXTEND TO NEW RECEPTACLES IN LAB AREA. LOAD CALC EXISTING= 10.8 kVA 30.1A, AFTER 19.2 kVA 53.4A.
- PROVIDE ETHERNET DATA PORTS IN LOCATIONS INDICATED ON PLANS. ROUTE CAT6 CABLING TO NETWORK SWITCH IN OFFICE. COORDINATE FINAL LOCATIONS WITH OWNER DURING CONSTRUCTION.
- PROVIDE THREE NEW ABOVE-COUNTER STRIP RECEPTACLES FOR GENERAL PURPOSE USE. 120VAC, 8-10 OUTLETS EACH, ALUMINUM HOUSING, PLASTIC END CAPS, BUILT IN CIRCUIT BREAKER. WIRE TO NEW GFCI RECEPTACLE TO EXISTING PANEL RECEPTACLE CIRCUIT.
- \$\frac{5}{5}\$ SYSTEM INTEGRATOR SHALL PROVIDE NEW REMOTE SCADA MONITOR PER SPECIFICATIONS FOR INSTALLATION IN THE LAB. PROVIDE 120VAC POWER AND HDMI DATA PROVISIONS FOR SCADA SYSTEM REMOTE MONITOR. COORDINATE FINAL LOCATIONS WITH OWNER DURING CONSTRUCTION.

LOAD

(VA)

320

448

900

1,920

800

1,068

1,080

1.440

1,140

180

834

132

CONNECTED

LOADS

6,994 VA

4.608 VA

7,440 VA

6,994 VA

8.414 VA

768 VA

0 VA

0 VA

0 VA

0 VA

0 VA

0 VA

0 VA

21.0 kVA

PH A

PH B

PH C

G

G

G

G

G

R

G

G

C.B.

20

20

20

20

20

20

20

20

20

20

20

20

20

SUBFED

LOADS [S]

POLE

1

1

1

58.3 AMPS

38.4 AMPS

62.0 AMPS

58.3 AMPS

0 VA

PANEL SCHEDULE

В

С

Α В

С

Α

В

С

С

Α

TOTAL

LOADS

8.414 VA

768 VA

9,860 VA

0 FICE PANEL SCHEDULE SCALE: 1" = 2' AT FULL SCALE

100A M.C.B

C.B.

AMP

20

20

20

20

20

20

20

20

20

DEMAND

FACTOR

100%

125%

100%

50%

100%

100%

100%

125%

125%

LOAD

TYPE

R

R

R

900

720

1.560

900

1,800

1,800

1,100

180

PANEL RATING:

TOTAL DEMAND LOAD:

DEMAND

LOAD

8.414 VA

960 VA

9,860 VA

0 B.

POLE

-	WE TISTORIO	-	DITTE
0.	REVISIONS	BY	DATE

PROJECT: Fastsound WWTP

FLUSH MOUNTED

DESCRIPTION /

LOCATION

RECEPTACLES - LAB SOUTH, POWER STRIP

RECEPTACLES - LAB - BLOWER, DISH, WATER

RECEPTACLES - OFFICE (5)

RECEPTACLES - OFFICE (2) LAB (2)

RECEPTACLES - LAB - OVEN, WORK

RECEPTACLE - REFRIGERATOR

RECEPTACLE - SPECTROPHOTOMETER

10,000 AIC

19.2 kVA

RECEPTACLE - INCUBATOR





12 1 1 2 1 E	Jang Jang	99, 620 1875 1875 1875 1875 1875 1875 1875 1875
ВУ	<b>&gt;</b>	<u></u>

1 100			TO SEE	01/24
BZ	DRAWN BY	BZ	CHECKED BY	BZ

BZ	DRAWN BY	BZ	CHECKED BY	BZ
	CTON			

||§ ~

ISTRIC<sup>-</sup> PHASE Ճ SCHEDULES ER

DATE: November 27, 2024

53.4 AMPS

24

AND

AND PLAN, ELECTRICAL

COUNTY WASTEWATER TREATMENT PLANT UPGRADE SEWER LABORATORY **EASTSOUND** 

01-24-2025 SCALE AS SHOWN JOB NUMBER 2023-123


9 Q.

ш

Call 811 two business days before you dig

**BID SET** 

LABORATORY ELECTRICAL PLAN AND SCHEDULES SCALE: 1" = 2' AT FULL SCALE



# TRAINS NO.1 AND 2 - ELECTRICAL PLAN AND ELEVATION (TYP OF 2)

SUBMERSIBL

MIXER MOTOR



-SUBMERSIBLE

MIXER MOTOR

# **GENERAL NOTES:**


- ALL CONDUIT ROUTING IS NOT SHOWN, AND WHERE SHOWN, IS SCHEMATIC. ELECTRICAL CONTRACTOR SHALL DETERMINE THE BEST ROUTING PATH AND CIRCUIT COMBINATIONS BASED ON FIELD CONDITIONS AND ELECTRICAL CODES
- EQUIPMENT LOCATIONS AND ARRANGEMENT ARE SCHEMATIC. CONTRACTOR SHALL COORDINATE WITH EQUIPMENT MANUFACTURER FOR DETAILED CONNECTION REQUIREMENTS AND PROVIDE MATERIALS AND INSTALLATION FOR A COMPLETE AND OPERATIONAL SYSTEM
- 3. PANEL AND RACEWAY RATINGS: WET AND CORROSIVE ENVIRONMENT ALL EQUIPMENT PANELS SHALL BE T316 STAINLESS STEEL NEMA 4X. SUPPORTS AND HARDWARE SHALL BE T316 STAINLESS STEEL. EXTERIOR EXPOSED RACEWAY SHALL BE ALUMINUM
- 4 INSTALL NEW AND COMPLETE TREATMENT TRAIN ELECTRICAL AND CONTROL SYSTEM PER MANUFACTURER REQUIREMENTS. THIS INSTALL NEW AND COMPLETE TREATMENT TRAIN ELECTRICAL AND CONTROL STSTEM PER MANDFACTURER REQUIREMENTS. THIS INCLUDES CONTROL PANEL, JUNCTION BOXES MOTORS, SENSORS, SWITCHES AND ALL OTHER EQUIPMENT REQUIRED BY THE MANUFACTURER. PROVIDE MOTOR DISCONNECTS AS REQUIRED BY CODE. THE QUANTITY AND SIZE OF RACEWAY AND CONDUCTORS IS ESTIMATED. THE CONTRACTOR SHALL ADJUST AS NECESSARY BASED ON EQUIPMENT MANUFACTURER SUBMITTALS AND PROVIDE A COMPLETE AND OPERATIONAL INSTALLATION

## KEY NOTES:

- 1 TREATMENT SYSTEM PROVIDER SHALL PROVIDE COMPLETE TREATMENT SYSTEM PER SPECIFICATIONS. CONTROL PANEL SHALL ACCEPT 480V 3 PHASE 30A INPUT AND INCLUDE ALL WIRING AND CONTROLS FOR THE COMPLETE TREATMENT SYSTEM. FEATURES SHALL INCLUDE BUT NOT BE LIMITED TO:
  - NEMA 4X TYPE 316 STAINLESS STEEL ENCLOSURE SIZED FOR THE APPLICATION. INCLUDE DRIP SHIELD FOR OUTDOOR PANELS.
  - NEMA FULL VOLTAGE MOTOR STARTERS FOR BOTH CLARIFIER DRIVE MOTOR AND TWO SUBMERSIBLE MIXERS SEAL FAIL AND OVERTEMP SENSOR FOR SUBMERSIBLE MOTOR PROTECTION.
  - 480-120V 5 kVA T316SS STEP DOWN TRANSFORMER FOR CONTROL CIRCUITS. MOUNT NEAR CONTROL PANEL
  - 4601-120V 5 KW 1505S STEP DOWN TRANSPORMER FOR CONTROL LIRCUITS. MOUNT NEA HARD WIRED RELAY LOGIC CONTROL CIRCUITS FOR SYSTEM CONTROL AND PROTECTION. ALARM LIGHT AND HORN WITH SILENCE PUSH BUTTON. INDICATOR LIGHTS, PUSH BUTTONS, HAND-OFF-AUTO SWITCHES FOR MOTOR CONTROL.

  - WIRING TERMINALS FOR FIELD MOUNTED DEVICES INCLUDING TORQUE SWITCHES, LIMIT SWITCHES, SOLENOIDS AND ANY OTHER REQUIRED DEVICES.

    DRY RELAY CONTACTS FOR CUSTOMER CONNECTION INCLUDING: RUN AND FAIL FOR EACH MOTOR, SEAL FAIL AND OVERTEMP
  - FOR MIXER, ALARM AND SHUTDOWN FOR CLARIFIER.
    PANEL HEATER WITH FAN TO PREVENT BUILDUP OF CONDENSATION IN PANEL.
    120V CIRCUITS FOR POLE LIGHT AND RECEPTACLE.
- 12. NEMA 4X T316 SS JUNCTION BOXES FOR INTERCONNECTION OF FIELD DEVICES.
- ALL PANELS AND COMPONENTS SHALL BE UL LISTED.
- 2 ELECTRICAL CONTRACTOR SHALL PROVIDE LOCAL MOTOR DISCONNECTS FOR DRIVE MOTOR AND MIXERS. NEMA 4X TYPE 316 STAINLESS STEEL OR FIBERGLASS.
- 3) ROUTE SEAL FAIL AND OVERTEMP MOTOR WIRING BACK TO CONTROL PANEL SENSOR. COMBINE WIRING IN CONTROL RACEWAY AS REQUIRED
- 4 CONTRACTOR SHALL INSTALL ALL TREATMENT SYSTEM COMPONENTS PROVIDED BY MANUFACTURER AND PROVIDE WIRING AND RACEWAY BACK TO TREATMENT CONTROL PANEL. RATINGS, RACEWAY AND CONDUCTORS SHOWN ARE ESTIMATED; ADJUST DURING SUBMITTAL PERIOD BASED ON TREATMENT SYSTEM EQUIPMENT SUBMITTAL REQUIREMENTS.
- 5 CONTRACTOR SHALL PROVIDE POLE LIGHT ON PLATFORM TO MATCH TRAIN NO.3. SECURE TO HANDRAIL WITH STAINLESS STEEL HARDWARE. PROVIDE 4" SQUARE ALUMINUM POLE 12' TALL WITH RECEPTACLE, PHOTOCELL AND LOCAL ON/OFF SWITCH. LITHONIA LIGHTING #DSX0-LED-P3-30K-T3M-MVOLT-SPA-DNAXD WITH PHOTOCELL, OR APPROVED EQUAL.
- 6 PROVIDE (2) COMPLETE DISSOLVED OXYGEN MONITORS FOR EACH TRAIN. MOUNT TO TOP OF WALL WITH FACTORY HARDWARE TO ALLOW FOR TRANSMITTER ACCESS AND CLEANING. HACH MODEL LDO PROBE WITH SC4500 TRANSMITTER AND ACCESSORIES. SEE SPECIFICATIONS.
- 7 PROVIDE JUNCTION BOXES AS REQUIRED TO ROUTE ALL POWER AND SIGNAL CIRCUITS TO TRAIN CONTROL PANEL AND PLC ENOUGH DUNCHION DUACS AS REQUIRED TO ROUTE ALL POWER AND SIGNAL CIRCUITS TO TRAIN CONTROL PANEL AND PLC CONTROL PANEL. MAINTAIN SEPARATION OF AC AND DC SIGNAL CIRCUITS. CONDUIT ROUTING AND CIRCUIT COMBINATIONS SHALL BE FIELD-LOCATED BY CONTRACTOR.
- (8) STUB SPARE CONDUITS ABOVE GROUND NEAR TREATMENT CELL WALLS. CAP FOR FUTURE USE.
- 9) PROVIDE 20A 120V GFCI RECEPTACLE FOR CARBON FEED POWER. MOUNT TO S.S UNISTRUT SUPPORT ATTACHED TO TREATMENT CELL WALL. WET LOCATION IN-USE COVER. SEE SITE PLANS FOR LOCATIONS







**BID SET** 

田 

Z Ð



BZ

STRICT 7

PHASE ELEVATION PLANT UPGRADE PLAN ELECTRICAL TREATMENT

Ճ

ER

AND

SEWER AND **EASTSOUND** WASTEWATER NO.1

AS

Ġ

ш

# CABLE LEGEND

AC CONDUIT AND WIRING

DC CONDUIT AND WIRING

## **KEY NOTES:**

- M DEVICE FURNISHED BY TREATMENT SYSTEM MANUFACTURER FOR CONTRACTOR INSTALLATION.
- DEVICE FURNISHED AND INSTALLED BY CONTRACTOR BASED ON TREATMENT SYSTEM MANUFACTURER REQUIREMENTS AND CONTRACT DOCUMENTS. (c)
- E EXISTING EQUIPMENT
  - NOTE: ALL CONDUIT AND WIRING PROVIDED BY CONTRACTOR

NOTE: PROVIDE EQUIPMENT GROUNDING CONDUCTOR IN ALL RACEWAY, SIZE PER NEC.

# **GENERAL NOTES:**

1. INSTALL NEW AND COMPLETE TREATMENT TRAIN ELECTRICAL AND CONTROL SYSTEM PER MANUFACTURER REQUIREMENTS. THIS INCLUDES CONTROL PANEL, JUNCTION BOXES MOTORS, SENSORS, SWITCHES AND ALL OTHER EQUIPMENT REQUIRED BY THE MANUFACTURER. PROVIDE MOTOR DISCONNECTS AS REQUIRED BY CODE. THE QUANTITY AND SIZE OF RACEWAY AND CONDUCTORS IS ESTIMATED. THE CONTRACTOR SHALL ADJUST AS NECESSARY BASED ON EQUIPMENT MANUFACTURER SUBMITTALS AND PROVIDE A COMPLETE AND OPERATIONAL INSTALLATION.

2. THE INTERCONNECTION DIAGRAM ON THIS SHEET IS SCHEMATIC AND IS INTENDED TO SHOW LIMITED DETAILS FOR THE INTERCONNECTION OF THE TREATMENT SYSTEM COMPONENTS. CONTRACTOR SHALL CONFIRM ALL INSTALLATION REQUIREMENTS AND PROVIDE THE ELECTRICAL INSTALLATION FOR A COMPLETE AND OPERATIONAL SYSTEM AS REQUIRED BY THE EQUIPMENT MANUFACTURER AND THE CONTRACT DOCUMENTS.





BZ

∛ ∧

PHASE

COUNTY WASTEWATER TREATMENT PLANT UPGRADE

INTERCONNECTION DIAGRAM

AND

NO.1

AS SHOWN JOB NUMBER 2023-123

6

DISTRICT

WATER


AND

SEWER


**EASTSOUND** 

 $\infty$ 

ш







NO.	REVISIONS	BY	DATE



ID	VOLTAGE	CONDUIT	WIRE QTY	SIZE	GND	FROM	то	NOTES
P-UH1	480V	1"	3	#12 AWG	#12 AWG	POWER PANEL 'HPDW'	DEWATERING BUILDING UNIT HEATER	
P-DWP	480V	1"	3	#12 AWG	#12 AWG	DEWATERING SUMP STARTER PANEL	DEWATERING SUMP MOTOR - 1.8 HP	
P-DSP	480V	1"	3	#12 AWG	#12 AWG	480V POWER PANEL 'HPDW'	DEWATERING SUMP STARTER PANEL	
P-HPDW	480V	1"	3	#3 AWG	#8 AWG	NEW MCC BREAKER	DEWATERING BUILDING NEW PANEL 'HPDW'	
P-TCP1	480V	1"	3	#10 AWG	#10 AWG	EXISTING MCC BREAKER	TRAIN NO.1 CONTROL PANEL	480V 30AMP FEEDER
P-TCP2	480V	1"	3	#10 AWG	#10 AWG	EXISTING MCC BREAKER	TRAIN NO.2 CONTROL PANEL	480V 30AMP FEEDER
P-LLCP	480V	1"	3	#10 AWG	#10 AWG	480V POWER PANEL 'HPDW'	LEVEL LODOR CONTROL PANEL	480V 30AMP FEEDER
P-HSM	480V	1"	3	#12 AWG	#12 AWG	LEVEL LODOR CONTROL PANEL	HOIST MOTOR AND DISCONNECT	
P-C1M	480V	1"	3	#12 AWG	#12 AWG	LEVEL LODOR CONTROL PANEL	CONVEYOR MOTOR AND DISCONNECT	
P-LLM	480V	1"	3	#12 AWG	#12 AWG	LEVEL LODOR CONTROL PANEL	LEVEL LODOR MOTOR AND DISCONNECT	
P-TDW	480V	1"	3	#6 AWG	#10 AWG	480V POWER PANEL 'HPDW'	TRANSFORMER 'TDW'	480V-208Y/120V 30 KVA
P-LPDW	208/120V	1-1/2"	4	#1 AWG	#8 AWG	TRANSFORMER 'TDW'	LIGHTING PANEL 'LPDW'	100A PANEL FEED
P-VSP	208V	1"	3	#12 AWG	#12 AWG	LIGHTING PANEL 'LPDW'	EXISTING VERTICAL SCREW PRESS	EXISTING, REDUNDANT SPARE
P-PFP	120V	1"	2	#12 AWG	#12 AWG	LIGHTING PANEL 'LPDW'	POLYMER FEED PUMP RECEPTACLE	
P-VCP	120V	1"	2	#12 AWG	#12 AWG	LIGHTING PANEL 'LPDW'	VENTILATION CONTROL PANEL	
P-DWCP	120V	1"	2	#12 AWG	#12 AWG	LIGHTING PANEL 'LPDW'	DEWATERING BLDG PLC CONTROL PANEL	
P-EF1	120V	1"	2	#14 AWG	#14 AWG	VENTILATION CONTROL PANEL	EXHAUST FAN AND DISCONNECT	
P-2WS	120V	1"	2	#12 AWG	#12 AWG	MCC LIGHTING PANEL - GFEP	2W RECEPTACLE IN ENCLOSURE	FOR HEAT TRACE
P-CFS1	120V	1"	4	#12 AWG	#12 AWG	MCC LIGHTING PANEL	CARBON FEED STATION NO.1 RECEPTACLE	FEED PUMP
P-CFS2	120V	1"	2	#12 AWG	#12 AWG	MCC LIGHTING PANEL	CARBON FEED STATION NO.2 RECEPTACLE	FEED PUMP
P-ISMP	120V	1"	2	#12 AWG	#12 AWG	PANEL 'LPDW'	INFLUENT SAMPLER RECEPTACLE	INFLUENT SAMPLER POWER
P-AFS1	120V	1"	2	#12 AWG	#12 AWG	PANEL 'LPDW'	ALKALINITY FEED STATION RECEPTACLE	FEED PUMP
SPARE	AC	1"			PULL STRING	AS INDICATED	AS INDICATED	

# POWER SCHEDULE SCALE: NONE

ID	VOLTAGE	CONDUIT	WIRE QTY	SIZE	GND	FROM	то	DESCRIPTION
C-AFS	120VAC	1"	2	#14 AWG	#14 AWG	AIR FLOW SWITCH	VENTILATION CONTROL PANEL	N.C. CONTACT FOR AIR FLOW STATUS
C-UH1	24VDC	1"	AS REQ'D	AS REQ'D	AS REQ'D	THERMOSTAT	UNIT HEATER	THERMOSTAT CONTROL WIRING
C-LBN	24VDC	1"	4	#14 AWG	#14 AWG	VENTILATION CONTROL PANEL	LIGHT BOX - DEWATER BLDG NORTH DOOR	INDICATOR LIGHTS
C-LBS	24VDC	1"	4	#14 AWG	#14 AWG	VENTILATION CONTROL PANEL	LIGHT BOX - DEWATER BLDG SOUTH DOOR	INDICATOR LIGHTS
C-DSP	24VDC	1"	10	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	DEWATERING SUMP STARTER PANEL	STATUS AND CONTROL SIGNALS - CONFIRM QTY
C-INT	24VDC	1/2"	4	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	DOOR INTRUSION SWITCHES	DOOR SWITCHES
C-SMK	24VDC	1/2"	4	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	SMOKE DETECTOR	DETECTOR POWER AND SIGNAL
C-LL	120VAC	1"	AS REQD	PER MANUF	PER MANUF	MOTION, TORQUE, ESTOP AS REQ'D	LEVEL LODOR CONTROL PANEL	CONTROL WIRING AS REQ'D BY MANUFACTURER
C-TCP1A	120VAC	1"	12	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	TRAIN NO.1 CONTROL PANEL	120V AC RELAY SIGNALS FOR AUTO CONTROL
C-DWP	120VAC	1"	6	#14 AWG	#14 AWG	DEWATERING SUMP FLOAT SWITCHES	DEWATERING SUMP STARTER PANEL	FLOAT SWITCHES
C-TCP1D	24VDC	1"	16	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	TRAIN NO.1 CONTROL PANEL	S&L RELAYS - DC INPUT STATUS SIGNALS
C-TCP2A	120VAC	1"	12	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	TRAIN NO.2 CONTROL PANEL	120V AC RELAY SIGNALS FOR AUTO CONTROL
C-TCP2D	24VDC	1"	16	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	TRAIN NO.2 CONTROL PANEL	S&L RELAYS - DC INPUT STATUS SIGNALS
C-VCP	24VDC	1"	4	#14 AWG	#14 AWG	VENTILATION CONTROL PANEL	DEWATERING BLDG PLC CONTROL PANEL	VENTILATION PANEL STATUS TO PLC
			1	#18TSP	SHIELD	VENTILATION CONTROL PANEL	DEWATERING BLDG PLC CONTROL PANEL	VENTILATION MOTOR AMPS
S-AE1	24VDC	1"	4	#14 AWG	#14 AWG	DEWATERING BLDG PLC CONTROL PANEL	GAS DETECTORS	24VDC POWER TO SENSORS
			2	#18TSP	SHIELD	DEWATERING BLDG PLC CONTROL PANEL	GAS DETECTORS	GAS LEVEL 4-20 MA SIGNALS TO PLC
S-2WPT	24VDC	1"	1	#18TSP	SHIELD	2W SHELTER PRESSURE SENSOR	BLOWER BUILDING MAIN PLC CONTROL PANEL	RELOCATED SENSOR
S-LL	24VDC	1"	AS REQD	PER MANUF	PER MANUF	LEVEL SENSOR	LEVEL LODOR CONTROL PANEL	FM RATED FOR CLASS I, DIV2
S-DO1	24VDC	1"	4	#18TSP	SHIELD	DEWATERING BLDG PLC CONTROL PANEL	DO TRANSMITTERS -TRAIN 1	BASINS DO, SPARES FOR FUTURE Ph
S-TCP1	24VDC	1-1/2"	12	#18TSP	SHIELD	DEWATERING BLDG PLC CONTROL PANEL	ANALOG I/O TO TRAIN 1 DEVICES	2-DO, 2-BV1, 2-BV2, 2-DO2BV, 2-WEIR LEVEL, 2-SPARE
S-DO2	24VDC	1"	4	#18TSP	SHIELD	DEWATERING BLDG PLC CONTROL PANEL	DO TRANSMITTERS -TRAIN 2	BASINS DO, SPARES FOR FUTURE Ph
S-TCP2	24VDC	1-1/2"	12	#18TSP	SHIELD	DEWATERING BLDG PLC CONTROL PANEL	ANALOG I/O TO TRAIN 2 DEVICES	2-DO, 2-BV1, 2-BV2, 2-DO2BV, 2-WEIR LEVEL, 2-SPARE
E-DWCP	24VDC	1"	1	CAT6	SHIELD	DEWATERING BLDG PLC CONTROL PANEL	BLOWER BUILDING MAIN PLC CONTROL PANEL	NETWORK CONNECTION
E-LLCP	24VDC	1"	1	CAT6	SHIELD	DEWATERING BLDG PLC CONTROL PANEL	LEVEL LODOR CONTROL PANEL	NETWORK CONNECTION
SPARE	DC	1"			PULL STRING	AS INDICATED	AS INDICATED	

 $\underbrace{ \text{CONTROL AND SIGNAL SCHEDULE}}_{\text{SCALE: NONE}}$ 



**BID SET** 

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2 EASTSOUND SEWER AND WATER DISTRICT CONDUIT AND CONDUCTOR SCHEDULES DATE
01-24-2025
SCALE
AS SHOWN
JOB NUMBER
2023-123 oF 91 E6.1 78

PROJECT: EASTSOUND WWTP - PHASE 2

SURFACE MOUNTED

DESCRIPTION /

LOCATION

GENERATOR - HEATER AND BATTERY CHGR

DATE: JANUARY 22, 2025

80.4 AMPS

MAIN CONTROL PANEL

HOT BOX 1 - GFEP

HOT BOX 2 - GFEP

EFFLUENT SAMPLER

HYPOCHLORITE FEED PUMP

10.000 AIC

19.3 kVA

SPARE

SPACE

SPACE

SPACE

BLOWER BUILDING LIGHTING

123 Ohme Garden Rd, Suite C1 Wenatchee WA 98801

ENGINEER (123 Ohme Garden Rd, Suit Wenatchee, WA 98801
--

١	
	Control of the contro

TO SO WAS	6		A STANDOLSTER	TANO!
BZ	DRAWN BY	BZ	CHECKED BY	BZ

•	4	1	•	
79	DRAWN BY	BZ	CHECKED BY	BZ
	NOT			

# DISTRICT

PHASE SEWER AND WATER

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE SCHEDULES ELECTRICAL PANEL

**EASTSOUND** 

AS SHOWN JOB NUMBER 2023-123 91 Q.

01-24-2025 SCALE E6.

**KEY NOTES:** 

PANEL: LP1 - BLOWER BUILDING MCC

120/240V, 1Ph, 3W.

DESCRIPTION /

LOCATION

BLOWER ROOM RECEPTACLES

9 UV1 POWER

UV2 POWER

13 UV1 CONTROLLER

UV2 CONTROLLER

LOUVER AND HVAC CONTROL

CARBON FEED STATION TRAIN 1

CARBON FEED STATION TRAIN 3

19 CARBON FEED STATION TRAIN 2

23 2W SHELTER RECEPTACLE

TOTAL CONNECTED LOAD:

TOTAL CONNECTED LOAD:

MAX PHASE CONNECTED LOAD:

TOTAL CONNECTED LOAD (2 x MAX):

TOTAL CONNECTED LOAD (3 x MAX):

EXHAUST FAN EF-1 (BLOWER BUILDING)

EXHAUST FAN EF-2 (BLOWER BUILDING)

1> MCC AND PANEL HPDW 100A 480V BREAKER SHALL BE UL489 WITH 75 DEG C LUGS. BLOWER VFDS SHALL BE PROGRAMMED TO OPERATE AT MAX 45 HZ ON GENERATOR POWER. 3 DEWATERING EQUIPMENT SHALL BE DISABLED FROM OPERATING ON GENERATOR POWER. EQUIPMENT IS REDUNDANT AND WILL NOT OPERATE DURING NORMAL OPERATION.

100A Bus

C.B.

AMP

20

20

20

20

30

30

20

20

20

20

20

72.1 AMPS

73.2 AMPS

73.2 AMPS

C.B.

POLE

LOAD

TYPE

R

M

М

М

С

С

R

R

LOAD

900

500

1,127

1,127

2.520

2,520

600

600

500

500

500

500

8,647 VA

8,786 VA

8.786 VA

17.6 kVA

41.6 kVA

PH A

РН В

PH B

PANEL SCHEDULE

PHASE

Α

В

Α

В

Α

В

В

Α

BLOWER BUILDING - MCC 120V PANEL 'LP1' SCHEDULE(E)

POLE

1

100A M.C.B.

20

20

20

20

20

20

C.B. C.B. LOAD LOAD

AMP TYPE

20 C 1,000

Н

G

M

PANEL RATING:

TOTAL DEMAND LOAD:

TOTAL DEMAND LOAD:

1,300

1.000

1,000

500

			LOAD CA	LCULATIONS			
EQUIPMENT	EQUIPMENT	CONNECT	ED LOAD	DEMAND	DEMAND	GENERATOR	GENERATOR
NO.	DESCRIPTION	HP/kVA	AMPS @ 480V	FACTOR	LOAD AMPS	FACTOR	LOAD AMPS
TCP-1	TRAIN 1 TREATMENT PANEL	13.3 KVA	16.0	1.00	16.0	1	16.0
TCP-2	TRAIN 2 TREATMENT PANEL	13.3 KVA	16.0	1.00	16.0	1	16.0
TCP-3	TRAIN 3 TREATMENT PANEL	13.3 KVA	16.0	1.00	16.0	1	16.0
2W-P1	2W WATER PUMP 1	5 HP	7.6	1.00	7.6	1	7.6
2W-P2	2W WATER PUMP 2	5 HP	7.6	1.00	7.6	0	0.0
IP-1	INFLUENT PUMP 1	2.7 HP	3.2	1.00	3.2	1	3.2
IP-2	INFLUENT PUMP 2	2.7 HP	3.2	1.00	3.2	0	0.0
IP-3	INFLUENT PUMP 3	5 HP	6.7	1.00	6.7	0	0.0
IP-4	INFLUENT PUMP 4	5 HP	6.7	1.00	6.7	0	0.0
BL-1	AERATION BLOWER 1 - TRAIN 1	20 HP	23.0	1.00	23.0	0.75	17.3
BL-2	AERATION BLOWER 2 - TRAIN 2	20 HP	23.0	1.00	23.0	0.75	17.3
BL-3	AERATION BLOWER 3 - TRAIN 3	20 HP	23.0	1.00	23.0	0.75	17.3
BL-4	AERATION BLOWER 4 - BACKUP	20 HP	23.0	4 0.00	0.0	0.00	0.0
DB	DIGESTER BLOWER	5 HP	5.9	1.00	5.9	1	5.9
WP-1	WAS PUMP 1	3 HP	4.8	1.00	4.8	1	4.8
WP-2	WAS PUMP 2 - SWING PUMP	3 HP	4.8	4 0.00	0.0	0	0.0
SD-1	SLUDGE PUMP	3 HP	4.8	1.00	4.8	0	0.0
DW-1	FKC DEWATERING SKID	9.4 KVA	11.3	1.00	11.3	0	0.0
LP-LAB	EXISTING LAB PANEL	20 KVA	24.0	1.00	24.0	0.50	12.0
LP-1	MCC LOAD CENTER LP1	15 KVA	18.0	1.00	18.0	1.00	18.0
LP-2	INFLUENT CONTROL PANEL LP2	5 KVA	6.0	1.00	6.0	1.00	6.0
HPDW	DEWATERING BUILDING 480V PANEL	39.1 KVA	47.0	1.00	47.0	0.50	23.5
TOTAL			301.6		273.8		180.8

# LOAD CALCULATION - 480V THREE PHASE

	PANEL: LPDW				PAN	EL SCHED	ULE				PROJECT: EASTSOUND WWTP - PHASE:	2
	208Y/120V, 3Ph, 4W.			125A Bus			1	00A M.C.E	3.		SURFACE MOUNTED	
СКТ	DESCRIPTION /	LOAD	LOAD	C.B.	C.B.		C.B.	C.B.	LOAD	LOAD	DESCRIPTION /	СКТ
NO	LOCATION	(VA)	TYPE	AMP	POLE	PHASE	POLE	AMP	TYPE	(VA)	LOCATION	NO
1	RECEPTACLES - BUILDING INTERIOR 1	540	R	20	1	Α	1	20	L	400	LIGHTING - BUILDING INTERIOR	2
3	RECEPTACLES - BUILDING INTERIOR 2	540	R	20	1	В	1	20	L	240	LIGHTING - BUILDING EXTERIOR	4
5	RECEPTACLES - BUILDING EXTERIOR 1	540	R	20	1	С	1	20			SPARE	6
7	RECEPTACLES - BUILDING EXTERIOR 2	540	R	20	1	Α	3	20	N	1,441	VERTICAL PRESS CONTROL PANEL (BACKUP)	8
9	EXISTING POLYMER FEED RECEPTACLE	180	R	20	1	В			N	1,441		10
11	DEWATERING PLC CONTROL PANEL	1,000	С	20	1	С			N	1,441		12
13	INFLUENT SAMPER STATION	500	Н	20	1	Α	1	20			SPARE	14
15	ALKALINITY FEED STATION	1,000	Н	20	1	В	1	20			SPARE	16
17	VENTILATION CONTROL PANEL (WITH EF-1)	1,500	С	20	1	С	1	20			SPARE	18
19	SPARE			20	1	Α					SPACE	20
21	SPARE			20	1	В					SPACE	22
23	SPARE			20	1	С					SPACE	24
25	SPARE			20	1	Α					SPACE	26
27	SPARE			20	1	В					SPACE	28
29	SPARE			20	1	С					SPACE	30
	TOTAL CONNECTED LOAD: PH /	3,421	VA	28.5	AMPS						DATE: JANUARY 22, 202	25
	TOTAL CONNECTED LOAD: PH I	3,401	VA	28.3	AMPS							
	TOTAL CONNECTED LOAD: PH	4,481	VA	37.3	AMPS							
	MAX PHASE CONNECTED LOAD: PH	3,421	VA						PANEL	RATING:	10,000 AIC	
	TOTAL CONNECTED LOAD (3 x MAX):	10.3	kVA	28.5	AMPS	S TOTAL DEMAND LOAD: 7.8 kVA 21.6 A		AD: 7.8 kVA 21.6 AMPS				

	PANEL: HPDW				PAN	EL SCHED	ULE				PROJECT: EASTSOUND WWTP - PHAS	E 2
	480V 3 PHASE 3 WIRE			125A Bus			1	00A M.C.E	3. 1		SURFACE MOUNTED	
CKT	DESCRIPTION /	LOAD	LOAD	C.B.	C.B.		C.B.	C.B.	LOAD	LOAD	DESCRIPTION /	скт
NO	LOCATION	(VA)	TYPE	AMP	POLE	PHASE	POLE	AMP	TYPE	(VA)	LOCATION	NO
1	MAIN BREAKER			100	3	Α	3	50	S	3,421	TRANSFORMER T-DW	2
3						В			S	3,401	480-208Y/120V 30 KVA	4
5						С			S	4,481		6
7	DEWATERING BUILDING UNIT HEATER UH-1	4,167	Н	20	3	Α	3	30	М	5,542	LEVEL LODOR CONTROL PANEL 3	8
9		4,167	Н			В			M	5,542	×	10
11		4,167	Н			С			М	5,542		12
13	DEWATERING SUMP PUMP (1.8 HP 2.6 FLA)	720	M	20	3	Α					SPACE	14
15		720	M			В						16
17		720	М			С						18

# DEWATERING BUILDING - 480V PANEL 'HPDW' SCHEDULE


50.0 AMPS



**BID SET** 

47.0 AMPS

39.1 kVA



NO.	REVISIONS	BY	DATE

SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM. ONLY MAJOR PANEL COMPONENTS ARE SPECIFIED.



SEWER AND WATER DISTRICT

**EASTSOUND** 

01-24-2025 SCALE

E7

AS SHOWN JOB NUMBER 2023-123


> о 91


8

NASH 2

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE

DEWATERING BUILDING PLC CONTROL PANEL ELEVATION





Call 811 two business days before you dig

BID SET

SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM. ONLY MAJOR PANEL COMPONENTS ARE SPECIFIED.

ZTEK





2 1 08 WASHINGTON	Simple Sound	04, 42025
ВУ	≿	ΒY

70

田 気 二

Z

WILSONENGINEERING.COM

Zž

BZ

DRAWN BY

BZ

CHECKED E


POWER WIRING DIAGRAM DISTRICT WASH PHASE 2


DEWATERING BUILDING PLC CONTROL PANEL

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE SEWER AND WATER **EASTSOUND** 

AS SHOWN JOB NUMBER 2023-123

DATE 01-24-2025 SCALE 9 Q. E7 82





**BID SET** 

1. SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM. ONLY MAJOR PANEL COMPONENTS ARE SPECIFIED.



70

2

Z

BZ DRAWN E

PHASE 2

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE

DIGITAL INPUTS

PANEL

PLC CONTROL

DEWATERING BUILDING

DISTRICT

WATER

SEWER AND

**EASTSOUND** 

01-24-2025 SCALE

 $\infty$ 

E7.

AS SHOWN JOB NUMBER 2023–123

91


Q.


83

WILSONENGINEERING.COM











16 PT 24VDC DISCRETE INPUT MODULE ALLEN BRADLEY #1769-IQ16

GENERAL FAULT ALARM

ANOXIC MIXER NO.1 FAULT

ANOXIC MIXER

CLARIFIER DRIVE OVERTORQUE

CLARIFIER DRIVE

OVERTORQUE

CLARIFIER DRIVE RUNNING

CI ARIFIER

CI ARIFIER

DI9
VENTILATION FAIL

DI10
VENTILATION ENABLED

DI8 SPARE

DI11
— SPARE

D13
— SPARE

D14
SPARE

D14
SPARE


D15 SPARE


ALARM

NO.2 FAULT

S&L TREATMENT CELL 1 CONTROL PANEL

VENTILATION PANEL





Call 811 two business days before you dig

**BID SET** 

91

Q.


85


2

E7

GENERAL NOTES:

 THESE SCHEMATICS SHOW FUNCTIONAL REQUIREMENTS OF THE PLC CONTROL PANEL. SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM.





**BID SET** 

91

P


86


9

E7



1. THESE SCHEMATICS SHOW FUNCTIONAL REQUIREMENTS OF THE PLC CONTROL PANEL. SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM.





СОМ

**GENERAL NOTES:** 

HYDROGEN SULFIDE SENSOR

+24VDC COM

24VDC FROM PLC CONTROL PANEL

METHANE GAS SENSOR

METHANE

(PPM)

+24VDC COM

24VDC FROM PLC

VENTILATION FAN

MOTOR EF-1

CURRRENT TRANSFORMER CT

(0-20A)

1. THESE SCHEMATICS SHOW FUNCTIONAL REQUIREMENTS OF THE PLC CONTROL PANEL. SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM.

4-20 mA

4-20 mA

4-20 mA

SPARE

+24VDC COM

V+ VCOM

V in 0+

I in 0+

V/I in 0-

СОМ

V in 1+

I in 1+

V/I in 1-

СОМ

V in 2+

I in 2+

V/I in 2-

СОМ

V in 3+

I in 3+

V/I in 3-

V+0 0.25A Al0+

AI0+

AIO-

СОМ

SHIELD

COM

SHIELD

AI2+

СОМ

SHIELD

AI3+

AI3-

СОМ

SHIELD

NOTE: REMOVE TERMINAL JUMPER FOR 4 WIRE DEVICE

V+3 0.25A Al3+

V+2 0.25A Al2+


V+1 0.25A Al1+

DEWATERING BUILDING PLC CONTROL PANEL - ANALOG INPUTS SCALE: NONE

**BID SET** 

91 P E7 87

1. THESE SCHEMATICS SHOW FUNCTIONAL REQUIREMENTS OF THE PLC CONTROL PANEL. SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM.







WILSONENGINEERING.COM

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2

DATE
01-24-2025
SCALE
AS SHOWN
JOB NUMBER
2023-123

E7.8

91

OF

88


DEWATERING BUILDING PLC CONTROL PANEL - ANALOG OUTPUTS

EASTSOUND SEWER AND WATER DISTRICT


	+24VDC DC COM
8 PT ANALOG OUTPUT MODULE - 1769-OF8	FUAO
+24VDC	
сом	TRAIN 1 - BV1
COM	0.25A  RAS LIQUIDLIFT L  MODULATING BALL VALVE POSITION COMMAND  120V FROM TRAIN CONTROL PANEL
l out 1+ COM	0.25A  MLR LIQUIDLIFT  MODULATING BALL VALVE POSITION COMMAND  120V FROM TRAIN CONTROL PANEL
l out 2+ COM	TRAIN 1 - DO2BV  AERATION ZONE L NO.2 D.O. CONTROL MODULATING N BALL VALVE POS FEEDBACK  TRAIN 1 - DO2BV  AERATION ZONE L 120V FROM TRAIN CONTROL PANEL
COM	0.25A  RAS LIQUIDLIFT MODULATING BALL VALVE POSITION COMMAND  OMMAND  TRAIN 2 - BV1  CONTROL PANEL
l out 4+ C	0.25A  WIR LIQUIDLIFT  MODULATING BALL VALVE POSITION COMMAND  TRAIN 2 - BV2  TRA
COM	0.25A  O.25A  O.25A  AERATION ZONE L  NO.2 D.O.  CONTROL  MODULATING N  CONTROL PANEL  BALL VALVE POS  FEEDBACK
l out 6+ COM	0.25A SPARE
lout 7+ COM	0.25A SPARE



1. THESE SCHEMATICS SHOW FUNCTIONAL REQUIREMENTS OF THE VENTILATION CONTROL PANEL. SYSTEM INTEGRATOR SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM.



# DEWATERING BUILDING VENTILATION CONTROL PANEL ELEVATION SCALE: NONE



VENTILATION WARNING LIGHT BOX -REMOTE PANELS (TYP OF 2) SCALE: NONE

# **SEQUENCE OF OPERATION:**

FROM LP

20/1

- 1. THERE IS ONE 120V 1/3 HP EXHAUST FAN TO PROVIDE CONSTANT 6 AIR EXCHANGES PER HOUR. THIS WILL DE-CLASSIFY THE BUILDING FROM CLASS I DIV 2 TO UNCLASSIFIED, PER NFPA 820 2024.
- 2. WHEN THE VENTILATION SYSTEM IS ENABLED, THE VENTILATION FAN WILL BE STARTED. THE INTAKE AND EXHAUST LOUVERS ARE NON-POWERED.

SINGLE PHASE

CURRENT TRANSDUCER

4-20mA OUTPUT

ACUAMP ACT050 OR EQUAL

(1) 0-20A

CR2

CR1-2

PLC ALARM

N.C. FLOW SWITCH (OPENS ON FLOW)

CR1-1

CRF-1

CRF-2 ~~H~~

PLC ALARM

3. A CURRENT TRANSFORMER WILL MONITOR THE RUNNING STATUS OF THE FAN MOTOR, AND AN AIR FLOW SWITCH WILL MONITOR FOR AIR FLOW. IF THE VENTILATION SYSTEM FAILS, WARNING LIGHTS AND AN ALARM HORN WILL BE ACTIVATED FOR LOCAL ALARM INDICATION.

-(CR1)

(CR2)

(TR1)

-(CRF)

MOTOR LOCAL DISCONNECT CONTROL POWER ON

VENTILATION SYSTEM **ENABLE** 

FAN RELAY - 15A RATED CONTACTS

EXHAUST FAN EF-1

TIME ON DELAY RELAY SET AT 5 SEC

VENTILATION SYSTEM FAIL RELAY

VENTILATION SYSTEM FAIL INDICATOR

VENTILATION SYSTEM

NORMAL OPERATION INDICATOR

VENTILATION NORMAL REMOTE STATION 1


VENTILATION NORMAL REMOTE STATION 2

VENTILATION ALARM HORN

VENTILATION FAIL REMOTE STATION 1

VENTILATION FAIL REMOTE STATION 2

4. THE ALARM STATUS WILL BE REMOTELY MONITORED BY THE PLC AND SCADA SYSTEM AND WILL NOTIFY THE PLANT OPERATOR OF A VENTILATION SYSTEM FAILURE ALARM.



EXHAUST FAN MOTOR AMPS TO PLC ANALOG INPUT FOR RUNNING STATUS

VENTILATION FAIL TO PLC - DIGITAL INPUT

VENTILATION ENABLED TO PLC - DIGITAL INPUT SEE I/O WIRING DIAGRAM

Call 811 two business days before you dig

**BID SET** 





DRAWN

DISTRICT **V** § 8

- PHASE WATER

**VENTILATION CONTROL** 

AND

SEWER .

**EASTSOUND** 


WASTEWATER TREATMENT PLANT UPGRADE DEWATERING BUILDING

01-24-2025 SCALE AS SHOWN JOB NUMBER 2023-123


91 Q.  $\infty$ ш 89


DEWATERING BUILDING - VENTILATION CONTROL PANEL ELEVATION AND WIRING DIAGRAM

SCALE: NONE



THESE SCHEMATICS SHOW FUNCTIONAL REQUIREMENTS OF THE PUMP STARTER PANEL. SUPPLIER SHALL PROVIDE DETAILED CONTROL PANEL DESIGN AND DOCUMENTATION FOR A COMPLETE AND OPERATIONAL SYSTEM.







O.L.

O.L. O.L.

CR-OT

CONTROL POWER XFMR 480V / 120V

HIGH LEVEL BACKUP

T2 GND

PUMP HOUSING

SEAL FAIL/OT RELAY

OVERTEMP

SEAL FAIL

RESET

1.8 SUBMERSIBLE SUMP PUMP

HTR

RUNNING

HIGH LEVEL

ETM)

OVERLOAD

-(CRH)-

HIGH LEVEL

(CR1)

-0-R-0-

-(CROT)-

-0-R-0-

CRSF

PANEL HEATER

PUMP RUNNING

OVERLOAD

HIGH LEVEL ALARM RELAY

HIGH LEVEL ALARM

AUTO PUMP CONTROL CIRCUIT

PUMP RUNNING

OVERTEMP

SEAL FAIL

SEAL FAIL OVERTEMPERATURE RELAY

DISCONNECT

SURGE SUPPRESSOR

PHASE FAIL RELAY

PUMP HIGH LEVEL FLOAT

PUMP START FLOAT

PUMP STOP FLOAT

WILSONENGINEERING.COM

BZ DRAWN F BZ CHECKED

SAN JUAN COUNTY
WASTEWATER TREATMENT PLANT UPGRADE - PHASE 2 STARTER WIRING DIAGRAM

EASTSOUND SEWER AND WATER DISTRICT

DEWATERING SUMP PUMP -

DATE 01-24-2025 SCALE AS SHOWN JOB NUMBER 2023-123

91 P E8. 90

